



**COUNCIL OF
THE EUROPEAN UNION**

Brussels, 22 November 2012

16616/12

**TDC 18
UD 297**

OUTCOME OF PROCEEDINGS

of : Working Party on Customs Union

on : 19 November 2012

Subject : Temporary suspensions of tariff duties/Opening and management of tariff quotas

- 3. Proposal for a Council Regulation amending Regulation (EU) No 7/2010 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products**
doc. 16088/12 TDC 16

The Working Party examined the content of the proposed proposal, took note of Commission's remarks and delegations' comments, and agreed¹ on the text without any amendments.

¹ FR, FI and DK delegations entered parliamentary scrutiny reservations.

4. Proposal for a Council Regulation amending Regulation (EU) No 1344/2011 suspending the autonomous Common Customs Tariff duties on certain agricultural, fishery and industrial products

doc. 16089/12 TDC 17 + REV 1 (en)

The Working Party examined the above proposal, took note of Commission's remarks and delegations' comments, and agreed² on the content with the following amendments to the Annex of the draft proposal:

- TARIC codes 3920 62 19 41 and 3920 62 19 43 are replaced by 3920 62 19 42³ and 3920 62 19 80 and 3920 62 19 82 are replaced by 3920 62 19 81⁴;
- Description for TARIC code 7019 19 10 15⁵ is changed.

The Chair concluded that delegations are invited to send linguistic comments **by 22 November 2012**, at the latest.

=====

² FR, FI and DK delegations entered parliamentary scrutiny reservations.

³ Poly(ethylene terephthalate) film, of a thickness of 18µm or more but not more than 25µm, having:

- a shrinkage of 3,4 (± 0,1) % in the machine direction (as determined by the ASTM D 1204 method at 190°C for 20 min) and
- a shrinkage of 0,3 (± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method at 190°C for 20 min).

⁴ Poly(ethylene terephthalate) film of a thickness of not more than 20 µm, coated on both sides with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 µm.

⁵ S-glass yarn of 33 tex or a multiple of 33 tex (± 13 %) made from continuous spun-glass filaments with fibres of a diameter of 9 µm (- 1 µm / + 1,5 µm).