

Brussels, 4 June 2015 (OR. en)

9357/15

Interinstitutional File: 2015/0104 (NLE)

UD 126

NOTE

From:	General Secretariat of the Council
To:	Delegations
No. Cion doc.:	ST 9001/15 + ADD 1
Subject:	Proposal for a Council Regulation amending
	Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products
	- Presidency Compromise

Delegations will find in the Annex the Presidency's Compromise text on the above draft Regulation.

9357/15 PhL/at 1
DG G 3 B

Proposal for a

Council Regulation amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

(1) It is in the interest of the Union to suspend totally the autonomous Common Customs Tariff duties on 111 products which are currently not listed in Annex I to Council Regulation (EU) No 1387/2013¹. Those new products should, therefore, be inserted into that Annex.

Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

- (2) It is no longer in the interest of the Union to maintain the suspension of autonomous Common Customs Tariff duties on 15 of the products that are currently listed in Annex I to Regulation (EU) No 1387/2013. Those products should, therefore, be deleted from that Annex.
- (3) It is necessary to modify the product descriptions of 30 suspensions included in Annex I to Regulation (EU) No 1387/2013 in order to take account of technical product developments, economic trends on the market or to carry out linguistic adaptations. Moreover, following further scrutiny of the products specifications, CN codes for twoadditional products should be amended. The suspensions in respect of which modifications are necessary should be deleted from the list of suspensions in Annex I to Regulation (EU) No 1387/2013, and the modified suspensions should be reinserted into that list.
- (4) In the interest of clarity, the modified entries should be marked with an asterisk.
- (5) In order to allow an appropriate statistical monitoring, Annex II to Regulation (EU) No 1387/2013 should be completed with supplementary units for some of the new products for which suspensions are granted. For reasons of consistency, the supplementary units assigned to the products deleted from Annex I to Regulation (EU) No 1387/2013 should also be deleted from Annex II to that Regulation.

- (6) It should be clarified that any mixtures, preparations or products made up of different components containing products subject to autonomous tariff suspensions are not covered by Annex I to Regulation (EU) No 1387/2013.
- (7) Regulation (EU) No 1387/2013 should therefore be amended accordingly.
- (8) Following specific administrative arrangements the amendments pursuant to this Regulation have to take effect from 1 July 2015. This Regulation should apply from that date.
- (9) However, in view to adequately ensure the benefit of the suspension with regard to the competitive capacity of the enterprises concerned by products:
 - with TARIC code 2930 90 99 21 the suspension relating to these products should apply from 1 January 2014;
 - with TARIC code 8507 60 00 87, the suspension relating to these products should apply from 1 July 2014;
 - with TARIC codes 8409 99 00 30, 8411 99 00 60 and 8411 99 00 70, the suspension relating to these products should apply from 1 January 2015,

HAS ADOPTED THIS REGULATION:

Article 1

Regulation (EU) No 1387/2013 is amended as follows:

(1) Article 1 is replaced by the following:

"Article 1

- 1. The autonomous Common Customs Tariff duties for the agricultural and industrial products listed in Annex I are hereby suspended.
- 2. Any mixtures, preparations or products made up of different components containing products listed in Annex I shall not be subject to paragraph 1 of this Article."
- (2) Annexes I and II are amended as set out in the Annex to this Regulation.

Article 2

This Regulation shall enter into force on the day of its publication in the *Official Journal of the European Union*.

It shall apply from 1 July 2015.

However, for products:

- with TARIC code 2930 90 99 21 the suspension relating to these products should apply from 1 January 2014;

- with TARIC code 8507 60 00 87, the suspension relating to these products should apply from 1 July 2014;

- with TARIC codes 8409 99 00 30, 8411 99 00 60 and 8411 99 00 70, the suspension relating to these products should apply from 1 January 2015.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels,

For the Council
The President

Regulation (EU) No 1387/2013 is amended as follows:

- (1) Annex I is amended as follows:
 - '(*) Suspension relating to a product in this Annex with regard to which the CN or TARIC code or the product description or the mandatory review date were amended by

between the title and the table, the note is replaced by the following note:

Council Regulation (EU) No 722/2014 of 24 June 2014 amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products (OJ L 192, 1.7.2014, p. 9)', by Council Regulation (EU) No 1341/2014 of 15 December 2014 amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and by Council Regulation (EU) .../... of ... amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products (OJ ...)';

(b) the following rows for the products are inserted following the order of the CN codes indicated in the first column of the table;

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
*ex 2009 89 73 ex 2009 89 73	11 13	Passion fruit juice and passion fruit juice concentrate, whether or not frozen: — with a Brix value of 13,7 or more but not more than 55, — of a value of more than € 30 per 100 kg net weight, — in immediate packings of a content of 50 litres or more, and — with added sugar for the use in the manufacture of products of food or drink industry (1)	0 %	31.12.2019
*ex 2009 89 99	94	Coconut water — unfermented, — not containing added spirit or sugar, and — in immediate packing of a content of 50 litres or more (2)	0 %	31.12.2016
*ex 2207 20 00 ex 2207 20 00 ex 3820 00 00	20 80 20	Feedstock consisting of by weight: — 88 % or more but not more than 92 % of ethanol, — 2,2 % or more but not more than 2,7 % of monoethylene glycol, — 1,0 % or more but not more than 1,3 % of methylethylketone, — 0,36 % or more but not more than 0,40 % of anionic surfactant (ca.30 % active), — 0,0293 % or more but not more than 0,0396 % of methyl isopropylketone, — 0,0195 % or more but not more than 0,0264 % of 5 methyl-3-heptanone, — 10 ppm or more but not more than 12 ppm of denatonium benzoate (Bitrex); — not more than 0,01 of perfumes — 6,5 % or more but not more than 8,0 % of water. for use in the manufacture of screenwash concentrate and other de-icing preparations (1)	0 %	31.12.2018
ex 2710 19 99	20	Catalytic de-waxed base oil, synthesised from gaseous hydrocarbons, followed by a heavy paraffin conversion process (HPC), containing: — not more than 1 mg/kg of sulphur — more than 99 % by weight of saturated hydrocarbons — more than 75 % by weight of n- and iso-paraffinic hydrocarbons with a carbon chain length of 18 or more but not more than 50; and — a kinematic viscosity at 40 °C of more than 6,5 mm²/s, or — a kinematic viscosity at 40 °C of more than 11 mm²/s with a viscosity index of 120 or more	0 %	31.12.2019
*ex 2818 10 91	20	Sintered corundum with a micro crystalline structure, consisting of aluminium oxide	0 %	31.12.2015

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		(CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight		
		(calculated as oxides) of:		
		— 94 % or more, but less than 98,5 % of aluminium oxide,		
		- 2 % (± 1,5 %) of magnesium oxide,		
		— 1 % (± 0,6 %) of yttrium oxide, And		
		— either 2 % (± 1,2 %) of lanthanum oxide or		
		-2% (± 1,2%) of lanthanum oxide and neodymium oxide,		
		with less than 50 % of the total weight having a particle size of more than 10 mm		
ex 2827 60 00	10	Sodium iodide (CAS RN 7681-82-5)	0 %	31.12.2019
ex 2841 70 00	30	Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2)	0 %	31.12.2019
ex 2903 39 90	35	Pentafluoroethane (CAS RN 354-33-6)	0 %	31.12.2019
ex 2903 79 19	10	Trans-1-chloro-3,3,3-trifluoropropene (CAS RN 102687-65-0)	0 %	31.12.2019
ex 2904 90 95	80	1-Chloro-2-nitrobenzene (CAS RN 88-73-3)	0 %	31.12.2019
ex 2905 22 00	10	Linalool (CAS RN 78-70-6) containing by weight 90,7 % or more of (3R)-(-)-Linalool (CAS RN 126-91-0)	0 %	31.12.2019
ex 2907 12 00	30	p-Cresol (CAS RN 106-44-5)	0 %	31.12.2019
ex 2907 29 00	25	4-Hydroxybenzyl alcohol (CAS RN 623-05-2)	0 %	31.12.2019
ex 2907 29 00	65	2,2'-Methylenebis(6-cyclohexyl-p-cresol) (CAS RN 4066-02-8)	0 %	31.12.2019
ex 2909 60 00	30	3,6,9-Triethyl-3,6,9-trimethyl-1,4,7-triperoxonane (CAS RN 24748-23-0), dissolved in isoparaffinic hydrocarbons	0 %	31.12.2019
ex 2914 69 90	50	Reaction mass of 2-(1,2-dimethylpropyl)anthraquinone (CAS RN 68892-28-4) and 2-(1,1-dimethylpropyl)anthraquinone (CAS RN 32588-54-8)	0 %	31.12.2019
ex 2916 39 90	18	2,4-Dichlorophenylacetic acid (CAS RN 19719-28-9)	0 %	31.12.2019
ex 2916 39 90	23	(2,4,6-Trimethylphenyl)acetyl chloride (CAS RN 52629-46-6)	0 %	31.12.2019
ex 2917 39 95	50	1,4,5,8-Naphthalenetetracarboxylic acid-1,8-monoanhydride (CAS RN 52671-72-4)	0 %	31.12.2019
ex 2917 39 95	60	Perylene-3,4:9,10-tetracarboxylic dianhydride(CAS RN 128-69-8)	0 %	31.12.2019
ex 2918 29 00	70	3,5-Diiodosalicylic acid (CAS RN 133-91-5)	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2918 30 00	70	2-[4-Chloro-3-(chlorosulphonyl)benzoyl]benzoic acid (CAS RN 68592-12-1)	0 %	31.12.2019
ex 2918 99 90	55	Stearyl glycyrrhetinate(CAS RN 13832-70-7)	0 %	31.12.2019
ex 2918 99 90	65	Acetic acid, difluoro[1,1,2,2-tetrafluoro-2-(pentafluoroethoxy)ethoxy]-, ammonium salt (CAS RN 908020-52-0)	0 %	31.12.2019
ex 2918 99 90	75	3,4-Dimethoxybenzoic acid (CAS RN 93-07-2)	0 %	31.12.2019
ex 2921 42 00	40	Sodium sulphanilate (CAS RN 515-74-2), also in form of its mono- or dihydrates (CAS RN 12333-70-0 or 6106-22-5)	0 %	31.12.2019
ex 2922 49 85	55	(E)-Ethyl 4-(dimethylamino)but-2-enoate maleate (CUS 0138070-7)	0 %	31.12.2019
ex 2923 90 00	20	Tetramethylammonium hydrogen phthalate (CAS RN 79723-02-7)	0 %	31.12.2019
ex 2924 19 00	35	Acetamide (CAS RN 60-35-5)	0 %	31.12.2019
ex 2924 29 98	23	Benalaxyl-M (ISO) (CAS RN 98243-83-5)	0 %	31.12.2019
ex 2924 29 98	33	N-(4-Amino-2-ethoxyphenyl)acetamide (CAS RN 848655-78-7)	0 %	31.12.2019
ex 2924 29 98	73	Napropamide (ISO) (CAS RN 15299-99-7)	0 %	31.12.2019
*ex 2927 00 00	35	C.C'-Azodi(formamide) (CAS RN 123-77-3) in the form of yellow powder with a decomposition temperature of 180°C or more but not more than 220°C used as a foaming agent in the manufacture of thermoplastic resins, elastomer and cross-linked polythene foam	0 %	31.12.2019
ex 2928 00 90	13	Cymoxanil (ISO) (CAS RN 57966-95-7)	0 %	31.12.2019
ex 2928 00 90	18	Acetone oxime (CAS RN 127-06-0) of a purity by weight of 99 % or more	0 %	31.12.2019
ex 2930 90 99	16	3-(Dimethoxymethylsilyl)-1-propanethiol (CAS RN 31001-77-1)	0 %	31.12.2019
ex 2930 90 99	21	[2,2'-Thio-bis(4-tert-octylphenolato)]-n-butylamine nickel (CAS RN 14516-71-3)	0 %	31.12.2016
ex 2930 90 99	27	2-[(4-Amino-3-methoxyphenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 26672-22-0)	0 %	31.12.2019
ex 2930 90 99	33	2-Amino-5-{[2-(sulfooxy)ethyl]sulfonyl}benzenesulfonIc acid (CAS RN 42986-22-1)	0 %	31.12.2019
ex 2933 39 99	11	2-(Chloromethyl)-4-(3-methoxypropoxy)-3-methylpyridine hydrochloride(CAS RN 153259-31-5)	0 %	31.12.2019
ex 2933 39 99	21	Boscalid (ISO) (CAS RN 188425-85-6)	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 39 99	31	2-(Chloromethyl)-3-methyl-4-(2,2,2-trifluoroethoxy)pyridine hydrochloride(CAS RN 127337-60-4)	0 %	31.12.2019
ex 2933 59 95	10	6-Amino-1,3-dimethyluracil (CAS RN 6642-31-5)	0 %	31.12.2019
ex 2933 69 80	75	Metamitron (ISO) (CAS RN 41394-05-2)	0 %	31.12.2019
ex 2933 99 80	11	Fenbuconazole (ISO) (CAS RN 114369-43-6)	0 %	31.12.2019
ex 2933 99 80	12	Myclobutanil (ISO) (CAS RN 88671-89-0)	0 %	31.12.2019
ex 2933 99 80	19	2-(2,4-Dichlorophenyl)-3-(1H-1,2,4-triazol-1-yl)propan-1-ol (CAS RN 112281-82-0)	0 %	31.12.2019
ex 2934 99 90	10	Fluralaner (INN) (CAS RN 864731-61-3)	0 %	31.12.2019
ex 2934 99 90	16	Difenoconazole (ISO) (CAS RN 119446-68-3)	0 %	31.12.2019
ex 2934 99 90	19	2-[4-(Dibenzo[b,f][1,4]thiazepin-11-yl)piperazin-1-yl] ethanol(CAS RN 329216-67-3)	0 %	31.12.2019
ex 2935 00 90	10	Florasulam (ISO) (CAS RN 145701-23-1)	0 %	31.12.2019
ex 3204 12 00	60	Colourant C.I. Acid Red 52 (CAS RN 3520-42-1) and preparations based thereon with a colourant C.I. Acid Red 52 content of 97 % or more by weight	0 %	31.12.2019
ex 3204 13 00	50	Colourant C.I Basic Violet 11 (CAS RN 2390-63-8) and preparations based thereon with a colourant C.I Basic Violet 11 content of 90 % or more by weight	0 %	31.12.2019
ex 3204 13 00	60	Colourant C.I Basic Red 1:1 (CAS RN 3068-39-1) and preparations based thereon with a colourant C.I Basic Red 1:1 content of 90 % or more by weight	0 %	31.12.2019
ex 3204 14 00	10	Colourant C.I. Direct Black 80 (CAS RN 8003-69-8) and preparations based thereon with a colourant C.I. Direct Black 80 content of 90 % or more by weight	0 %	31.12.2019
ex 3204 14 00	20	Colourant C.I. Direct Blue 80 (CAS RN 12222-00-3) and preparations based thereon with a colourant C.I. Direct Blue 80 content of 90 % or more by weight	0 %	31.12.2019
ex 3204 14 00	30	C.I. Colourant Direct Red 23 (CAS RN 3441-14-3) and preparations based thereon with a colourant C.I. Direct Red 23 content of 90 % or more by weight	0 %	31.12.2019
ex 3204 17 00	45	Colourant C.I. Pigment Yellow 174 (CAS RN 4118-16-5), highly resinated pigment (approx. 35 % disproportionate resin), with a purity of 98 % by weight or more, in the form of extruded beads with a moisture content of not more than 1 % by weight	0 %	31.12.2018
ex 3204 17 00	67	Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) with a purity of 98 % by weight or more, in the form of extruded beads, with a moisture content of not more than 1 % by weight.	0 %	31.12.2018

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3204 90 00	10	Colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) (CAS RN 68427-35-0) and preparations based thereon with a colourant C.I Solvent Yellow 172 (also known as C.I. Solvent Yellow 135) content of 90 % or more by weight	0 %	31.12.2019
ex 3212 10 00 ex 7607 20 90	10 30	 Metallised film: — consisting of eight or more layers of aluminium (CAS RN 7429-90-5) of a purity of 99,8 % or more, — with an optical density of each aluminium layer of not more than 3.0, — with each aluminium layer separated by a resin layer, — on a carrier film of PET, and — on rolls of up to 50 000 metres in length 	0 %	31.12.2019
ex 3808 94 20	30	Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing: — 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5), — 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5), — 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2), and — 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7)	0 %	31.12.2019
ex 3811 21 00	23	Additives containing: — polyisobutene succinimide derived from reaction of polyethylenepropylamide with polyisobutenyl succinic anhydride (CAS RN 84605-20-9), — containing more than 31,9 % but not more than 43,3 % by weight of mineral oils, — not more than 0,05 % by weight chlorine, and — having a total base number (TBN) greater than 20, for use in the manufacture of additives blends for lubricating oils (1)	0 %	31.12.2019
*ex 3811 21 00	53	Additives containing: — overbased calcium petroleum sulphonates (CAS 68783-96-0) with a sulphonate content by weight of 15 % or more, but not more than 30 % and — by weight more than 40 % but not more than 60 % of mineral oil, having a total base number of 280 or more but not more than 420, for use in the manufacture of lubricating oils (1)	0 %	31.12.2019
*ex 3811 21 00	73	Additives containing: — borated succinimide compounds (CAS RN 134758-95-5), — mineral oils, and — having a total base number (TBN) greater than 40, for use in the manufacture of additive mixtures for lubricating oils (1)	0 %	31.12.2018

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3812 30 29	10	4,4'-Isopropylidenediphenol C12-15 alcohol phosphite containing by weight 1 % or more but not more than 3 % of bisphenol A (CAS RN 96152-48-6)	0 %	31.12.2019
ex 3824 90 92	82	T-butylchloride dimethylsilane (CAS RN 18162-48-6) solution in toluene	0 %	31.12.2019
*ex 3824 90 92	83	Preparation, consisting of two or more of the following glycols: — dipropylene glycol — tripropylene glycol or — pentapropylene glycol	0 %	31.12.2017
*ex 3824 90 93	46	Sodium hydrogen 3-aminonaphthalene-1,5-disulfonate (CAS RN 4681-22-5) containing by weight: — not more than 20 % of disodium sulphate, — not more than 5 % of sodium chloride	0 %	31.12.2015
*ex 3901 10 10 ex 3901 90 90	20 50	High flow linear low density polyethylene-1-butene (LLDPE) (CAS RN 25087-34-7) in form of powder, with — a melt flow rate (MFR 190 °C/2,16 kg) of 16 g/10 min or more, but not more than 24 g/10 min and — a density (ASTM D 1505) of 0,922 g/cm³ or more, but not more than 0,926 g/cm³ and — a vicat softening temperature of min. 94 °C	0 %	31.12.2019
*ex 3901 10 10	30	Linear low-density polyethylene (LLDPE) (CAS RN 9002-88-4) in the form of powder, with — not more than 5 % by weight of comonomer, — a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and — a density of 0,922 g/cm³ or more, but not more than 0,928 g/cm³	0 %	31.12.2018
*ex 3901 90 90	60	Linear low-density polyethylene (LLDPE) (CAS RN 9002-88-4) in the form of powder, with — more than 5 %, but not more than 8 % by weight of comonomer, — a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and — a density of 0,922 g/cm³ or more, but not more than 0,928 g/cm³	0 %	31.12.2018
*ex 3903 19 00	40	Crystalline polystyrene with: — a melting point of 268 °C or more but not more than 272 °C — a setting point of 232 °C or more but not more than 247 °C, — whether or not containing additives and filling material	0 %	31.12.2016
ex 3903 90 90	45	Preparation, in form of powder, containing by weight: — 86 % or more but not more than 90 % of styrene-acrylic-copolymer and	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— 9 % or more but not more than 11 % of fatty acid ethoxylate (CAS RN 9004-81-3)		
ex 3903 90 90	55	Preparation, in form of an aqueous suspension, containing by weight: — 25 % or more but not more than 26 % of styrene-acrylic-copolymer and — 5 % or more but not more than 6 % of glycol	0 %	31.12.2019
ex 3908 90 00	70	Copolymer containing: — 1,3-benzenedimethanamine (CAS RN 1477-55-0) and — adipic acid (CAS RN 124-04-9) whether or not containing isophthalic acid (CAS RN 121-91-5)	0 %	31.12.2019
ex 3911 90 19	60	Formaldehyde, polymer with 1,3-dimethylbenzene and tert-butyl-phenol (CAS RN 60806-48-6)	0 %	31.12.2019
ex 3911 90 19	70	Preparation, containing: — Cyanic acid, C,C'-((1-methylethylidene)di-4,1-phenylene) ester, homopolymer (CAS RN 25722-66-1), — 1,3-Bis(4-cyanophenyl)propane (CAS RN 1156-51-0), — in a solution of butanone (CAS RN 78-93-3) with a content of less than 50 % by weight	0 %	31.12.2019
*ex 3912 20 19	10	Nitrocellulose (CAS RN 9004-70-0)	0 %	31.12.2016
*ex 3919 10 80 ex 3919 90 00 ex 3920 61 00	57 30 30	Reflecting sheet: — of a polycarbonate or acrylic polymer film embossed on one side in a regular shaped pattern — covered on one or both sides with one or more layers of plastic or metallisation, and — whether or not covered on one side with a self-adhesive layer and a release sheet	0 %	31.12.2018
*ex 3919 10 80 ex 3919 90 00	67 46	Self-adhesive reflecting sheet whether or not in segmented pieces: — showing a regular pattern, — with or without an application tape layer, — consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) or polycarbonate containing microprisms, — whether or not containing an additional layer of polyester and — an adhesive with a final release sheet	0 %	31.12.2018
*ex 3919 90 00	48	Transparent poly(vinyl chloride) film:	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		 coated on one side with an acrylic UV-sensitive adhesive with an adhesive strength of 70 N/m or more, which is reduced upon irradiation, with a polyester liner with a total thickness without release liner of 78 μm or more 		
ex 3920 10 28	30	Printed embossed film — of polymers of ethylene — having a gravity of 0,94g/cm3 or more — of a thickness of 0,019mm ± 0,003mm — with permanent graphics consisting of two different alternating designs whose individual length is 525 mm or more	0 %	31.12.2019
*ex 3920 62 19	60	 Poly (ethylene terephtalate) film: — of a thickness of not more than 20μm, — coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica or aluminium oxide has been dispersed and of a thickness of not more than 2μm 	0 %	31.12.2017
ex 3920 69 00	50	Monolayer, biaxially oriented film: — composed of more than 85 % by weight of poly(lactic acid) and not more than 10,50 % by weight of modified poly(lactic acid) based polymer, poly-glycol ester and talc, — having a thickness of 20 μm or more but not more than 120 μm — biodegradable and compostable (as determined by the method EN 13432)	0 %	31.12.2019
ex 3920 69 00	60	Monolayer, transverse oriented, shrink film: — composed of more than 80 % by weight of poly(lactic acid) and not more than 15,75 % by weight of additives of modified poly(lactic acid), — having a thickness of 45 μm or more but not more than 50 μm, — biodegradable and compostable (as determined by the method EN 13432)	0 %	31.12.2019
ex 3920 79 10	10	Sheets of painted vulcanised fibre-board with a thickness of not more than 1,5 mm	0 %	31.12.2019
ex 3920 99 28	65	 Matt, thermoplastic polyurethane foil in rolls with: — a width of 1640 mm (± 10 mm), — a gloss of 3,3 degrees or more but not more than 3,8 (as determined by the method ASTM D2457), — a surface roughness of 1,9 Ra or more but not more than 2,8 Ra (as determined by the method ISO 4287), — a thickness of more than 365 μm but not more than 760 μm, — a hardness of 90 (± 4) (as determined by the method: Shore A (ASTM D2240)), — an elongation to break of 470 % (as determined by the method: EN ISO 527) 	0 %	31.12.2019
ex 3920 99 28	75	Thermoplastic polyurethane foil in rolls with: — a width of more than 900 mm but not more than 1016 mm, — a matt finish,	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		 a thickness of 0,43 mm (± 0.03 mm), an elongation to break of 420 % or more but not more than 520 %, a tensile strength of 55 N/mm2 (± 3) (as determined by the method EN ISO 527) a hardness of 90 (± 4) (as determined by the method: Shore A [ASTM D2240]), wrinkle inside (waves) of 6,35 mm, a flatness of 0,025 mm 		
ex 3921 90 60	30	Heat-, infra- and UV insulating poly(vinyl butyral) film: — laminated with a metal layer with a thickness of 0,05 mm(±0,01 mm), — containing by weight 29,75 % or more but not more than 40,25 % of triethyleneglycol di (2-ethyl hexanoate) as plasticizer, — with a light transmission of 70 % or more (as determined by the ISO 9050 standard); — with an UV transmission of 1 % or less (as determined by the ISO 9050 standard); — with a total thickness of 0,43 mm (± 0,043 mm)	0 %	31.12.2019
ex 6804 21 00	10	Discs — of synthetic diamonds which are agglomerated with a metal alloy, ceramic alloy or plastic alloy, — having a self-sharpening effect by constant release of the diamonds, — suitable for abrasive cutting of wafers, — whether or not containing a hole in the centre, — whether or not on a support	0 %	31.12.2019
ex 7409 11 00 ex 7409 19 00 ex 7410 11 00	10 10 20	Refined copper foil and -strips of a thickness of not more than 400 μm	0 %	31.12.2019
*ex 7606 12 92 ex 7607 11 90	30 50	Aluminium and magnesium alloy strip <i>or foil</i> : — in rolls, — of a thickness of 0,14 mm or more but not more than 0,40 mm, — a width of 12,5 mm or more but not more than 359 mm, — a tensile strength of 285 N/mm2 or more, and — an elongation at break of 1 % or more, and containing by weight: — 93,3 % or more of aluminium, — 0,8 % or more but not more than 5 % of magnesium, and — not more than 1,8 % of other elements	0 %	31.12.2017
*ex 7607 11 90	60	Plain aluminium foil with the following parameters: — an aluminium content of 99,98 % or more — a thickness of 0,070 mm or more but not more than 0,125 mm	0 %	31.12.2016

- with a cubic texture of a kind used for high voltage clething Alminitum engine bracket, with dimensions of: - height of more than 10 mm but not more than 200 mm - width of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 1 mm: - outer porosity not more than 1 mm: - outer porosity not more than 1 mm: - note with of more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 **O Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 428, 4965 and 4967 cx 8108 90 50 **O Plates, sheets, strips and foil of non-alloyed titanium - of a width of more than 750 mm - of a width of more than 3 mm cx 8108 90 50 **S Strip or foil of non-alloyed titanium: - containing more than 0,07 % by weight of exygen (O2), - of a thickness of 0,4 mm or more but not more than 1,7 mm - conforming to the Vickers hardness ITV1 standard of not more than 1,7 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 ex 8411 99 00 50 Wheel-shaped gas turbine turbocharger component: - with a leat-resistance of not more than 1050 °C; - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 - mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G NiCri3AldMoNor DIN G- NiCri3AlI6MoNor DIN NiCo10W10Cr9AlTi or - AMS AlSLe86, - with a leat-resistance of not more than 1 100 °C; - with a diameter of 30 mm or more, but not more than 100 mm; - with a leight of 20	CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 7616 99 10 30 Aluminium engine bracket, with dimensions of: - height of more than 10 mm but not more than 200 mm - width of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - micraral purssity not more than 2 mm; - mote work of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6v4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium - of a width of more than 750 mm - of a dithcress of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium - of a dithcress of 10 d more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium - of a hickness of 0d 4 mm or more but not more than 2.5 mm - conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1050 °C; - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm. - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G- NiCr13Al6hOob or DIN G- NiCr13Al16hOob or DIN NiCo10W10Ct9AlTi or AMS AlS1.686, - with a heat-resistance of not more than 1 100 °C; - with a heat-resistance of not more than 1 100 mm; -					
- height of more than 10 mm but not more than 200 mm - width of more than 10 mm but not more than 200 mm - length of more than 10 mm but not more than 200 mm - equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN-1706) with following characteristics: - internal porosity not more than 1 mm; - outer prorisity not more than 2 mm; - Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *cx 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4228, 4968 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium - of a width of more than 750 mm - of a thickness of not more than 3 mm Ex 8108 90 50 85 Strip or foil of non-alloyed titanium: - containing more than 0,07 % by weight of oxygen (O ₂), - of a thickness of 0.4 mm or more but not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 90 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1050 °C; - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G- NiC13Al6MoNb or DIN G-NiC13Al16MoNb or DIN NiC010W10C19AlTi or AMS AlS1-686, - with a diameter of 30 mm or more, but not more than 100 mm; - with a healt-resistance of not more than 100 mm; - with a healt-resistance of not more, but not more than 100 mm; - with a healt-resistance of not more, but not more than 100 mm; - with a healt-resistance of not more, but not more than 100 mm; - with a healt-resistance of not more, but not more than 100 mm;			of a kind used for high voltage etching		
equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN-1706) with following characteristics: — internal porosity not more than 1 mm; — outer porosity not more than 2 mm; — Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — confarining more than 0,07 % by weight of oxygen (O ₂), — of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiC13Al6MoNb or DIN G-NiC13Al16MoNb or DIN NiCc10W10Cr9AlTi or AMS AlSI-686, — with a heat-resistance of not more than 1100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	ex 7616 99 10	30	 height of more than 10 mm but not more than 200 mm width of more than 10 mm but not more than 200 mm 	0 %	31.12.2019
ENAC-42100 (based on the norm EN:1706) with following characteristics: — internal porosity not more than 1 mm; — outer porosity not more than 1 mm; — Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-east nickel based alloy complying with standard DIN G- NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1100 °C; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm;					
- internal porosity not more than 1 mm; - outer porosity not more than 2 mm; - Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 cx 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium					
- outer porosity not more than 2 mm; - Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium of a width of more than 750 mm of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: - containing more than 0,07 % by weight of oxygen (O ₂), - of a thickness of 0,4 mm or more but not more than 2.5 mm conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1 050 °C, - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-east nickel based alloy complying with standard DIN G-NiCri3Al6MoNb or DIN G-NiCri3Al6MoNb or DIN SiCol0W10Cr9AlTi or AMS Al81:686, - with a heat-resistance of not more than 1 100 °C; - with a diameter of 30 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 100 mm;					
- Rockwell hardness HRB 10 or more of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a vidth of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₃), — of a hickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al16MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AlS1:686, — with a heat-resistance of not more than 1100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 100 mm;					
of a kind used in the production of suspensions systems for engines in motor vehicles *ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al16MoNb or DIN NiCr13Al16MoNb or DIN NiCr10V10Cr9AlTi or AMS AlSI-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
*ex 8108 90 30 50 Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967 ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: 0 % 31.12.2018 ex 8411 99 00 70 — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al6MoNb or DIN NiCo10W10Cr9AlTi or AMS AlSi-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
ex 8108 90 50 80 Plates, sheets, strips and foil of non-alloyed titanium — of a width of more than 750 mm — of a thickness of not more than 3 mm ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: ex 8411 99 00 70 — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			of a kind used in the production of suspensions systems for engines in motor venicles		
ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0.07 % by weight of oxygen (O ₂), — of a thickness of 0.4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HVI standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Alf6MoNb or DIN NiCr13Alf6MoNb or DIN NiCr10W10Cr9AlTi or AMS AlSI-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	*ex 8108 90 30	50		0 %	31.12.2015
ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0.07 % by weight of oxygen (O ₂), — of a thickness of 0.4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HVI standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Alf6MoNb or DIN NiCr13Alf6MoNb or DIN NiCr10W10Cr9AlTi or AMS AlSI-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	ex 8108 90 50	80	Plates, sheets, strips and foil of non-alloyed titanium	0 %	31.12.2019
ex 8108 90 50 85 Strip or foil of non-alloyed titanium: — containing more than 0,07 % by weight of oxygen (O ₂), — of a thickness of 0,4 mm or more but not more than 2,5 mm — conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 70 Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G- NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISi-686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
- containing more than 0,07 % by weight of oxygen (O ₂), - of a thickness of 0,4 mm or more but not more than 2,5 mm - conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1 050 °C, - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or - AMS AISI:686, - with a heat-resistance of not more than 1 100 °C; - with a diameter of 30 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			— of a thickness of not more than 3 mm		
- containing more than 0,07 % by weight of oxygen (O ₂), - of a thickness of 0,4 mm or more but not more than 2,5 mm - conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1 050 °C, - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or - AMS AISI:686, - with a heat-resistance of not more than 1 100 °C; - with a diameter of 30 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	ex 8108 90 50	85	Strip or foil of non-alloyed titanium:	0 %	31.12.2019
- of a thickness of 0,4 mm or more but not more than 2,5 mm - conforming to the Vickers hardness HV1 standard of not more than 170 of a kind used in the manufacture of welded tubes for nuclear power plant condensers ex 8409 99 00 30 Spiral-shaped gas turbine turbocharger component: - with a heat-resistance of not more than 1 050 °C, - with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, - whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: - of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or - AMS AISI:686, - with a heat-resistance of not more than 1 100 °C; - with a diameter of 30 mm or more, but not more than 100 mm; - with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
of a kind used in the manufacture of welded tubes for nuclear power plant condensers Spiral-shaped gas turbine turbocharger component: — with a heat-resistance of not more than 1 050 °C, — with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, — whether or not with an engine exhaust manifold ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or — AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2018					
ex 8409 99 00			— conforming to the Vickers hardness HV1 standard of not more than 170		
ex 8411 99 00 To with a heat-resistance of not more than 1 050 °C, with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, whether or not with an engine exhaust manifold ex 8411 99 00 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, with a heat-resistance of not more than 1 100 °C; with a diameter of 30 mm or more, but not more than 100 mm; with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			of a kind used in the manufacture of welded tubes for nuclear power plant condensers		
ex 8411 99 00 To with a heat-resistance of not more than 1 050 °C, with a turbine wheel hole diameter of 30 mm or more, but not more than 110 mm, whether or not with an engine exhaust manifold ex 8411 99 00 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, with a heat-resistance of not more than 1 100 °C; with a diameter of 30 mm or more, but not more than 100 mm; with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	ex 8409 99 00	30	Spiral-shaped gas turbine turbocharger component:	0 %	31.12.2018
ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019		70	— with a heat-resistance of not more than 1 050 °C,		
ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			— with a turbine wheel hole diameter of 30 mm or more, but not more than 110		
ex 8411 99 00 60 Wheel-shaped gas turbine component with blades, of a kind used in turbochargers: — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			mm,		
— of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al6MoNb or DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			— whether or not with an engine exhaust manifold		
NiCr13Al6MoNb or DIN G- NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686, — with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019	ex 8411 99 00	60		0 %	31.12.2017
— with a heat-resistance of not more than 1 100 °C; — with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
— with a diameter of 30 mm or more, but not more than 100 mm; — with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019			AMS AISI:686,		
— with a height of 20 mm or more, but not more than 70 mm ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
ex 8479 89 97 70 Machine to accurately align and attach lenses into a camera assembly in five axis 0 % 31.12.2019					
			— with a height of 20 mm or more, but not more than 70 mm		
	ex 8479 89 97	70	Machine to accurately align and attach lenses into a camera assembly in five axis	0 %	31.12.2019
anginnont cadacinty and IIA month in doction with a two dail offic county	0.101170771	, ,	alignment capability and fix them in position with a two part cure epoxy		51.12.2017

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8479 89 97	80	Machinery for the production of a sub assembled component (anode conductor and the negative closing cap) for the manufacture of AA and/or AAA alkaline batteries (1)	0 %	31.12.2019
*ex 8483 30 38	40	Cylindrical bearing housing: — of precision-cast grey cast iron complying with standard DIN EN 1561, — with oil chambers, — without bearings, — with a diameter of 50 mm or more, but not more than 250 mm, — with a height of 40 mm or more, but not more than 150 mm, — whether or not with water chambers and connectors	0 %	31.12.2017
ex 8501 32 00 ex 8501 33 00	60 15	Traction motor, with: — a torque output of 200 Nm or more but not more than 300 Nm — a power output of 50 kW or more but not more than 100 kW — a speed of not more than 12 500 rpm for use in the manufacture of electric vehicles (1)	0 %	31.12.2019
ex 8504 40 88	30	DC to AC inverter for use in traction motor control for use in the manufacture of electric vehicles (1)	0 %	31.12.2019
ex 8504 40 90	80	Power converter containing: — a DC to DC converter — a charger of a capacity of not not more than 7 kw — switching functions for use in the manufacture of electric vehicles (1)	0 %	31.12.2019
ex 8505 90 20	30	Coil for an electromagnetic valve, with: — a plunger — a diameter of 12,9 mm (+/- 0,1), — a height without plunger of 20,5 mm (+/- 0,1), — an electric cable with connector, and in a cylindrical metal housing	0 %	31.12.2019
*ex 8507 10 20	30	Lead-acid accumulators or -modules, of a kind used for starting piston engines with — a nominal capacity of not more 32 Ah, — a length of not more than 205 mm, — a width of not more than 130 mm and — a height of not more than 190 mm for use in the manufacture of articles of CN-code 8711 (1)	0 %	31.12.2018

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8507 60 00	85	Rectangular modules for incorporation in lithium-ion rechargeable batteries: — of a length of 312 mm or more, but not more than 350 mm — of a width of 79,8 mm or more, but not more than 225 mm — of a height of 35 mm or more, but not more than 168 mm — of a weight of 3,95 kg or more, but not more than 8,56 Kg — with a rating of 66,6 Ah or more, but not more than 129 Ah	0 %	31.12.2015
*ex 8507 60 00	87	Lithium-ion rechargeable batteries, with: — a length of 1 475 mm or more, but not more than 2 820 mm — a width of 935 mm or more, but not more than 1 660 mm — a height of 260 mm or more, but not more than 600 mm — a weight of 320 kg or more, but not more than 700 kg — a nominal capacity of 18,4 Ah or more, but not more than 130 Ah, — put up in packs of 12 or 16 modules	0 %	31.12.2017
*ex 8511 30 00	30	Igniter integrated coil assembly with: — an igniter, — a coil on plug assembly with an integrated mounting bracket, — a housing, — a length of 90 mm or more but not more than 200 mm (+/- 5 mm), — an operating temperature of -40 °C or more but not more than 130 °C, — a voltage of 10,5 V or more, but not more than 16 V	0 %	31.12.2019
ex 8512 20 00	10	Fog lamps with galvanised inner surface, containing: — plastic holder with four or more brackets, — one or more, but not more than two 12 V bulbs, — connection cable with a connector, — plastic cover for use in the manufacture of goods of chapter 87 (1)	0 %	31.12.2019
ex 8512 20 00	20	Information screen displaying at least time, date and status of safety features in a vehicle with an operating voltage of 12 V or more, but not more than 14,4 V, of a kind used in the manufacturing of goods of Chapter 87	0 %	31.12.2019
ex 8512 30 90	10	Horn assembly operating on piezomechanical principle for generating a specific sound signal, with a voltage of 12 V, comprising: — coil, — magnet, — metal membrane, — connector, — holder of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 8512 90 90	10	Ultrasonic parking sensor with — printed circuit board inside the housing and sensor cell on the cover connected	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		through terminal pins, — an operating voltage of not more than 12 V, — ability to receive and transmit signals processed by the control unit of a kind used in the manufacturing of goods of Chapter 87		
ex 8514 20 80 ex 8516 50 00 ex 8516 60 80	10 10 10	Cavity assembly comprising at least: — a transformer with an input of not more than 240 V and an output of not more than 3 000 W — an AC or DC fan motor with an output of not more than 42 watts — a housing made of stainless steel — with or without a magnetron of a microwave output power of not more than 900 W	0 %	31.12.2019
		for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and 8516 6080 (1)		
ex 8516 90 00	80	Door assembly incorporating a capacitive sealing element and wavelength choke for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and 8516 6080 (1)	0 %	31.12.2019
ex 8518 90 00	80	Integrated car loudspeaker housing, consisting of: — a speaker frame and magnet system holder with a protective coating and — an embossed anti-dust cloth	0 %	31.12.2019
*ex 8525 80 19	60	Image scanning cameras, using: — a "Dynamic"- or "Static overlay lines" system, — an output NTSC video signal, — a voltage of 6,5 V or more, — an illuminance of 0,5 lux or more	0 %	31.12.2019
*ex 8527 91 99 ex 8529 90 65	20 85	Assembly consisting of at least: — an audio frequency amplifier unit, comprising at least an audio frequency amplifier and a sound generator, — a transformer and — a radio broadcast receiver for use in the manufacture of consumer electronic products (1)	0 %	31.12.2019
ex 8529 10 80	70	Ceramic filters — with an applicable frequency range of 10 kHz or more but no more than 100 MHz — with a housing of ceramic plates provided with electrodes	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		of a kind used in electrical-mechanical transducer or resonator in audio visual and communication equipment		
ex 8529 90 65	80	Tuner transforming high-frequency signals into digital signal, for use in the manufacture of products falling under heading 8527 (1)	0 %	31.12.2019
*ex 8529 90 92	15	LCD modules,	0 %	31.12.2018
ex 8548 90 90	60	 — solely consisting of one or more TFT glass or plastic cells, — not combined with touch screen facilities, — with one or more printed circuits boards with control electronics for pixel addressing only, — with or without backlight unit and — with or without inverters 		
ex 8537 10 99	40	Electronic control unit for monitoring car vehicle tyre pressure comprising plastic box with printed circuit board inside and with or without metal holder, of: — a length of 50 mm or more, but not more than 120 mm, — a width of 20 mm or more but not more than 40 mm, — a height of 30 mm or more, but not more than 120 mm of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 8537 10 99	50	Electronic control unit BCM (Body Control Module) comprising — plastic box with printed circuit board and metal holder, — with voltage of 9V or more, but not more than 16V, — able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 8537 10 99	60	Electronic assembly consisting of: — a microprocessor, — light-emitting diode (LED) or liquid crystal display (LCD) indicators, — electronic components mounted on a printed circuit, for use in the manufacture of built-in products of CN-codes 8514 2080, 8516 5000 and 8516 6080 (1)	0 %	31.12.2019
ex 8544 49 91	10	Insulated copper electrical wires: — with individual conductor wires of a diameter exceeding 0,51 mm., — for a voltage of not more than 1 000 V, for use in the manufacture of automotive cable harnesses (1)	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
*ex 8548 90 90	65	LCD modules, — solely consisting of one or more TFT glass or plastic cells, — combined with touch screen facilities, — with one or more printed circuits boards with control electronics for pixel addressing only, — with or without backlight unit and — with or without inverters	0 %	31.12.2018
ex 8708 30 10	10	Brake unit assembly comprising — electric control brake, — stroke sensor, — VDC (vehicle dynamic control) and — backup power source for use in the manufacture of vehicles (1)	0 %	31.12.2019
ex 8708 30 91	20	Non-asbestos organic brake pads with friction material mounted to the band steel back plate for use in the manufacture of goods of Chapter 87 (1)	0 %	31.12.2019
ex 8708 30 91	30	Body of disc type brake in BIR ("Ball in Ramp") or EPB ("Electronic Parking Brake") version containing functional and mounting openings and guide grooves, of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 8708 91 35	10	Aluminium cooler using compressed air with a ribbed design of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 8708 94 35	20	Rack steering gear in aluminium housing with homokinetic hinges of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 9002 11 00	80	Lens assembly with: — a field of view range of 58,5 deg or more, but not more than 194 deg, — a focal length of 1,16 mm or more, but not more than 3,88 mm, — a relative aperture of F/2.0 or more but not more than 2.6, — a diameter of 17 mm or more but not more than 18,5 mm, for use in the manufacture of CMOS automotive cameras (1)	0 %	31.12.2019
ex 9029 10 00	30	Speed sensor using the Hall effect for measuring wheels rotation in a motor vehicle equipped with plastic housing and attached to connecting cable with a joining connector and mounting holders of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 9029 20 31 ex 9029 90 00	10 20	Clustered instrument panel with the microprocessor control board, stepping motors and LED indicators showing at least: — speed,	0 %	31.12.2019

CN code	TARI C	Description	Rate of autonomous duty	Date foreseen for mandatory review
		 — engine revolutions, — engine temperature, — the fuel level communicating via CAN-BUS and K-LINE protocols, of a kind used in the manufacture of goods of Chapter 87 		
ex 9031 80 34	50	Programmable dual linear Hall sensor — consisting of two non-electrically connected integrated circuits, a top die and a bottom die, — positioned on the top and bottom of a lead frame, — in a semiconductor housing, for use as a means for measuring angles, positions and currents in cars	0 %	31.12.2019
ex 9031 80 38	50	Gyroscopic sensor for measuring lateral acceleration of the vehicle vertical axis comprising — a piezoelectric crystal for generating an electrical potential during deformation and — a plastic box with metal holder of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 9031 80 38	60	Congestion sensor, printed circuit board and connector, moulded together in plastic, for monitoring congestion "G" and providing the values for further evaluation of triggering the airbags, of a kind used in the manufacture of goods of Chapter 87	0 %	31.12.2019
ex 9031 80 98	30	Functional Test Machine for calibrating and image quality testing lenses in automotive cameras	0 %	31.12.2019

(c) the following rows for the products with the CN and TARIC codes are deleted:

CN code	TARIC
ex 2009 89 73	11
ex 2009 89 73	13

⁽¹⁾ Suspension of duties is subject to Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 of 2 July 1993 laying down provisions for the implementation of Council Regulation (EEC) No 2913/92 establishing the Community Customs Code (OJ L 253, 11.10.1993, p. 1).

⁽²⁾ However, the measure is not allowed where processing is carried out by retail or catering undertakings.

CN code	TARIC
ex 2009 89 99	93
ex 2207 20 00	20
ex 2207 20 00	80
ex 2818 10 91	10
ex 2915 90 70	40
ex 2921 45 00	10
ex 2927 00 00	15
ex 2932 99 00	35
ex 2934 99 90	33
ex 3204 20 00	40
ex 3811 21 00	43
ex 3811 21 00	53
ex 3820 00 00	20
ex 3824 90 92	52
ex 3901 10 10	10
ex 3901 10 10	20
ex 3901 90 90	30
ex 3901 90 90	40
ex 3901 90 90	50
ex 3903 19 00	30
ex 3912 20 11	10
ex 3919 10 80	21
ex 3919 10 80	65
ex 3919 90 00	21
ex 3919 90 00	37
ex 3919 90 00	57

CN code	TARIC
ex 3920 61 00	20
ex 3920 62 19	81
ex 7606 12 92	20
ex 7607 11 90	10
ex 7607 11 90	20
ex 8108 90 30	30
ex 8411 99 00	30
ex 8411 99 00	40
ex 8483 30 38	30
ex 8504 50 95	60
ex 8507 10 20	85
ex 8507 60 00	35
ex 8507 60 00	70
ex 8511 30 00	20
ex 8525 80 19	35
ex 8527 21 59	10
ex 8527 29 00	20
ex 8527 29 00	30
ex 8527 91 99	10
ex 8529 90 65	35
ex 8529 90 92	44
ex 8543 70 90	13
ex 8543 70 90	23
ex 8548 90 90	47
ex 8548 90 90	49
ex 8548 90 90	55

CN code	TARIC
ex 9405 40 39	50
ex 9405 40 39	60
ex 9405 40 99	03
ex 9405 40 99	06

(2) Annex II is amended as follows:

(b) the following rows for the supplementary units with the CN and TARIC codes are added:

CN	TARIC	SUPPLEMENTARY UNIT
9031 8034	50	1 000 p/st
8544 4991	10	m
3901 1010	30	m ³
3901 9090	60	m ³
3920 9928	65	m ²
3920 9928	75	m ²
3921 9060	30	m ²
3903 9090	45	m ³
3920 7910	10	p/st
6804 2100	10	p/st
7616 9910	30	p/st
8409 9900	30	p/st
8411 9900	60	p/st
8411 9900	70	p/st
8479 8997	70	p/st
8479 8997	80	p/st
8483 3038	40	p/st
8504 4088	30	p/st
8504 4090	80	p/st
8505 9020	30	p/st
8511 3000	30	p/st
8512 2000	10	p/st
8512 2000	20	p/st
8512 3090	10	p/st
8512 9090	10	p/st
8514 2080	10	p/st
8516 9000	80	p/st
8518 9000	80	p/st
8529 1080	70	p/st
8529 9065	80	p/st
8529 9092	15	p/st
8537 1099	40	p/st
8537 1099	50	p/st
8537 1099	60	p/st
8548 9090	60	p/st
8548 9090	65	p/st
8708 3010	10	p/st
8708 3091	20	p/st
8708 3091	30	p/st

CN	TARIC	SUPPLEMENTARY UNIT
8708 9135	10	p/st
8708 9435	20	p/st
9029 1000	30	p/st
9029 2031	10	p/st
9029 9000	20	p/st
9031 8038	50	p/st
9031 8038	60	p/st
9031 8098	30	p/st

(c) the following rows for the supplementary units with the CN and TARIC codes are deleted:

CN	TARIC	SUPPLEMENTARY UNIT
3901 1010	10	m ³
3901 9090	30	m ³
8411 9900	30	p/st
8411 9900	40	p/st
8483 3038	30	p/st
8504 5095	60	p/st
8511 3000	20	p/st
8527 2900	30	p/st
8529 9092	44	p/st
8543 7090	13	p/st
8543 7090	23	p/st
8548 9090	47	p/st
8548 9090	49	p/st
8548 9090	55	p/st
9405 4039	50	p/st
9405 4099	03	p/st
9405 4099	06	p/st