



Council of the
European Union

141112/EU XXVII. GP
Eingelangt am 16/05/23

Brussels, 16 May 2023
(OR. en)

Interinstitutional File:
2023/0151(NLE)

9513/23
ADD 1

UD 104

PROPOSAL

From:	Secretary-General of the European Commission, signed by Ms Martine DEPREZ, Director
date of receipt:	16 May 2023
To:	Ms Thérèse BLANCHET, Secretary-General of the Council of the European Union
No. Cion doc.:	COM(2023) 255 final
Subject:	ANNEX to the Proposal for a COUNCIL REGULATION amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 on certain agricultural and industrial products

Delegations will find attached document COM(2023) 255 final.

Encl.: COM(2023) 255 final



EUROPEAN
COMMISSION

Brussels, 16.5.2023
COM(2023) 255 final

ANNEX

ANNEX

to the

Proposal for a COUNCIL REGULATION

amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 on certain agricultural and industrial products

ANNEX

The Annex is amended as follows:

- (1) the entries with the following serial numbers are deleted: 0.2425, 0.3140, 0.3966, 0.4030, 0.4140, 0.4305, 0.4609, 0.4733, 0.4893, 0.5018, 0.5187, 0.5788, 0.6629, 0.6654, 0.6689, 0.6781, 0.7489, 0.7972, 0.8111, 0.8112, 0.8140, 0.8311;
- (2) the following entries replace those entries that have the same serial numbers:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3227	2846 90 30 2846 90 40 2846 90 50 2846 90 60 2846 90 70 2846 90 90		Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00	0 %	-	31.12.2023
0.7389	ex 2914 29 00	55	1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of more than 90 %	0 %	-	31.12.2024
0.7722	ex 2919 90 00	55	Reaction products of phosphoryl trichloride and 2-methyloxirane (CAS RN 1244733-77-4)	0 %	-	31.12.2024
0.4058	ex 3204 20 00	10	Colourant C.I. Fluorescent Brightener 184 (CAS RN 7128-64-5) and preparations based thereon with a colourant C.I. Fluorescent Brightener 184 content of 20 % or more by weight	0 %	-	31.12.2026
0.4922	ex 3601 00 00	20	Pyrotechnical mixture in cylindrical shape or granulate form, composed of strontium nitrate or copper nitrate or basic copper nitrate in a matrix of nitroguanidine or guanidine nitrate, also containing a binder and additives, used as a component of airbag inflators ⁽¹⁾	0 %	-	31.12.2026
0.4410	ex 3903 90 90	86	Mixture containing by weight: — 45 % or more but not more than 65 % of polymers of styrene, — 30 % or more but not more than 45 % of poly(phenylene ether), and — not more than 11 % of additives	0 %	-	31.12.2023
0.6351	ex 3907 29 20	50	Poly(<i>p</i> -phenylene oxide) in the form of powder with: — a glass-transition temperature of 210 °C or more, — a weight average molecular weight (Mw) of 35 000 or more but not more than 80 000, — an inherent viscosity of 0,2 or more but not more than 0,6 dl/gram	0 %	-	31.12.2024

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5506	ex 3920 51 00	30	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 µm or more but not exceeding 125 µm	0 %	-	31.12.2023
0.8438	ex 3920 62 19	28	Non-transparent film of poly(ethylene terephthalate) or poly(vinyl difluoride): — each outer layer with a thickness of 7 µm or more but not more than 80 µm, — with a tensile strength of 300 N/cm ² or more (ASTM D-882), — with a total thickness of 200 µm or more but not more than 350 µm, and — with a width of 600 mm or more but not more than 1 600 mm, — covered on one side with a layer of a fluoropolymer, and on the other side with an adhesive and a layer of polyvinylidene difluoride, or coated on both sides with polyvinylidene difluoride or polyvinyl fluoride based on fluorinated polymer composites	0 %	-	31.12.2027
0.7056	ex 7019 61 00 ex 7019 63 00	70 30	E-fibre glass fabrics: — having a weight of 20 g/m ² or more, but not more than 214 g/m ² , — surface treated with an organosilane coupling agent, — in rolls, — having a humidity content by weight of 0,13 % or less, and — having not more than 3 hollow fibres out of 100 000 fibres, for the exclusive use in the manufacture of prepregs and copper clad laminates (1)	0 %	m ²	31.12.2026
0.8300	ex 8408 90 65 ex 8408 90 67 ex 8408 90 81	20 20 20	Compression-ignition internal combustion piston engines: — of the inline type, — with a cylinder capacity of 7 000 cm ³ or more but not more than 18 100 cm ³ , — with a power of 205 kW or more but not more than 597 kW, — with an exhaust after-treatment module, — with external width/height/depth dimensions of not more than 1 310/ — 1 300/1 040 mm or 2 005/1 505/1 300 mm or 2 005/1 505/1 800 mm, for use in the manufacture of crushing, screening, separation or compost turning machines (1)	0 %	-	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.6627	ex 8501 10 99	75	Permanently excited DC motor with — a multiple-phase winding, — an external diameter of 24 mm or more but not more than 38 mm, — a rated speed of not more than 12 000 rpm, — a power supply voltage of 8 V or more but not more than 27 V, — with or without a pulley, — with or without a gear wheel	0 %	-	31.12.2025
0.2838	ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm or a pinion, of a specified temperature range covering at least - 20°C to + 70°C	0 %	-	31.12.2023
0.7789	ex 8505 19 10	20	Arc segments of permanent magnets of agglomerated ferrite, with: — a length of 16,8 mm or more, but not more than 110,2 mm, — a width of 14,8 mm or more, but not more than 75,2 mm, — a thickness of 4,8 mm or more, but not more than 13,2 mm, for use in the manufacture of electromotor rotors ⁽¹⁾	0 %	-	31.12.2024
0.6703	ex 8507 60 00	33	Lithium-ion accumulator, with: — a length of 150 mm or more, but not more than 1 310 mm, — a width of 100 mm or more, but not more than 1 000 mm, — a height of 200 mm or more, but not more than 1 500 mm, — a weight of 75 kg or more, but not more than 200 kg, — a nominal capacity not less than 58 Ah and not more than 500 Ah, — a nominal output voltage of 230V AC (line to neutral) or a nominal voltage of 50V (± 10 %)	1.3 %	-	31.12.2023
0.7796	ex 8536 49 00	60	Relay in the shape of a cube with: — a coil operating voltage of 12 VDC (Voltage Direct Current) or more, but not more than 24 VDC (Voltage Direct Current), — a contact current carrying capacity of 5A or more, but not more than 15A, — a contact voltage of 80 VAC (Voltage Alternating Current) or more, but not more than 270 VAC (Voltage Alternating Current), — outer dimensions of 19 mm (± 0,4 mm) x 15,2 mm (± 0,4 mm) x 15,5 mm (± 0,4 mm), for use in the production of control board of household appliances ⁽¹⁾	0 %	-	31.12.2024

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4616	ex 8536 69 90	83	AC socket with a noise filter, composed of: — AC socket (for power cord connection) of 230 V, — integrated noise filter composed of capacitors and inductors, — cable connector for connecting an AC socket with the PDP (Plasma display panel) power supply unit, whether or not equipped with a metal support, which joins the AC socket to the PDP TV set	0 %	p/st	31.12.2024
0.6507	ex 8537 10 98	50	Electronic control unit BCM (Body Control Module) or IBM (Integrated Body Control Module) or similar: — comprising at least a plastic box with printed circuit board, with operating direct voltage of 9 V or more, but not more than 16 V, — whether or not with metal holder, — able to control, evaluate and manage functions of assisting services in an automobile, at least wiper timing, window heating, interior lighting, seat belt reminder, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2024
0.7409	ex 8540 91 00	20	Thermionic electron source (emitter point) of lanthanum hexaboride (CAS RN 12008-21-8) or cerium hexaboride (CAS RN 12008-02-5), with electric connectors — with or without a metal housing, — with or without a graphite carbon shield mounted in a mini-Vogel type system, — with or without separate pyrolytic carbon blocks used as heating elements, and — a cathode temperature of less than 1 800 K at a filament current of 1,26 A	0 %	-	31.12.2027
0.2434	ex 8548 00 90	44	Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing	0 %	p/st	31.12.2023
0.8279	ex 8708 40 20	80	Transmission gearbox without torque converter, with: — dual clutch, — 7 or more forward gears, — 1 reverse gear, — a maximum torque of 390 Nm, — whether or not with electric motor integrated, — a height of 400 mm or more but not more than 600 mm, — a width 350 mm or more but not more than 600 mm, and — a weight of 70 kg or more but not more than 110 kg, for use in the manufacture of motor vehicles of Heading 8703 (1)	0 %	p/st	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7710	ex 8714 99 50 ex 8714 99 50	11 91	Deraillleur gears, consisting of: — rear deraillleur and mounting articles, — with or without front deraillleur, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	p/st	31.12.2024
0.7708	ex 8714 99 90	40	Stem for bicycle handlebars, for use in the manufacture of bicycles (including electric bicycles) (1)	0 %	p/st	31.12.2024
0.7973	ex 9002 11 00	23	Lens with: — motorized focus, zoom, aperture, — electronically switchable infrared cut filter, — an adjustable focal length not less than 2,7 mm and not more than 55mm, — a weight of not more than 120 g, — a length of less than 70 mm, — a diameter of not more than 70 mm	0 %	-	31.12.2025

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013. ';

(3) the following entries are inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8448	ex 2835 10 00	40	Calcium phosphinate (CAS RN 7789-79-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8520	ex 2840 20 90	20	Barium borate (CAS RN 13701-59-2) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8492	ex 2903 99 80	18	1-Fluoronaphthalene (CAS RN 321-38-0) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8482	ex 2907 29 00	13	4,4'-Methylenedi-2,6-xylenol (CAS RN 5384-21-4) with a purity by weight of 98,5 % or more	0 %	-	31.12.2027
0.8495	ex 2915 90 30	20	Chloromethyl dodecanoate (CAS RN 61413-67-0) with a purity by weight of 97 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8457	ex 2915 90 70	53	3-Chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8489	ex 2916 39 90	40	Ethyl 4-bromo-3-(bromomethyl)benzoate (CAS RN 347852-72-6) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8509	ex 2918 19 98	25	(S)-2-Hydroxy-2-phenylacetic acid (CAS RN 17199-29-0) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8511	ex 2920 90 10	85	Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99,9 % or more	3.2 %	-	31.12.2023
0.8490	ex 2920 90 70	70	4,4,5,5-Tetramethyl-1,3,2-dioxaborolane (CAS RN 25015-63-8) with a purity by weight of 97 % or more, containing not more than 1 % of the stabiliser triethylamine (CAS RN 121-44-8)	0 %	-	31.12.2027
0.8477	ex 2921 19 99	35	N-Ethyl-N-isopropylpropan-2-amine 2-(difluoromethoxy)acetate with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8473	ex 2922 50 00	45	(S)-2-Amino-2-(3-fluoro-5-methoxyphenyl)ethanol hydrochloride (CAS RN 2095692-22-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8462	ex 2926 90 70	31	Lambda-cyhalothrin (ISO) (CAS RN 91465-08-6) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8474	ex 2928 00 90	53	Ethyl chloro[(4-methoxyphenyl)hydrazono]acetate (CAS RN 27143-07-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8451	ex 2929 10 00	65	Ethyl isocyanate (CAS RN 109-90-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8510	ex 2930 90 98	36	Anhydrous potassium O-isopentyl-dithiocarbonate (CAS RN 928-70-1) with a purity by weight of 90 % or more	0 %	-	31.12.2027
0.8447	ex 2930 90 98	39	Thiodiacetic acid (CAS RN 123-93-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8481	ex 2930 90 98	41	2,2'-Diallyl-4,4'-sulphonyldiphenol (CAS RN 41481-66-7) with a purity by weight of 96 % or more	0 %	-	31.12.2027
0.8478	ex 2932 20 90	28	(R)-3-(3,4-difluoro-2-methoxyphenyl)-4,5-dimethyl-5-(trifluoromethyl)furan-2(5H)-one (CAS RN 2875066-35-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8452	ex 2933 29 90	38	Cyazofamid (ISO) (CAS RN 120116-88-3) with a purity by weight of 94 % or more	0 %	-	31.12.2027
0.8485	ex 2933 39 99	08	Fluazinam (ISO) (CAS RN 79622-59-6) with a purity by weight of 97 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8456	ex 2933 59 95	32	5-Chloro-3-nitropyrzolo[1,5-a]pyrimidine (CAS RN 1363380-51-1) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8484	ex 2933 59 95	44	1,4,5,6-Tetrahydro-1,2-dimethylpyrimidine (CAS RN 4271-96-9) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8488	ex 2933 59 95	46	Trilaciclib (CAS RN 1374743-00-6) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8455	ex 2933 99 80	43	4-([1,2,4]Triazolo[1,5-a]pyridin-7-yloxy)-3-methylaniline (CAS RN 937263-71-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8487	ex 2934 99 90	07	Cedazuridine (INN) (CAS RN 1141397-80-9) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8472	ex 2934 99 90	08	(<i>R</i>)- <i>tert</i> -butyl 2-(6-(5-chloro-2-((tetrahydro-2H-pyran-4-yl)amino)pyrimidin-4-yl)-1-oxoisindolin-2-yl)propanoate (CAS RN 2095665-45-3) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8449	ex 2934 99 90	09	3-[2-((2 <i>R</i> ,3 <i>S</i>)-3-[(1 <i>R</i>)-1-[[<i>tert</i> -butyl(dimethyl)silyl]oxy}ethyl]-4-oxoazetidin-2-yl)propanoyl]-4,4-dimethyl-1,3-oxazolidin-2-one (isomeric mixture of CAS RNs 114341-89-8 and 114418-63-2) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8479	ex 2935 90 90	16	2-Bromo- <i>N</i> -(4,5-dimethyl-1,2-oxazol-3-yl)- <i>N</i> -(methoxymethyl) benzene-1-sulfonamide (CAS RN 415697-57-3) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8467	ex 2935 90 90	26	5-(2-Fluorophenyl)-1-(pyridin-3-ylsulfonyl)-1 <i>H</i> -pyrrole-3-carbaldehyde (CAS RN 881677-11-8) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.8471	ex 3824 99 92	73	<i>Tri</i> -C8-10-alkyl amines (CAS RN 68814-95-9) with a purity by weight of 95 % or more	0 %	-	31.12.2027
0.8463	ex 3824 99 92	74	Reaction mass containing by weight: — 22,4 % or more, but not more than 26,4 % of 3-methylphenyl diphenyl phosphate (CAS RN 69500-28-3); — 17,3 % or more, but not more than 21,3 % of 4-methylphenyl diphenyl phosphate (CAS RN 78-31-9); — 5 % or more, but not more than 9 % of bis(3-methylphenyl) phenyl phosphate (CAS RN 34909-68-7); — 8,9 % or more, but not more than 12,9 % of 3-methylphenyl 4-methylphenyl phenyl phosphate (CAS RN 222165-66-4); — 26,9 % or more, but not more than 30,9 % of triphenyl phosphate (CAS RN 115-86-6)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8486	ex 3824 99 92	75	Mixture, containing by weight: — not more than 75 % of tetrabutyltin (CAS RN 1461-25-2), — not more than 20 % of tributyltin chloride (CAS RN 1461-22-9), — not more than 4 % of dibutyltin dichloride (CAS RN 683-18-1), for use in the production of butyltin compounds used in glass manufacture and tributyltin chloride used as a catalyst in the pharmaceutical industry (1)	3.2 %	-	31.12.2027
0.8506	ex 3824 99 92	79	Mixture, containing by weight: — tributyltin chloride (CAS RN 1461-22-9) with a purity by weight of 80 % or more, — not more than 5 % tetrabutyltin (CAS RN 1461-25-2), — not more than 6 % dibutyltin dichloride (CAS RN 683-18-1), — not more than 11 % o-xylene (CAS RN 95-47-6), for use in the production of tributyltin chloride used as a catalyst in the pharmaceutical industry (1)	3.2 %	-	31.12.2027
0.8517	ex 3824 99 92	83	1-(Cedr-8-en-9-yl)ethanone (CAS RN 32388-55-9) with a purity by weight of 70 % or more, but not more than 90 %	0 %	-	31.12.2024
0.8499	ex 3824 99 92	86	Tall oil <i>N,N</i> -dimethyl fatty amides (CAS RN 68308-74-7) with a purity by weight of 99 % or more	0 %	-	31.12.2027
0.8498	ex 3824 99 93	33	Preparation containing by weight — 60 % or more but not more than 70 % of calcium <i>rel</i> -(1 <i>R</i> ,2 <i>S</i>)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1), — 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1), — 1 % or more but not more than 5 % of CI Pigment Blue 29 (CAS RN 57455-37-5) and — 1 % or more but not more than 5 % of CI Pigment Violet 15 (CAS RN 12769-96-9)	0 %	-	31.12.2027
0.8497	ex 3824 99 93	36	Preparation containing by weight 60 % or more but not more than 70 % of calcium <i>rel</i> -(1 <i>R</i> ,2 <i>S</i>)-cyclohexane-1,2-dicarboxylate (CAS RN 491589-22-1) and 30 % or more but not more than 40 % of zinc stearate (CAS RN 557-05-1)	0 %	-	31.12.2027
0.8514	ex 3824 99 96	43	2-(Ethylthio)ethanethiol functionalized silicagel with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.8491	ex 3907 29 99	70	Poly(oxy-1,4-phenyleneoxy-1,4-phenylenecarbonyl-1,4-phenylene) (CAS RN 29658-26-2) containing by weight not more than 35 % of additives	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8504	ex 4009 31 00 ex 4009 32 00	10 20	Multilayered rubber pipe, reinforced with aramide fabric, whether or not having polyamide connection elements and steel clamps, for use in the manufacture of automotive heat exchangers and/or condenser in automotive air conditioning systems (1)	0 %	-	31.12.2027
0.8480	ex 7326 90 98	60	Vane ring of a kind for fastening gas flow control blades: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92 mm, — with holes for holding the gas flow control blades, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027
0.8512	ex 7326 90 98	70	Disc of a kind for ensuring the gas flow channel width: — of iron or steel alloy, — with a heat resistance of 830 °C or more but not more than 1 050 °C, — with an external diameter of not more than 92,5 mm, — with an internal diameter of not more than 62 mm, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027
0.8464	ex 7609 00 00	40	Flame brazed aluminium block for connecting tubes in automotive heat exchangers and/or turbocharged air coolers and/or automatic transmission coolers: — with extruded, bent connection tubes with an outer diameter of 5 mm or more, but not more than 25 mm, — with a weight of 0,02 kg or more, but not more than 0,25 kg, for use in the manufacture of cooling system in vehicles of Chapter 87 (1)	0 %	p/st	31.12.2027
0.8503	ex 7609 00 00	50	Machined aluminium components: — containing by weight 0,55 %, or more but not more than 0,61 % of magnesium, — containing by weight 0,55 %, or more but not more than 0,61 % of silicon, — with a hardening state of T5 or T6, — with a mass of 0,05 kg or more, but not more than 0,2 kg, for use in the manufacture of CO ₂ cooling systems in motor vehicles (1)	0 %	p/st	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8493	ex 7609 00 00	60	Aluminium connection block: — with a weight of 3 g or more but not more than 400 g, — manufactured from 6061-T6 or 6060-T6 or 6082-T6 aluminium grade, — being an integral part of an air conditioning hose assembly or oil cooling line hose assembly or air brake line hose assembly or water cooling line hose assembly, — with holes (sockets) or splines (pilots) or threads that allow installation in an automotive or other air conditioning system (also understood as installation in the line), — with sockets designed for brazing or fastening, — with at least 1 through-hole with a diameter of 3 mm or more but not more than 25 mm, for the manufacture of automotive cooling and air conditioning systems (1)	0 %	p/st	31.12.2027
0.8466	ex 8409 91 00	33	Camshaft carrier for a spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, with: — a weight of 4,0 kg or more but not more than 5,5 kg, — a wall thickness of 2,0 mm or more but not more than 6,0 mm, for use in the manufacture of motor vehicle engines (1)	0 %	p/st	31.12.2027
0.8469	ex 8409 91 00	38	Crankcase for 4-cylinder spark-ignition piston internal combustion engine, made of ADC12 aluminium alloy, for use in the manufacture of motor vehicle engines (1)	0 %	-	31.12.2027
0.8483	ex 8414 90 00	15	Fan assembly made of aluminium and magnesium alloy: — with an outer diameter of 54 mm or more but not more than 130 mm, — with a height of 8 mm or more but not more than 30 mm, — with two discs connected by blades of involute shape, — with or without dowel, and with or without washer, for use in the manufacture of electromotors (1)	0 %	-	31.12.2027
0.8494	ex 8414 90 00	25	Scroll type compressor housing of an aluminium alloy of a kind with: — a heat resistance of 200 °C or more but not more than 250 °C, — one or more fixing points suitable for mounting an actuator, for use in the manufacture of turbochargers (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8465	ex 8415 90 00	15	Electrically welded manifolds for the condenser in automotive air conditioning systems: — consisting of a tube produced by stamping an aluminium strip and joining the edges by electric arc welding, — containing internal baffles responsible for the proper flow of coolant, — with a length of 190 mm or more, but not more than 460 mm, — with a diameter of 9 mm or more, but not more than 42 mm, — with a weight of 0,01 kg or more, but not more than 0,45 kg, — whether or not having aluminium connection blocks, used in the production of air conditioning systems in vehicles of Chapter 87 (1)	0 %	p/st	31.12.2027
0.8458	ex 8501 53 50	50	Asynchronous traction motor, with: — a continuous power of 140 kW or more but not more than 180 kW, — a liquid cooled system, — a total length of 580 mm or more but not more than 730 mm, — a total width of 550 mm or more but not more than 670 mm, — a total height of 510 mm or more but not more than 630 mm, — with a weight of not more than 390 kg, — with or without reduction gear, — with or without starter generator, — 2 mounting points, for use in the manufacture of the electric drive of hybrid buses (1)	0 %	-	31.12.2027
0.8508	ex 8505 11 10	78	Two permanent magnets made of a praseodymium-neodymium alloy, in a rectangular steel holder with an outer casing of rubber with outer dimensions: — a length of 200 mm or more but not more than 205 mm, — a width of 58 mm or more but not more than 62 mm, — a height of 25 mm or more but not more than 30 mm, with a stud mounted in the middle	0 %	-	31.12.2027
0.8453	ex 8512 30 90	40	Device for simulating engine sound at reduced speed of a hybrid or electric vehicle: — containing at least printed circuit board and loudspeaker, — in a plastic housing with a holder, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8460	ex 8537 10 91	43	Electronic suspension control unit with: — a printed circuit board in plastic housing, — LIN and CAN buses, — a programmable memory, — a signal processor, — an operating direct current voltage of 9 V or more but not more than 16 V, — at least one connector, — whether or not with metal mounting bracket, for use in the manufacture of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.8461	ex 8708 50 20	18	Propeller shaft for torque transmission from the gearbox to the rear axle, consisting of: — two cardan rods, — central universal joint, — central bearing with suspension in a plastic cover, — universal joints on both ends of the shaft, — slip, tube and end yokes, — of a length of 1,4 m or more but not more than 2,4 m, for use in the production of goods of Chapter 87 (1)	0 %	-	31.12.2027
0.8507	ex 8714 99 90	50	Rear air shock absorber in form of a pneumatic spring element with oil damper for use in the manufacture of bicycles, including electrical bicycles (1)	0 %	-	31.12.2027

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013. '.