

Council of the European Union

> Brussels, 24 April 2020 (OR. en)

Interinstitutional File: 2020/0062(NLE) 7549/20 ADD 1

UD 64

From:	Secretary-General of the European Commission, signed by Mr Jordi AYET PUIGARNAU, Director
date of receipt:	24 April 2020
To:	Mr Jeppe TRANHOLM-MIKKELSEN, Secretary-General of the Council of the European Union
No. Cion doc.:	COM(2020) 156 final
Subject:	ANNEX to the Proposal for a COUNCIL REGULATION amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products

Delegations will find attached document COM(2020) 156 final.

Encl.: COM(2020) 156 final

ECOMP 2 B



EUROPEAN COMMISSION

> Brussels, 24.4.2020 COM(2020) 156 final

ANNEX

## ANNEX

to the

## Proposal for a COUNCIL REGULATION

amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products

## <u>ANNEX</u>

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

(1) all asterisks and the endnote (\*), containing the text 'A newly introduced measure or a measure with amended conditions. Where more than one CN code is listed as falling within the scope of the measure, the asterisk concerns the entire measure. ', are deleted;

(2) the rows having the following serial numbers are deleted:

Serial Number
0.2706
0.2972
0.3650
0.3886
0.3894
0.3895
0.4004
0.4039
0.4177
0.4647
0.4648
0.4751
0.5504
0.5615
0.5929
0.6601
0.6745
0.7784
0.7803

;

(3) the rows set out in the table below replace those in the Annex to Regulation (EU) No1387/2013 having the same serial numbers:

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7288	ex 2841 50 00	11	Potassium dichromate (CAS RN 7778-50-9) with a purity by weight of 99 % or more	2 %	-	31.12.2021
0.3419	ex 2850 00 20	80	Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more	0 %	-	31.12.2024
0.2583	ex 2903 89 80	45	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 <sup>6,9</sup> .0 <sup>2,13</sup> .0 <sup>5,10</sup> ]octadeca-7,15-diene (CAS RN 13560- 89-9) with purity by weight of 99 % or more	2 %	-	31.12.2021
0.2942	ex 2919 90 00	35	2,2'-Methylenebis(4,6-di-tert-butylphenyl) phosphate, monosodium salt (CAS RN 85209-91-2) with a purity by weight of 95 % or more, with particles greater than 100 $\mu$ m used in the manufacture of nucleating agents with a particle size (D90) no greater than 35 $\mu$ m as measured by a light scattering technique <sup>(2)</sup>	0 %	-	31.12.2023
0.5037	ex 2922 49 85	17	Glycine (CAS RN 56-40-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8)	0 %	-	31.12.2020
0.3689	ex 2924 19 00	23	Acrylamide (CAS RN 79-06-1) with a purity by weight of 97 % or more	2 %	-	31.12.2021
0.6259	ex 2926 90 70	26	Cyfluthrin (ISO) (CAS RN 68359-37-5) with a purity by weight of 95,5 % or more for the use in the manufacture of biocidal products <sup>(2)</sup>	0 %	-	31.12.2024
0.2656	ex 2931 39 90	38	N-(Phosphonomethyl)iminodiacetic acid (CAS RN 5994- 61-6) containing by weight not more than 15 % of water, and with a dry weight purity of 97 % or more	0 %	-	31.12.2024
0.7811	ex 2933 19 90	33	Fipronil (ISO) (CAS RN 120068-37-3) with a purity by weight of 95 % or more for the use in the manufacture of veterinary medicine (2)	0 %	-	31.12.2024
0.4346	ex 2934 20 80	25	1,2-Benzisothiazol-3(2H)-one (CAS RN 2634-33-5) in the form of a powder with a purity by weight of 95 % or more, or in an aqueous mixture containing by weight 20 % or more of 1,2-benzisothiazol-3(2H)-one	0 %	-	31.12.2022
0.5134	ex 3204 11 00	45	<ul> <li>Preparation of dispersion dyes, containing:</li> <li>C.I. Disperse Orange 61 (CAS RN 12270-45-0) or Disperse Orange 288 (CAS RN 96662-24-7),</li> <li>C.I. Disperse Blue 291:1 (CAS RN 872142-01-3),</li> <li>C.I. Disperse Violet 93:1 (CAS RN 122463-28-9),</li> <li>whether or not containing C.I. Disperse Red 54 (CAS RN 6657-37-0)</li> </ul>	0 %	-	31.12.2020
0.7318	ex 3603 00 60	10	Igniters for gas generators with an overall maximum length of 20,34mm or more but not more than 29,4 mm and a pin length of 6,68 mm ( $\pm$ 0,3 mm) or more but not more than 7,54 mm ( $\pm$ 0,3 mm)	0 %	-	31.12.2022

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.5718	ex 3811 21 00	85	<ul> <li>Additives:</li> <li>— containing more than 20 % or more but not more than 45 % by weight of mineral oils,</li> <li>— based on a mixture of branched dodecylphenol sulfide calcium salts, whether or not carbonated, for use in the manufacture of blends of additives</li> <li><sup>(2)</sup></li> </ul>	0 %	-	31.12.2022
0.7512	ex 3811 29 00	18	Additive consisting of dihydroxy butanedioic acid - (mixed C12-16-alkyl and C13-rich C11-14-isoalkyl) diester, for use in the manufacture of engine oils	0 %	-	31.12.2023
0.3069	ex 3824 99 92	88	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated (CAS RN 9014-85-1)	0 %	-	31.12.2020
0.4719	ex 3824 99 93	35	Paraffin with a level of chlorination of 70 % or more (CAS RN 63449-39-8)	0 %	-	31.12.2024
0.6953	ex 3901 40 00	20	<ul> <li>Octene linear low-density polyethylene (LLDPE) in the form of pellets with:</li> <li>10 % or more but not more than 20 % by weight of octene,</li> <li>a melt flow ratio of 9,0 or more, but not more than 10,0 (using ASTM D1238 10.0/2.16),</li> <li>a melt index (190°C/2.16 kg) of 0,4 g / 10 min or more but not more than 0,6 g / 10 min,</li> <li>a density of 0,909 g/cm<sup>3</sup> or more, but not more than 0,913 g/cm<sup>3</sup> using ASTM D4703,</li> <li>a gel area per 24,6 cm<sup>3</sup> of not more than 20 mm<sup>2</sup>, and</li> <li>an anti-oxidant level of not more than 240 ppm</li> </ul>	0 %	m <sup>3</sup>	31.12.2020
0.5161	ex 3919 10 80 ex 3919 90 80	70 75	<ul> <li>Rolls of polyethylene foil:</li> <li>self-adhesive on one side,</li> <li>of a total thickness of 0,025 mm or more, but not more than 0,09 mm,</li> <li>of a total width of 60 mm or more, but not more than 1 110 mm,</li> <li>for use in the manufacture of products of headings 8521 or 8528 for the protection purposes</li> </ul>	0 %	-	31.12.2021
0.4947	ex 3919 90 80	65	Self-adhesive film with a thickness of 40 $\mu$ m or more, but not more than 475 $\mu$ m, consisting of one or more layers of transparent, metallized or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner	0 %	-	31.12.2024
0.3241	ex 3920 10 25	30	<ul> <li>Mono-layered High-Density Polyethylene film:</li> <li>— containing by weight 99% or more of polyethylene,</li> <li>— with a thickness of 12 μm or more but not more than 20 μm,</li> <li>— with a length of 4000 m or more but not more than 7000 m,</li> <li>— with a width of 600 mm or more but not more than</li> </ul>	0 %	-	31.12.2023

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			900 mm			
0.3312	ex 3921 90 60	35	Ion-exchange membranes based on a fabric coated on both sides with fluorinated plastic material, for use in chlor- alkali electrolytic cells	0 %	-	31.12.2023
0.6708	ex 4009 42 00	20	Rubber brake hose with: — textile strings, — a wallet thickness of 3,2 mm, — a metal hollow terminal pressed on both ends, and — one or more mounting brackets, for use in the manufacture of goods of chapter 87 <sup>(2)</sup>	0 %	-	31.12.2024
0.7372	ex 5311 00 90	10	<ul> <li>Plain-woven fabric of paper yarns glued on a tissue paper layer:</li> <li>— with a weight of 190 g/m2 or more but not more than 280 g/m2, and</li> <li>— cut into rectangles with a side length of 40 cm or more but not more than 140 cm</li> </ul>	0 %	-	31.12.2022
0.2546	ex 6903 90 90	30	Silicon carbide reactor tubes and holders having a softening point of 1 400 °C or higher	0 %	-	31.12.2023
0.7619	ex 7006 00 90	40	<ul> <li>Plates of sodalime glass of STN (Super Twisted Nematic) quality having:</li> <li>a length of 300 mm or more but not more than 1 500 mm,</li> <li>a width of 300 mm or more but not more than 1 500 mm,</li> <li>a thickness of 0,5 mm or more but not more than 1,1 mm,</li> <li>an indium-tin-oxide coating with a resistance of 80 Ohms or more, but not more than 160 Ohms on one side,</li> <li>with or without a multi layer anti-reflection-coating on the other side and machined (chamfered) edges</li> </ul>	0 %	-	31.12.2023
0.7341	ex 7413 00 00	20	Loudspeaker centering ring, consisting of one or more vibration dampers and minimum 2 non-insulated copper cables, therein woven or pressed	0 %	-	31.12.2022
0.3928	ex 7616 99 90	15	Honeycomb aluminium blocks for use in the manufacture of aircraft parts	0 %	p/st	31.12.2023
0.6730	ex 8101 96 00	10	<ul> <li>Tungsten wire containing by weight 99% or more of tungsten with:</li> <li>— a maximum cross-sectional dimension of not more than 50 μm</li> <li>— a resistance of 40 Ohm or more but not more than 300 Ohm at length of 1 metre</li> </ul>	0 %	-	31.12.2020
0.5838	ex 8105 90 00	10	Bars or wires made of cobalt alloy containing, by weight: — 35 % (± 2 %) cobalt, — 25 % (± 1 %) nickel,	0 %	-	31.12.2023

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			<ul> <li>19 % (± 1 %) chromium and</li> <li>7 % (± 2 %) iron,</li> <li>conforming to the material specifications AMS 5842</li> </ul>			
0.5570	ex 8207 30 10	10	Set of transfer and/or tandem press tools for cold-forming, pressing, drawing, cutting, punching, bending, calibrating, bordering and throating of metal sheets, for use in the manufacture of frame parts or body parts of motor vehicles <sup>(2)</sup>	0 %	p/st	31.12.2022
0.5024	ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8503 00 99 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97	30 40 30 50 43 40 55 70 55 22	<ul> <li>Silicone or plastic keyboards, comprising:</li> <li>parts of common metal, and</li> <li>whether or not comprising parts of plastic,</li> <li>epoxy resin reinforced with fiberglass or wood,</li> <li>whether or not printed or surface-treated,</li> <li>with or without electrical conductors</li> <li>with or without a membrane bonded to the keyboard,</li> <li>with or without mono or multilayer protective film</li> </ul>	0 %	p/st	31.12.2020
0.7670	ex 8409 91 00	25	<ul> <li>Air intake module for engine cylinders consisting of:</li> <li>a suction pipe,</li> <li>a pressure sensor,</li> <li>an electric throttle,</li> <li>hoses,</li> <li>brackets,</li> <li>for use in the manufacture of engines of motor vehicles</li> </ul>	0 %	-	31.12.2023
0.7718	ex 8409 99 00	75	<ul> <li>High pressure fuel rail of galvanized ferrite-pearlite steel with:</li> <li>at least one pressure sensor and one valve,</li> <li>a length of 314 mm or more but not more than 322 mm,</li> <li>an operating pressure not more than 225 MPa,</li> <li>an inlet temperature not more than 95°C,</li> <li>ambient temperature of -45°C or more but not more than 145°C,</li> <li>for use in the manufacture of compression ignition engines of motor vehicles <sup>(2)</sup></li> </ul>	0 %	-	31.12.2024
0.7377	ex 8481 80 59	40	<ul> <li>Flow-control valve:</li> <li>made of steel,</li> <li>with an outlet hole with a diameter of at least 0,05 mm, but not more than 0,5 mm,</li> <li>with an inlet hole with a diameter of at least 0,1 mm, but not more than 1,3 mm,</li> <li>with chromium nitride coating,</li> <li>with a surface roughness of Rp 0,4</li> </ul>	0 %	-	31.12.2022
0.7381	ex 8481 80 59	50	Electromagnetic valve for quantity control with: — a plunger, — a solenoid with a of coil resistance of at least 1,85 Ohm, but not more than 8,2 Ohm	0 %	-	31.12.2022

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7604	ex 8484 20 00	20	Mechanical face sealing device made of two movable rings (one ceramic mating, having a thermal conductivity lower than 80W/Mk and the other carbon sliding), one spring and a nitrile sealant on the external side	0 %	-	31.12.2023
0.5577	ex 8501 31 00	50	<ul> <li>DC motors, brushless, with:</li> <li>an external diameter of 80 mm or more, but not more than 200 mm,</li> <li>a supply voltage of 9 V or more, but not more than 16 V,</li> <li>an output at 20 °C of 300 W or more, but not more than 750 W,</li> <li>a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm,</li> <li>a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm,</li> <li>with or without the rotor angle position sensor of resolver type or Hall effect type,</li> <li>with or without the pulley, of the kind used in power steering systems for cars</li> </ul>	0 %	-	31.12.2022
0.4855	ex 8501 33 00 ex 8501 40 80 ex 8501 53 50	30 50 10	<ul> <li>Electric drive for motor vehicles, with an output of not more than 315 kW:</li> <li>— with an AC or DC motor whether or not with transmission,</li> <li>— with or without power electronics</li> </ul>	0 %	-	31.12.2021
0.5783	ex 8503 00 99	40	Fuel cell membrane, in rolls or sheets, with a width of not more than 150 cm, for use in the manufacture of fuel cells in heading 8501	0 %	p/st	31.12.2022
0.7029	ex 8505 11 00	47	<ul> <li>Articles in the form of a triangle, square or rectangle, whether or not arched or with rounded corners intended to become permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:</li> <li>a length of 9 mm or more but not more than 105 mm,</li> <li>a width of 5 mm or more but not more than 105 mm, and</li> <li>a height of 2 mm or more but not more than 55 mm</li> </ul>	0 %	-	31.12.2021
0.7511	ex 8505 19 90	60	<ul> <li>Article of agglomerated ferrite in the shape of a half-sleeve or a quarter-sleeve, or with rounded corners, to become a permanent magnet after magnetization</li> <li>of a length of 10 mm or more but not more than 100 mm (± 1 mm),</li> <li>of a width of 10 mm or more but not more than 100 mm (± 1 mm),</li> <li>of a thickness of 2 mm or more but not more than 15 mm (± 0,15 mm)</li> </ul>	0 %	-	31.12.2023
0.6703	ex 8507 60 00	33	<ul> <li>Lithium-ion accumulator, with:</li> <li>a length of 150 mm or more, but not more than 1,000 mm,</li> <li>a width of 100 mm or more, but not more than 1,000 mm,</li> <li>a height of 200 mm or more, but not more than</li> </ul>	1.3 %	-	31.12.2020

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			<ul> <li>1,500 mm,</li> <li>a weight of 75 kg or more, but not more than 200 kg,</li> <li>a nominal capacity not less than 150Ah and not more than 500 Ah,</li> <li>a nominal output voltage of 230V AC (Line to neutral) or a nominal voltage of 64V (+/-10 %)</li> </ul>			
0.6702	ex 8507 60 00	37	<ul> <li>Lithium-ion accumulator, with:</li> <li>a length of 1 200 mm or more, but not more than 2 000 mm,</li> <li>a width of 800 mm or more, but not more than 1 300 mm,</li> <li>a height of 2 000 mm or more, but not more than 2 800 mm,</li> <li>a weight of 1 800 kg or more, but not more than 3 000 kg,</li> <li>a nominal capacity of 2 800 Ah or more but not more than 7 200 Ah</li> </ul>	1.3 %	-	31.12.2020
0.5342	ex 8507 60 00	65	Cylindrical lithium ion cell with — 3,5 VDC to 3,8 VDC, — 300 mAh to 900 mAh, and — a diameter of 10,0 mm to 14,5 mm	1.3 %	-	31.12.2021
0.6753	ex 8507 60 00	77	<ul> <li>Lithium-ion rechargeable batteries, with:</li> <li>a length of 700 mm or more, but not more than 2 820 mm,</li> <li>a width of 935 mm or more, but not more than 1 660 mm,</li> <li>a height of 85 mm or more, but not more than 700 mm,</li> <li>a weight of 250 kgor more, but not more than 700 kg,</li> <li>a power of not more than 175 kWh,</li> <li>a nominal voltage of 400 V</li> </ul>	1.3 %	-	31.12.2020
0.6863	ex 8512 30 90	20	Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing: — a printed circuit board, — a connector, — whether or not a metal holder, for use in the manufacture of goods of chapter 87 <sup>(2)</sup>	0 %	p/st	31.12.2020
0.6689	ex 8529 90 65	28	<ul> <li>Electronic assembly comprising at least <ul> <li>a printed circuit board with,</li> <li>processors for multi-media applications and video signal processing,</li> <li>FPGA (Field Programmable Gate Array),</li> <li>Flash memory,</li> <li>operating memory,</li> <li>with or without USB, HDMI, VGA- and RJ-45 interfaces,</li> <li>sockets and plugs for connecting a LCD-display, a LED lighting and a control panel</li> </ul></li></ul>	0 %	p/st	31.12.2020

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7251	ex 8537 10 91	70	<ul> <li>Programmable motor memory controller for a voltage not exceeding 1 000 V, comprising at least:</li> <li>a printed circuit with active and passive components,</li> <li>an aluminium housing, and</li> <li>multiple connectors</li> </ul>	0 %	p/st	31.12.2022
0.6866	ex 8538 90 91 ex 8538 90 99	20 50	<ul> <li>Interior antenna for a car door locking system, comprising:</li> <li>an antenna module in a plastic housing,</li> <li>a connection cable with a plug,</li> <li>at least two mounting brackets,</li> <li>whether or not PCB including integrated circuits, diodes and transistors,</li> <li>for use in the manufacture of goods of Chapter 87</li> </ul>	0 %	p/st	31.12.2020
0.5953	ex 8538 90 99	95	Copper base plate, containing more components than Insulated Gate Bipolar Transistor (IGBT) chips and diodes with a voltage of 650 V or more but not more than 1 200 V, for use as a heatsink in the manufacture of IGBT modules (2)	0 %	p/st	31.12.2023
0.6710	ex 8544 30 00 ex 8544 42 90	60 50	Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and audio systems to a USB connector, for use in the manufacture of goods of Chapter 87	0 %	-	31.12.2020
0.6867	ex 8544 30 00	85	Extension two-core cable with two connectors, containing at least: — a rubber grommet, — a metal attachment bracket of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87	0 %	p/st	31.12.2020
0.5002	ex 8545 90 90	40	<ul> <li>Corrosion resistant, layered technical fibre substrate of a gas diffuser layer with:</li> <li>— controlled fibre length, flex strength, porosity, thermal conductance, electrical resistance,</li> <li>— a thickness of less than 600 μm,</li> <li>— a weight of less than 500 g/m<sup>2</sup></li> </ul>	0 %	m <sup>2</sup>	31.12.2020
0.7581	ex 8708 50 20 ex 8708 50 99 ex 8708 99 10 ex 8708 99 97	60 15 45 65	Car transfer case with single input, dual output, to distribute torque between front and rear axles in an aluminium housing, with dimension of not more than 565 × 570 × 510 mm, comprising: — at least an actuator, — whether or not an interior distribution by chain	0 %	-	31.12.2024
0.6711	ex 8708 80 20 ex 8708 80 35	10 10	Upper strut insulator containing: — a metal holder with three mounting screws, and — a rubber bump, for use in the manufacture of goods of Chapter 87 <sup>(2)</sup>	0 %	p/st	31.12.2020
0.6705	ex 8708 80 20	20	Rear chassis arm with a protective plastic label equipped	0 %	p/st	31.12.2020

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
	ex 8708 80 91	10	with two metal casings with pressed-in rubber silent blocks, for use in the manufacture of goods of Chapter 87			
0.6704	ex 8708 80 20 ex 8708 80 91	30 20	Rear chassis arm equipped with a ball pivot and metal casing with a pressed-in rubber silent block, for use in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2020
0.7365	ex 8708 80 99	30	<ul> <li>Surface-hardened, steel piston rod for a hydraulic or hydropneumatic shock absorber of motor vehicles:</li> <li>— with a chrome coating,</li> <li>— of a diameter of 11 mm or more, but not more than 28 mm,</li> <li>— of a length of 80 mm or more, but not more than 600 mm,</li> <li>with a threaded end or a mandrel for resistance welding</li> </ul>	0 %	-	31.12.2022
0.6687	ex 8708 95 10 ex 8708 95 99	10 20	<ul> <li>Inflatable safety cushion of high strength polyamide fibre:</li> <li>— sewn,</li> <li>— folded into three-dimensional packing form, fixed by thermal forming, or flat (unfolded) safety cushion with or without thermal forming</li> </ul>	0 %	p/st	31.12.2020
0.6686	ex 8714 10 90	10	<ul> <li>Motorcycle fork rod inner tubes:</li> <li>of SAE1541 carbon steel,</li> <li>with a hard chromium layer of 20 μm (+ 15 μm/ - 5 μm),</li> <li>having a wall thickness of 1,3 mm or more, but not more than 1,6 mm,</li> <li>having an elongation at break of 15 %,</li> <li>perforated</li> </ul>	0 %	p/st	31.12.2020
0.5692	ex 9002 11 00	20	Lenses: — measuring not more than 95 mm × 55 mm × 50 mm, — with a resolution of 160 lines/mm or better, and — with a zoom ratio of 18 times	0 %	-	31.12.2022
0.6527	ex 9029 20 31 ex 9029 90 00	20 30	Clustered instrument panel with the microprocessor control board, with or without stepping motors, LED indicators or LCD display showing at least: — speed, — engine revolutions, — engine temperature, — the fuel level, communicating via CAN-BUS and/or K-LINE protocols, of a kind used in the manufacture of goods of Chapter 87	0 %	p/st	31.12.2024
0.5025	ex 9401 90 80	10	Ratchet disk for use in the manufacture of reclining car seats	0 %	p/st	31.12.2020

(2) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)

(4) the following rows are added or inserted according to the order of the first CN and TARIC codes of the corresponding measure indicated in the second and third column, respectively:

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7897	2825 20 00	10	Lithium hydroxide monohydrate (CAS RN 1310- 66-3)	2.6 %	-	31.12.2020
0.7895	2903 72 00	10	Dichloro-1,1,1-trifluoroethane (CAS RN 306-83- 2) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7826	2903 79 30	30	1-Bromo-5-chloropentane (CAS RN 54512-75-3) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7914	2905 39 95	70	2-methylpropane-1,3-diol (CAS RN 2163-42-0) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7828	2909 30 38	50	2-(1-Adamantyl)-4-Bromoanisole (CAS RN 104224-63-7) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7846	2909 50 00	40	2-methoxy-4-(trifluoromethoxy)phenol (CAS RN 166312-49-8) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7910	2909 60 00	50	Solution of 3,6,9-(ethyl and/or propyl)-3,6,9- trimethyl-1,2,4,5,7,8-hexoxonanes (CAS RN 1613243-54-1) in mineral spirits (CAS RN 1174522-09-8), containing by weight 25 % or more, but not more than 41 % of the hexoxonanes	0 %	-	31.12.2024
0.7824	2914 50 00	15	1,1-dimethoxyacetone (CAS RN 6342-56-9) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7834	2915 40 00	10	Ethyl trichloroacetate (CAS RN 515-84-4) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7830	2915 40 00	20	Sodium trichloroacetate (CAS RN 650-51-1) with a purity by weight of 96 % or more	0 %	-	31.12.2024
0.7899	2915 90 70	18	Myristitic acid, lithium salt (CAS RN 20336-96- 3) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7827	2916 39 90	27	Methyl 6-Bromo-2-naphthoate (CAS RN 33626- 98-1) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7845	2916 39 90	22	6-bromo-2-fluoro-3-(trifluoromethyl)benzoic acid (CAS RN 1026962-68-4) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7880	2917 19 80	45	Iron fumarate (CAS RN 141-01-5) with a purity by weight of 93 % or more	0 %	-	31.12.2024

;

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7907	2918 19 98	50	12-Hydroxyoctadecanoic acid (CAS RN 106-14- 9) with a purity of 90 % or more for the manufacture of polyglycerin-poly-12- hydroxyoctadecanoic acid esters	0 %	-	31.12.2024
0.7864	2918 30 00	35	3-Oxocyclobutane-1-carboxylic acid with a purity by weight of 98 % or more (CAS RN 23761-23- 1)	0 %	-	31.12.2024
0.7898	2920 29 00	80	2,4,8,10-tetrakis(1,1-dimethylethyl)-6-(2- ethylhexyloxy)-12H dibenzo[d,g][1,3,2]dioxaphosphocin (CAS RN 126050-54-2) with a content of 95 % or more by weight (CAS RN 126050-54-2)	0 %	-	31.12.2024
0.7894	2921 51 90	10	N-(4-Chlorophenyl)benzene-1,2-diamine (CAS RN 68817-71-0) with a purity by weight of 97 % or more	0 %	-	31.12.2024
0.7860	2922 19 00	15	<ul> <li>Aqueous solution, containing by weight:</li> <li>73 % or more 2-amino-2-methyl-1-propanol (CAS RN 124-68-5),</li> <li>4,5 % or more, but not more than 27 % water (CAS RN 7732-18-5)</li> </ul>	0 %	-	31.12.2024
0.7853	2922 49 85	13	O-Benzylglycine p-toluenesulphonate (CAS RN 1738-76-7), with a purity by weight of 93 % or more	0 %	-	31.12.2024
0.7879	2923 90 00	50	Betaine hydrochloride (CAS RN 590-46-5), with a purity by weight of 93 % or more	0 %	-	31.12.2024
0.7841	2924 29 70	47	(S)-tert-butyl (1-amino-3-(4-iodophenyl)-1- oxopropan-2-yl)carbamate (CAS RN 868694-44- 4) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7832	2925 29 00	50	(Chloromethylene)dimethyliminium chloride (CAS RN 3724-43-4) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7833	2930 90 98	31	(p-toluenesulphonyl)methyl isocyanide (CAS RN 36635-61-7) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7859	2930 90 98	29	4-amino-5-(ethylsulfanyl)-2-methoxybenzoic acid (CAS RN 71675-86-0) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7838	2932 20 90	53	(R)-4-propyldihydrofuran-2(3H)-one (CAS RN 63095-51-2) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7855	2932 99 00	37	4-(2-butyl-1-benzofuran-3-carbonyl)-2,6- diiodophenol (CAS RN 1951-26-4) with a purity by weight of 99 % or more	0 %	-	31.12.2024

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7903	2933 19 90	13	3-(Difluoromethyl)-5-fluoro-1-methyl-1H- pyrazole-4-carbonyl fluoride (CAS RN 1255735- 07-9) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7918	2933 19 90	23	Fluindapyr (ISO) (CAS RN 1383809-87-7) with a purity by weight of 96 % or more	0 %	-	31.12.2024
0.7835	2933 19 90	17	1,3-dimethyl-1H-pyrazole (CAS RN 694-48-4) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7836	2933 19 90	27	3-(3,3,3-trifluoro-2,2-dimethylpropoxy)-1H- pyrazole-4-carboxylic acid (CAS RN 2229861- 20-3) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7844	2933 39 99	74	4-Aminopyridine-2-carboxamide (CAS RN 100137-47-1) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7906	2933 39 99	81	4-Hydroxy-3-pyridinesulphonic acid (CAS RN 51498-37-4) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7866	2933 39 99	82	Picloram (ISO) (CAS RN 1918-02-1) containing by weight not more than 15 % of water and with a dry weight purity of 92 % or more	0 %	-	31.12.2024
0.7825	2933 59 95	68	Guanine (CAS RN 73-40-5) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7839	2933 99 80	66	(6-(4-fluorobenzyl)-3,3-dimethyl-2,3-dihydro-1H- pyrrolo[3,2-b]pyrid-5-yl)methanol (CAS RN 1799327-42-6) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7843	2934 99 90	17	(S)-4-(tert-butoxycarbonyl)-1,4-oxazepane-2- carboxylic acid (CAS RN 1273567-44-4) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7842	2934 99 90	69	3-methyl-5-(4,4,5,5-tetramethyl-1,3,2- dioxaborolan-2-yl)benzo[d]oxazol-2(3H)-one (CAS RN 1220696-32-1) with a purity by weight of 95 % or more	0 %	-	31.12.2024
0.7837	2934 99 90	29	(2R,5S)-tert-butyl 4-benzyl-2-methyl-5-(((R)-3- methylmorpholino)methyl)piperazine-1- carboxylate (CAS RN 1403902-77-1) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7840	2934 99 90	33	(2R,3R,5R)-5-(4-amino-2-oxopyrimidin-1(2H)- yl)-2-((benzoyloxy)methyl)-4,4- difluorotetrahydrofuran-3-yl benzoate (CAS RN 134790-39-9) with a purity by weight of 98 % or more	0 %	-	31.12.2024
0.7854	2935 90 90	70	(4S)-4-hydroxy-2-(3-methoxypropyl)-3,4- dihydro-2H-thieno[3,2-e]thiazine-6-sulfonamide- 1,1-dioxide (CAS RN 154127-42-1) with a purity	0 %	-	31.12.2024

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			by weight of 97 % or more			
0.7885	3204 15 00	20	Colourant C.I. Vat Blue 1 (CAS RN 482-89-3) and preparations based thereon with a colourant C.I. Vat Blue 1 content of 94 % or more by weight	0 %	-	31.12.2024
0.7922	3823 19 10	20	12-Hydroxyoctadecanoic acid (CAS RN 106-14- 9) for the manufacture of polyglycerin-poly-12- hydroxyoctadecanoic acid esters	0 %	-	31.12.2024
0.7831	3824 99 92	62	Solution of 9-borabicyclo[3.3.1]nonane (CAS RN 280-64-8) in tetrahydrofurane (CAS RN 109-99-9), containing by weight 6 % or more 9-borabicyclo[3.3.1]nonane	0 %	-	31.12.2024
0.7861	3903 90 90	33	Copolymer of styrene, divinylbenzene and chloromethylstyrene (CAS RN 55844-94-5) with a purity by weight of 99 % or more	0 %	-	31.12.2024
0.7865	3909 40 00	70	Polymer in the form of flakes composed of 98 % or more by weight of phenolic resin (brominated octylphenol-formaldehyde) with a softening point of 80°C or more but not exceeding 95°C according to standard ASTM E28-92 (CAS RN 112484-41-0)	0 %	-	31.12.2024
0.7883	3920 69 00	70	<ul> <li>Mono- or multilayer, biaxially oriented film:</li> <li>composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives, and not more than 10 % by weight of additives based on biodegradable polyesters,</li> <li>with a thickness of 9 μm or more but not more than 120 μm,</li> <li>with a length of 1 395 m or more but not more than 21 560 m,</li> <li>biodegradable and compostable (as determined by the method EN 13432)</li> </ul>	0 %	-	31.12.2024
0.7882	3920 69 00	30	<ul> <li>Mono- or multilayer, transverse oriented, shrink film:</li> <li>composed of more than 85 % by weight of polylactic acid, not more than 5 % by weight of inorganic or organic additives and not more than 10 % by weight of additives based on biodegradable polyesters,</li> <li>with a thickness of 20 µm or more but not more than 100 µm,</li> <li>with a length of 2 385 m or more but not more than 9 075 m,</li> <li>biodegradable and compostable (as determined by the method EN 13432)</li> </ul>	0 %	-	31.12.2024
0.7891	7326 90 94	40	Steel ball neck, drop forged, machined, also heat treated or surface treated, having an angle between the center of the conical head and the	0 %	-	31.12.2024

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			arm of less than $90^{\circ}$ or having an angle between the center of the ball and the arm of less than $90^{\circ}$ , for use in the manufacture of trailer hitches for passenger cars (2)			
0.7911	7506 20 00	10	<ul> <li>Sheets and strips in coils of nickel alloy C276 (EN 2.4819) with</li> <li>a thickness of 0,5 mm or more but not more than 3 mm,</li> <li>a width of 770 mm or more but not more than 1 250 mm</li> </ul>	0 %	-	31.12.2024
0.7851	8409 99 00	25	<ul> <li>Hoses assembly for fuel return from injectors to engine fuel unit consisting of at least:</li> <li>three rubber hoses, whether or not with a protective braided sleeving,</li> <li>three connectors for connecting fuel injectors,</li> <li>five metal clamps,</li> <li>one T-shaped plastic joint, for use in the manufacture of engines of motor vehicles</li> <li><sup>(2)</sup></li> </ul>	0 %	-	31.12.2024
0.7850	8481 30 99	30	Brake booster check valve assembly containing at least: — three vulcanized rubber hoses, — one membrane valve, — two metal clamps, — one metal holder, — whether or not connecting metal pipe, for use in the manufacture of motor vehicles <sup>(2)</sup>	0 %	-	31.12.2024
0.7920	8483 40 59	30	<ul> <li>Hydrostatic speed changer:</li> <li>— with a hydro pump and a differential with wheel axle,</li> <li>— whether or not with a fan impeller and/or a pulley,</li> <li>for use in the manufacture of lawn mowers of subheadings 8433 11 and 8433 19 or other mowers of subheading 8433 20</li> </ul>	0 %	p/st	31.12.2024
0.7857	8501 10 10	40	Synchronous hybrid stepper motor with: — an output not exceeding 18 W, — two phases, — a rated current of not more than 2,5 A/phase, — a rated voltage of not more than 20 V, — with or without a threaded shaft, for use in the manufacture of 3D printers <sup>(2)</sup>	0 %	-	31.12.2024
0.7888	8507 60 00	68	<ul> <li>Lithium-ion accumulator in a metal housing with:</li> <li>a length of 173 mm or more but not more than 175 mm,</li> <li>a width of 41,5 mm or more but not more</li> </ul>	1.3 %	-	31.12.2024

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			<ul> <li>than 43 mm,</li> <li>a height of 85 mm or more but not more than 103 mm,</li> <li>a nominal voltage of 3,6 V or more but not more than 3,75 V, and</li> <li>a nominal capacity of 93 Ah or more but not more than 94 Ah</li> </ul>			
0.7873	8537 10 91	20	<ul> <li>Electronic assembly containing: <ul> <li>a microprocessor,</li> <li>a programmable memory controller and other electronic components mounted on a printed circuit,</li> <li>with or without light-emitting diode (LED) or liquid crystal display (LCD) indicators, for use in the manufacture of products of subheadings 8418 21, 8418 29, 8421 12, 8422 11, 8450 11, 8450 12, 8450 19, 8451 21, 8451 29 and 8516 60</li> </ul></li></ul>	0 %	-	31.12.2024
0.7848	8544 30 00	45	Linking seven-core cable for connecting sensor for pressure measure in intake manifold (Boost Pressure Sensor - BPS) and sockets for glow plugs with common connector, containing four sockets and two connectors for use in the manufacture of compression-ignition internal combustion piston engines for passenger car <sup>(2)</sup>	0 %	-	31.12.2024
0.7847	8544 30 00	55	Connecting five-core cable with connectors for coupling the temperature sensor and the exhaust manifold pressure difference sensor to the common connector for use in the manufacture of compression-ignition internal combustion piston engines of passenger cars (2)	0 %	-	31.12.2024
0.7856	8708 40 20 8708 40 50	70 60	Manual gearbox in cast aluminium housing with: — a width of not more than 480 mm, — a height of not more than 400 mm, — a length of not more than 550 mm, — five gears, — a differential gear, — an engine torque of 250 Nm or less, — for transverse installation, for use in the manufacture of motor vehicles of heading 8703 <sup>(2)</sup>	0 %	-	31.12.2024
0.7849	8708 93 10 8708 93 90	40 40	<ul> <li>Clutch pedal with electronic parking brake connection (EPB), whether or not with sending signal function for:</li> <li>cruise control reset,</li> <li>electronic parking brake release,</li> <li>start and stop engine management under Idle Stop and Go system (ISG),</li> <li>for use in the manufacture of passenger vehicles</li> </ul>	0 %	-	31.12.2024

Serial number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			(2)			
0.7921	8708 99 97	18	<ul> <li>Hydrostatic speed changer:</li> <li>with a hydro pump and a differential with wheel axle,</li> <li>whether or not with a fan impeller and/or a pulley,</li> <li>for use in the manufacture of tractors of subheadings 8701 91 90 and 8701 92 90, whose main function is that of a lawn mower</li> </ul>	0 %	p/st	31.12.2023

<sup>(2)</sup> Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)