



Council of the  
European Union

Brussels, 15 December 2020  
(OR. en)

13205/20

---

**Interinstitutional File:**  
2020/0328 (NLE)

---

UD 358

#### LEGISLATIVE ACTS AND OTHER INSTRUMENTS

---

Subject: COUNCIL REGULATION amending Regulation (EU) No 1387/2013  
suspending the autonomous Common Customs Tariff duties on certain  
agricultural and industrial products

---

**COUNCIL REGULATION (EU) 2020/...**

**of ...**

**amending Regulation (EU) No 1387/2013  
suspending the autonomous Common Customs Tariff duties  
on certain agricultural and industrial products**

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient and uninterrupted supply of certain agricultural and industrial products which are not produced in the Union and thereby avoid any disturbances in the market for those products, Common Customs Tariff duties of the type referred to in Article 56(2)(c) of Regulation (EU) No 952/2013 of the European Parliament and of the Council<sup>1</sup> ('CCT duties') on those products have been suspended by Council Regulation (EU) No 1387/2013<sup>2</sup>. Those products can be imported into the Union at reduced or zero duty rates.
- (2) The Union production of certain products that are not listed in the Annex to Regulation (EU) No 1387/2013 is inadequate or non-existent. It is therefore in the interest of the Union to grant a complete suspension of the CCT duties on those products.

---

<sup>1</sup> Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).

<sup>2</sup> Council Regulation (EU) No 1387/2013 of 17 December 2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011 (OJ L 354, 28.12.2013, p. 201).

- (3) With a view to promoting integrated battery production in the Union in accordance with the communication from the Commission of 17 May 2018 entitled 'Europe on the Move – Sustainable Mobility for Europe: safe, connected, and clean', a partial suspension of the CCT duties should be granted in respect of certain products that are not listed in the Annex to Regulation (EU) No 1387/2013. In addition, only a partial suspension of the CCT duties should be granted in respect of certain products that are currently subject to complete suspensions. The date for the mandatory review of those suspensions should be 31 December 2021, in order for that review to take into account the evolution of the battery sector in the Union.
- (4) It is necessary to amend the product description, classification and end-use requirement for certain CCT duty suspensions listed in the Annex to Regulation (EU) No 1387/2013 in order to take into account technical product developments and economic trends in the market.
- (5) A review has been undertaken of certain CCT duty suspensions listed in the Annex to Regulation (EU) No 1387/2013. New dates should therefore be set for their next mandatory review.

- (6) It is no longer in the interest of the Union to maintain the suspension of CCT duties for certain products listed in the Annex to Regulation (EU) No 1387/2013. The suspensions for those products should therefore be deleted. Moreover, according to the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, for practical reasons requests for tariff suspensions or quotas where the amount of uncollected customs duty is estimated to be less than EUR 15 000 per year cannot be taken into consideration. The suspensions for products which do not reach that threshold, as indicated by the mandatory review, should therefore be deleted from the Annex to Regulation (EU) No 1387/2013.
- (7) Regulation (EU) No 1387/2013 should therefore be amended accordingly.
- (8) In order to avoid any interruption in the application of the autonomous tariff suspension scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the tariff suspensions for the products concerned should apply from 1 January 2021. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

*Article 1*

The Annex to Regulation (EU) No 1387/2013 is amended in accordance with the Annex to this Regulation.

*Article 2*

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2021.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at ...,

*For the Council*

*The President*

---

## ANNEX

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

(1) the entries with the following serial numbers are deleted:

0.3338, 0.3662, 0.4675, 0.4795, 0.4856, 0.4891, 0.4902, 0.4903, 0.4905, 0.4908, 0.4911, 0.4920, 0.4926, 0.4935, 0.4939, 0.4943, 0.4973, 0.4995, 0.5012, 0.5022, 0.5039, 0.5043, 0.5052, 0.5053, 0.5067, 0.5092, 0.5103, 0.5123, 0.5125, 0.5126, 0.5311, 0.5498, 0.5953, 0.6036, 0.6068, 0.6087, 0.6450, 0.6527, 0.6591, 0.6592, 0.6595, 0.6596, 0.6597, 0.6606, 0.6607, 0.6608, 0.6610, 0.6615, 0.6616, 0.6619, 0.6626, 0.6636, 0.6639, 0.6651, 0.6653, 0.6665, 0.6676, 0.6694, 0.6697, 0.6704, 0.6705, 0.6715, 0.6724, 0.6727, 0.6731, 0.6733, 0.6735, 0.6743, 0.6744, 0.6755, 0.6756, 0.6758, 0.6760, 0.6768, 0.6775, 0.6776, 0.6778, 0.6780, 0.6785, 0.6786, 0.6787, 0.6788, 0.6795, 0.6798, 0.6803, 0.6807, 0.6811, 0.6832, 0.6833, 0.6834, 0.6838, 0.6841, 0.6883, 0.6890, 0.6895, 0.6900, 0.6902, 0.6909, 0.6914, 0.6916, 0.6918, 0.6928, 0.6941, 0.6942, 0.6943, 0.6944, 0.6953, 0.6954, 0.7040, 0.7222, 0.7293, 0.7558, 0.7560, 0.7697, 0.7715 and 0.7855;

(2) the following entries replace those entries that have the same serial numbers:

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| '0.6748       | ex 0709 59 10 | 10    | Fresh or chilled chanterelles for treatment other than simple repacking for retail sale <sup>(1)(2)</sup> | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.2864        | ex 1511 90 19 | 20    | Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:  | 0 %                     | -                  | 31.12.2021                         |
|               | ex 1511 90 91 | 20    | – industrial monocarboxylic fatty acids of subheading 3823 19 10,  |                         |                    |                                    |
|               | ex 1513 11 10 | 20    | – methyl esters of fatty acids of heading 2915 or 2916,  |                         |                    |                                    |
|               | ex 1513 19 30 | 20    | – fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, |                         |                    |                                    |
|               | ex 1513 21 10 | 20    | – fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products,       |                         |                    |                                    |
|               | ex 1513 29 30 | 20    | – stearic acid of subheading 3823 11 00,   |                         |                    |                                    |
|               |               |       | – goods of heading 3401, or  |                         |                    |                                    |
|               |               |       | – fatty acids with high purity of heading 2915 <sup>(2)</sup>  |                         |                    |                                    |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.6789        | ex 1512 19 10                  | 10       | Refined safflower oil (CAS RN 8001-23-8) for use in the manufacture of<br>- conjugated linoleic acid of heading 3823 or<br>- ethyl- or methyl esters of linoleic acid of heading 2916 <sup>(2)</sup>           | 0 %                     | -                  | 31.12.2022                         |
| 0.5004        | ex 2008 99 48                  | 94       | Mango puree:<br>- not from concentrate,<br>- of the genus <i>Mangifera</i> ,<br>- of a Brix value of 14 or more, but not more than 20,<br>used in the manufacture of products of drink industry <sup>(2)</sup> | 6 %                     | -                  | 31.12.2022                         |
| 0.4709        | ex 2008 99 49<br>ex 2008 99 99 | 30<br>40 | Seedless boysenberry puree not containing added spirit, whether or not containing added sugar  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.6723        | ex 2008 99 91                  | 20       | Chinese water chestnuts ( <i>Eleocharis dulcis</i> or <i>Eleocharis tuberosa</i> ) peeled, washed, blanched, chilled and individually quick-frozen for use in the manufacture of products of food industry for treatment other than simple repacking <sup>(1)(2)</sup> | 0 % <sup>(3)</sup>      | -                  | 31.12.2025                         |
| 0.4992        | ex 2009 41 92<br>ex 2009 41 99 | 20<br>70 | Pineapple juice:<br>- not from concentrate,<br>- of the genus <i>Ananas</i> ,<br>- of a Brix value of 11 or more but not more than 16,<br>used in the manufacture of products of drink industry <sup>(2)</sup>   | 8 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                                | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7393        | ex 2712 90 99                          | 10    | Blend of 1-alkenes containing by weight 90 % or more 1-alkenes of a chain length of 24 carbon atoms or more but not more than 1 % 1-alkenes of a chain length of more than 70 carbon atoms | 0 %                     | -                  | 31.12.2022                         |
| 0.6658        | ex 2805 12 00                          | 10    | Calcium with a purity of 98 % or more by weight, in powder or wire form (CAS RN 7440-70-2)   | 0 %                     | -                  | 31.12.2025                         |
| 0.4979        | 2805 30 20<br>2805 30 30<br>2805 30 40 |       | Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6836        | ex 2811 22 00 | 15    | Amorphous silicon dioxide (CAS RN 60676-86-0)<br>- in the form of powder<br>- of a purity by weight of 99,0 % or more<br>- with a median grain size of 0,7 µm or more, but not more than 2,1 µm<br>- where 70 % of the particles have a diameter of not more than 3 µm | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5110        | ex 2818 10 91 | 20    | <p>Sintered corundum with a micro crystalline structure, consisting of aluminium oxide (CAS RN 1344-28-1), magnesium aluminate (CAS RN 12068-51-8) and the rare earth aluminates of yttrium, lanthanum, and neodymium, with a content by weight (calculated as oxides) of:</p> <ul style="list-style-type: none"> <li>– 94 % or more, but less than 98,5 % of aluminium oxide,</li> <li>– 2 % (<math>\pm 1,5</math> %) of magnesium oxide,</li> <li>– 1 % (<math>\pm 0,6</math> %) of yttrium oxide,</li> </ul> <p>and</p> <ul style="list-style-type: none"> <li>– either 2 % (<math>\pm 1,2</math> %) of lanthanum oxide, or</li> <li>– 2 % (<math>\pm 1,2</math> %) of lanthanum oxide and neodymium oxide,</li> </ul> <p>with less than 50 % of the total weight having a particle size of more than 10 mm</p> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6837        | ex 2818 30 00 | 20    | Aluminium hydroxide (CAS RN 21645-51-2)<br>- in the form of powder,<br>- with a purity by weight of 99,5 % or more,<br>- with a decomposition point of 263°C or more,<br>- with a particle size of 4 µm (± 1 µm),<br>- with a Total-Na <sub>2</sub> O-content by weight of not more than 0,06 % | 0 %                     | -                  | 31.12.2025                         |
| 0.7897        | ex 2825 20 00 | 10    | Lithium hydroxide monohydrate (CAS RN 1310-66-3)  | 2.6 %                   | -                  | 31.12.2021                         |
| 0.6819        | ex 2825 50 00 | 30    | Copper (II) oxide (CAS RN 1317-38-0), with a particle size of not more than 100 nm  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5055        | ex 2826 19 90 | 10    | Tungsten hexafluoride (CAS RN 7783-82-6) with a purity by weight of 99,9 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.5090        | ex 2833 29 80 | 30    | Zirconium sulphate (CAS RN 14644-61-2)   | 0 %                     | -                  | 31.12.2021                         |
| 0.6632        | ex 2840 20 90 | 10    | Zinc borate (CAS RN 12767-90-7)  | 0 %                     | -                  | 31.12.2025                         |
| 0.7288        | ex 2841 50 00 | 11    | Potassium dichromate (CAS RN 7778-50-9) with a purity by weight of 99 % or more      | 2 %                     | -                  | 31.12.2021                         |
| 0.4222        | ex 2841 90 85 | 10    | Lithium cobalt(III) oxide (CAS RN 12190-79-3) with a cobalt content of at least 59 % | 2.7 %                   | -                  | 31.12.2021                         |
| 0.3419        | ex 2850 00 20 | 80    | Arsine (CAS RN 7784-42-1) with a purity by volume of 99,999 % or more                | 0 %                     | -                  | 31.12.2024                         |
| 0.6633        | 2903 39 21    |       | Difluoromethane (CAS RN 75-10-5)   | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.2583        | ex 2903 89 80 | 45    | 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 <sup>6,9</sup> 0 <sup>2,13</sup> 0 <sup>5,10</sup> ]octadeca-7,15-diene (CAS RN 13560-89-9) with a purity by weight of 99 % or more | 2 %                     | -                  | 31.12.2021                         |
| 0.6611        | ex 2903 99 80 | 15    | 4-Bromo-2-chloro-1-fluorobenzene (CAS RN 60811-21-4)  | 0 %                     | -                  | 31.12.2025                         |
| 0.3409        | ex 2904 20 00 | 10    | Nitromethane (CAS RN 75-52-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.3391        | ex 2904 20 00 | 20    | Nitroethane (CAS RN 79-24-3)  | 0 %                     | -                  | 31.12.2022                         |
| 0.3408        | ex 2904 20 00 | 30    | 1-Nitropropane (CAS RN 108-03-2)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6612        | ex 2904 99 00 | 25    | Difluoromethanesulphonyl chloride (CAS RN 1512-30-7)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6613        | ex 2904 99 00 | 35    | 1-Fluoro-4-nitrobenzene (CAS RN 350-46-9)   | 0 %                     | -                  | 31.12.2025                         |
| 0.4934        | ex 2905 39 95 | 10    | Propane-1,3-diol (CAS RN 504-63-2)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6757        | ex 2906 29 00 | 40    | 2-Bromo-5-iodo-benzenemethanol (CAS RN 946525-30-0)   | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6782        | ex 2908 19 00 | 40    | 3,4,5-Trifluorophenol (CAS RN 99627-05-1)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6915        | ex 2908 19 00 | 50    | 4-Fluorophenol (CAS RN 371-41-5)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6649        | ex 2909 30 38 | 30    | 1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7) | 0 %                     | -                  | 31.12.2025                         |
| 0.5117        | ex 2909 30 90 | 30    | 3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6614        | ex 2909 30 90 | 40    | 1-Chloro-2,5-dimethoxybenzene (CAS RN 2100-42-7)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6783        | ex 2909 30 90 | 50    | 1-Ethoxy-2,3-difluorobenzene (CAS RN 121219-07-6)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6784        | ex 2909 30 90 | 60    | 1-Butoxy-2,3-difluorobenzene (CAS RN 136239-66-2)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6927        | ex 2909 49 80 | 10    | 1-Propoxypropan-2-ol (CAS RN 1569-01-3)   | 0 %                     | -                  | 31.12.2021                         |
| 0.6660        | ex 2910 90 00 | 50    | 2,3-Epoxypropyl phenyl ether (CAS RN 122-60-1)  | 0 %                     | -                  | 31.12.2025                         |
| 0.5135        | ex 2912 49 00 | 30    | Salicylaldehyde (CAS RN 90-02-8)  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6678        | ex 2912 49 00 | 40    | 3-Hydroxy-p-anisaldehyde (CAS RN 621-59-0)                              | 0 %                     | -                  | 31.12.2025                         |
| 0.4933        | ex 2914 29 00 | 30    | (R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)                       | 0 %                     | -                  | 31.12.2025                         |
| 0.4932        | ex 2914 50 00 | 20    | 3'-Hydroxyacetophenone (CAS RN 121-71-1)                                | 0 %                     | -                  | 31.12.2025                         |
| 0.6762        | ex 2914 50 00 | 75    | 7-Hydroxy-3,4-dihydro-1(2H)-naphthalenone (CAS RN 22009-38-7)           | 0 %                     | -                  | 31.12.2022                         |
| 0.4948        | ex 2914 79 00 | 60    | 4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1) | 0 %                     | -                  | 31.12.2021                         |
| 0.5119        | ex 2915 39 00 | 60    | Dodec-8-enyl acetate (CAS RN 28079-04-1)                                | 0 %                     | -                  | 31.12.2025                         |
| 0.5121        | ex 2915 39 00 | 65    | Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)                           | 0 %                     | -                  | 31.12.2025                         |
| 0.5120        | ex 2915 39 00 | 70    | Dodec-9-enyl acetate (CAS RN 16974-11-1)                                | 0 %                     | -                  | 31.12.2025                         |
| 0.7541        | ex 2915 90 30 | 10    | Methyl laurate (CAS RN 111-82-0)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4954        | ex 2915 90 70 | 60    | Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)                          | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.3466        | ex 2916 13 00 | 30    | Zinc monomethacrylate powder (CAS RN 63451-47-8) whether or not containing not more than 17 % by weight of manufacturing impurities | 0 %                     | -                  | 31.12.2025                         |
| 0.4931        | ex 2916 20 00 | 60    | 3-Cyclohexylpropionic acid (CAS RN 701-97-3)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4930        | ex 2916 39 90 | 30    | 2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6794        | ex 2916 39 90 | 41    | 4-Bromo-2,6-difluorobenzoyl chloride (CAS RN 497181-19-8)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6661        | ex 2916 39 90 | 53    | 5-Iodo-2-methylbenzoic acid (CAS RN 54811-38-0)   | 0 %                     | -                  | 31.12.2025                         |
| 0.4918        | ex 2917 19 80 | 50    | Tetradecanedioic acid (CAS RN 821-38-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.4945        | ex 2917 39 95 | 20    | Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6796        | ex 2917 39 95 | 25    | Naphthalene-1,8-dicarboxylic anhydride (CAS RN 81-84-5)   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.3640        | ex 2917 39 95 | 30    | Benzene-1,2,4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)                       | 0 %                     | -                  | 31.12.2025                         |
| 0.6800        | ex 2917 39 95 | 35    | 1-Methyl-2-nitrotetraphthalate (CAS RN 35092-89-8)                                 | 0 %                     | -                  | 31.12.2025                         |
| 0.6814        | ex 2918 99 90 | 13    | 3-Methoxy-2-methylbenzoyl chloride (CAS RN 24487-91-0)                             | 0 %                     | -                  | 31.12.2025                         |
| 0.6901        | ex 2918 99 90 | 18    | Ethyl 2-hydroxy-2-(4-phenoxyphenyl)propanoate (CAS RN 132584-17-9)                 | 0 %                     | -                  | 31.12.2025                         |
| 0.6747        | ex 2918 99 90 | 85    | Trinexapac-Ethyl (ISO) (CAS RN 95266-40-3) with a purity by weight of 96 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.5038        | ex 2920 29 00 | 20    | Tris(methylphenyl)phosphite (CAS RN 25586-42-9)                                    | 0 %                     | -                  | 31.12.2025                         |
| 0.5045        | ex 2920 29 00 | 40    | Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)             | 0 %                     | -                  | 31.12.2025                         |
| 0.7559        | ex 2920 90 10 | 15    | Ethyl methyl carbonate (CAS RN 623-53-0)   | 3.2 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6598        | ex 2920 90 70 | 80    | Bis(pinacolato)diboron (CAS RN 73183-34-3)                                  | 0 %                     | -                  | 31.12.2025                         |
| 0.4917        | ex 2921 29 00 | 40    | Decamethylenediamine (CAS RN 646-25-3)                                      | 0 %                     | -                  | 31.12.2025                         |
| 0.4862        | ex 2921 30 99 | 30    | 1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)                             | 0 %                     | -                  | 31.12.2021                         |
| 0.5124        | ex 2921 43 00 | 60    | 3-Aminobenzotrifluoride (CAS RN 98-16-8)                                    | 0 %                     | -                  | 31.12.2025                         |
| 0.6825        | ex 2921 49 00 | 60    | 2,6-Diisopropylaniline (CAS RN 24544-04-5)                                  | 0 %                     | -                  | 31.12.2025                         |
| 0.6947        | ex 2922 19 00 | 35    | 2-[2-(Dimethylamino)ethoxy] ethanol (CAS RN 1704-62-7)                      | 0 %                     | -                  | 31.12.2025                         |
| 0.6624        | ex 2922 29 00 | 30    | 1,2-Bis(2-aminophenoxy)ethane (CAS RN 52411-34-4)                           | 0 %                     | -                  | 31.12.2025                         |
| 0.6634        | ex 2922 29 00 | 63    | Aclonifen (ISO) (CAS RN 74070-46-5) with a purity by weight of 97 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.4956        | ex 2922 29 00 | 75    | 4-(2-Aminoethyl)phenol (CAS RN 51-67-2)                                     | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.4914        | ex 2922 39 00 | 20    | 2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6761        | ex 2922 39 00 | 35    | 5-Chloro-2-(methylamino)benzophenone (CAS RN 1022-13-5)  | 0 %                     | -                  | 31.12.2025                         |
| 0.7853        | ex 2922 49 85 | 13    | Benzyl glycinate—4-methylbenzene-1-sulfonic acid (1/1) (CAS RN 1738-76-7) with a purity by weight of 93 % or more  | 0 %                     | -                  | 31.12.2024                         |
| 0.5037        | ex 2922 49 85 | 17    | Glycine (CAS RN 56-40-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of anti-caking agent silicon dioxide (CAS RN 112926-00-8) | 0 %                     | -                  | 31.12.2025                         |
| 0.6948        | ex 2922 49 85 | 30    | Aqueous solution containing 40 % by weight or more of sodium methylaminoacetate (CAS RN 4316-73-8)   | 0 %                     | -                  | 31.12.2021                         |
| 0.6650        | ex 2922 49 85 | 65    | Diethyl aminomalonate hydrochloride (CAS RN 13433-00-6)  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5063        | ex 2923 90 00 | 75    | Tetraethylammonium hydroxide, in the form of an aqueous solution containing:<br><ul style="list-style-type: none"> <li>– 35 % (<math>\pm</math> 0,5 %) by weight of tetraethylammonium hydroxide,</li> <li>– not more than 1 000 mg/kg of chloride,</li> <li>– not more than 2 mg/kg of iron, and</li> <li>– not more than 10 mg/kg of potassium</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.3689        | ex 2924 19 00 | 23    | Acrylamide (CAS RN 79-06-1) with a purity by weight of 97 % or more   | 2 %                     | -                  | 31.12.2021                         |
| 0.5066        | ex 2924 29 70 | 40    | N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.5127        | ex 2924 29 70 | 45    | Propoxur (ISO) (CAS RN 114-26-1)  | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5069        | ex 2924 29 70 | 55    | N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 24304-50-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6767        | ex 2924 29 70 | 62    | 2-Chlorobenzamide (CAS RN 609-66-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6766        | ex 2924 29 70 | 64    | N-(3',4'-dichloro-5-fluoro[1,1'-biphenyl]-2-yl)acetamide (CAS RN 877179-03-8)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6934        | ex 2926 90 70 | 17    | Cypermethrin (ISO) with its stereoisomers (CAS RN 52315-07-8) with a purity by weight of 90 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.6259        | ex 2926 90 70 | 26    | Cyfluthrin (ISO) (CAS RN 68359-37-5) with a purity by weight of 95,5 % or more for the use in the manufacture of biocidal products <sup>(2)</sup> | 0 %                     | -                  | 31.12.2024                         |
| 0.6871        | ex 2928 00 90 | 23    | Metobromuron (ISO) (CAS RN 3060-89-7) with a purity by weight of 98 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.4929        | ex 2928 00 90 | 25    | Acetaldehyde oxime (CAS RN 107-29-9) in an aqueous solution   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6635        | ex 2928 00 90 | 50    | Aqueous solution of 2,2'-(hydroxyimino) bisethanesulphonic acid disodium salt (CAS RN 133986-51-3) with a content by weight of more than 33,5 % but not more than 36,5 % | 0 %                     | -                  | 31.12.2025                         |
| 0.5035        | ex 2930 90 98 | 10    | 2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)   | 0 %                     | -                  | 31.12.2022                         |
| 0.6769        | ex 2930 90 98 | 22    | Tembotrione (ISO) (CAS RN 335104-84-2) with a purity by weight of 94,5 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.6873        | ex 2930 90 98 | 26    | Folpet (ISO)(CAS RN 133-07-3) with a purity by weight of 97,5 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.6617        | ex 2930 90 98 | 53    | Bis(4-chlorophenyl) sulphone (CAS RN 80-07-9)  | 0 %                     | -                  | 31.12.2025                         |
| 0.5114        | ex 2930 90 98 | 55    | Thiourea (CAS RN 62-56-6)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6917        | ex 2931 90 00 | 63    | Chloroethyldimethylsilane (CAS RN 1719-58-0)   | 0 %                     | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6946        | ex 2931 90 00 | 65    | Bis(4-tert-butylphenyl)iodonium hexafluorophosphate (CAS RN 61358-25-6)  | 0 %                     | -                  | 31.12.2021                         |
| 0.6620        | ex 2932 20 90 | 65    | Sodium 4-(methoxycarbonyl)-5-oxo-2,5-dihydrofuran-3-olate (CAS RN 1134960-41-0)  | 0 %                     | -                  | 31.12.2025                         |
| 0.7639        | ex 2932 99 00 | 27    | (2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4) with a purity by weight of 99 % or more                         | 0 %                     | -                  | 31.12.2023                         |
| 0.4907        | ex 2932 99 00 | 50    | 7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)  | 0 %                     | -                  | 31.12.2021                         |
| 0.6771        | ex 2932 99 00 | 65    | 4,4-Dimethyl-3,5,8-trioxabicyclo[5,1,0]octane (CAS RN 57280-22-5)  | 0 %                     | -                  | 31.12.2025                         |
| 0.7811        | ex 2933 19 90 | 33    | Fipronil (ISO) (CAS RN 120068-37-3) with a purity by weight of 95 % or more for the use in the manufacture of veterinary medicine <sup>(2)</sup> | 0 %                     | -                  | 31.12.2024                         |
| 0.6835        | ex 2933 21 00 | 55    | 1-Aminohydantoin hydrochloride (CAS RN 2827-56-7)  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5115        | ex 2933 21 00 | 80    | 5,5-Dimethylhydantoin (CAS RN 77-71-4)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6812        | ex 2933 39 99 | 14    | N,4-Dimethyl-1-(phenylmethyl)- 3-piperidinamine hydrochloride (1:2) (CAS RN 1228879-37-5)      | 0 %                     | -                  | 31.12.2022                         |
| 0.4842        | ex 2933 39 99 | 20    | Copper pyrrithione powder (CAS RN 14915-37-8)  | 0 %                     | -                  | 31.12.2021                         |
| 0.6813        | ex 2933 39 99 | 26    | 2-[4-(Hydrazinylmethyl)phenyl]-pyridine dihydrochloride (CAS RN 1802485-62-6)                  | 0 %                     | -                  | 31.12.2022                         |
| 0.5129        | ex 2933 39 99 | 85    | 2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6773        | ex 2933 49 10 | 50    | 1-Cyclopropyl-6,7,8-trifluoro-1,4-dihydro-4-oxo-3-quinolinecarboxylic acid (CAS RN 94695-52-0) | 0 %                     | -                  | 31.12.2025                         |
| 0.4927        | ex 2933 49 90 | 30    | Quinoline (CAS RN 91-22-5)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6763        | ex 2933 59 95 | 21    | N-(2-oxo-1,2-dihydropyrimidin-4-yl)benzamide (CAS RN 26661-13-2)                               | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6677        | ex 2933 59 95 | 47    | 6-Methyl-2-oxo-5,6-dihydropyrimidin-4-ylurea (CAS RN 1129-42-6) with a purity of 94 % or more              | 0 %                     | -                  | 31.12.2025                         |
| 0.6774        | ex 2933 69 80 | 13    | Metribuzin (ISO) (CAS RN 21087-64-9) with a purity by weight of 93 % or more                               | 0 %                     | -                  | 31.12.2025                         |
| 0.6621        | ex 2933 69 80 | 15    | 2-Chloro-4,6-dimethoxy-1,3,5-triazine (CAS RN 3140-73-6)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6951        | ex 2933 69 80 | 17    | Benzoguanamine (CAS RN 91-76-9)  | 0 %                     | -                  | 31.12.2021                         |
| 0.5131        | ex 2933 69 80 | 55    | Terbutryn (ISO) (CAS RN 886-50-0)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4957        | ex 2933 69 80 | 60    | Cyanuric acid (CAS RN 108-80-5)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4985        | ex 2933 79 00 | 70    | (S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2) | 0 %                     | -                  | 31.12.2025                         |
| 0.6872        | ex 2933 99 80 | 16    | Pyridate (ISO)(CAS RN 55512-33-9) with a purity by weight of 90 % or more                                  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6829        | ex 2933 99 80 | 21    | 1-(Bis(dimethylamino)methylene)-1H-[1,2,3]triazolo[4,5-b]pyridinium 3-oxide hexafluorophosphate(V) (CAS RN 148893-10-1) | 0 %                     | -                  | 31.12.2025                         |
| 0.6599        | ex 2933 99 80 | 54    | 3-(Salicyloylamino)-1,2,4-triazole (CAS RN 36411-52-6)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6933        | ex 2933 99 80 | 87    | Carfentrazone-ethyl (ISOM) (CAS RN 128639-02-1) with a purity by weight of 90 % or more                                 | 0 %                     | -                  | 31.12.2025                         |
| 0.4955        | ex 2934 20 80 | 60    | Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)                        | 0 %                     | -                  | 31.12.2022                         |
| 0.4910        | ex 2934 20 80 | 70    | N,N-Bis(1,3-benzothiazol-2-ylsulphonyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)                                       | 0 %                     | -                  | 31.12.2025                         |
| 0.4942        | ex 2934 99 90 | 25    | 2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6824        | ex 2934 99 90 | 39    | 4-(Oxiran-2-ylmethoxy)-9H-carbazole (CAS RN 51997-51-4)   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6823        | ex 2934 99 90 | 41    | 11-[4-(2-Chloro-ethyl)-1-piperazinyl]dibenzo(b,f)(1,4)thiazepine (CAS RN 352232-17-8)      | 0 %                     | -                  | 31.12.2025                         |
| 0.6893        | ex 2934 99 90 | 44    | Propiconazole (ISO) (CAS RN 60207-90-1) with a purity by weight of 92 % or more            | 0 %                     | -                  | 31.12.2025                         |
| 0.5133        | ex 2934 99 90 | 86    | Dithianon (ISO) (CAS RN 3347-22-6)   | 0 %                     | -                  | 31.12.2025                         |
| 0.5136        | ex 2934 99 90 | 87    | 2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)                       | 0 %                     | -                  | 31.12.2025                         |
| 0.5036        | ex 2935 90 90 | 42    | Penoxsulam (ISO) (CAS RN 219714-96-2)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6777        | ex 2935 90 90 | 54    | Propoxycarbazone-sodium (ISO) (CAS RN 181274-15-7) with a purity by weight of 95 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.6802        | ex 2935 90 90 | 56    | N-(p-Toluenesulphonyl)-N'-(3-(p-toluenesulphonyloxy)phenyl)urea (CAS RN 232938-43-1)       | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6903        | ex 2935 90 90                  | 57       | N-{2-[(phenylcarbonyl)amino]phenyl}benzenesulphonamide (CAS RN 215917-77-4)   | 0 %                     | -                  | 31.12.2025                         |
| 0.6664        | ex 2935 90 90                  | 59       | Flazasulfuron (ISO) (CAS RN 104040-78-0) with a purity of 94 % by weight or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.4944        | ex 2938 90 30                  | 10       | Ammonium glycyrrhizate (CAS RN 53956-04-0)  | 0 %                     | -                  | 31.12.2025                         |
| 0.6600        | ex 3201 90 90<br>ex 3202 90 00 | 40<br>10 | Reaction product of <i>Acacia mearnsii</i> extract, ammonium chloride and formaldehyde (CAS RN 85029-52-3)  | 0 %                     | -                  | 31.12.2021                         |
| 0.5091        | ex 3204 11 00                  | 20       | Colourant C.I. Disperse Yellow 241 (CAS RN 83249-52-9) and preparations based thereon with a colourant C.I. Disperse Yellow 241 content of 97 % or more by weight | 0 %                     | -                  | 31.12.2021                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5134        | ex 3204 11 00 | 45    | Preparation of dispersion dyes, containing:<br>- C.I. Disperse Orange 61 (CAS RN 12270-45-0) or Disperse Orange 288 (CAS RN 96662-24-7),<br>- C.I. Disperse Blue 291:1 (CAS RN 872142-01-3),<br>- C.I. Disperse Violet 93:1 (CAS RN 122463-28-9),<br>whether or not containing C.I. Disperse Red 54 (CAS RN 6657-37-0) | 0 %                     | -                  | 31.12.2025                         |
| 0.6652        | ex 3204 12 00 | 70    | Colourant C.I. Acid blue 25 (CAS RN 6408-78-2) and preparations based thereon with a colourant C.I. Acid blue 25 content of 80 % or more by weight   | 0 %                     | -                  | 31.12.2025                         |
| 0.6603        | ex 3204 17 00 | 33    | Colourant C.I. Pigment Blue 15:1 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:1 content of 35 % or more by weight  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5100        | ex 3204 19 00 | 73    | Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight   | 0 %                     | -                  | 31.12.2021                         |
| 0.6726        | ex 3208 90 19 | 55    | Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic anhydride in an organic solvent | 0 %                     | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5031        | ex 3215 90 70 | 40    | Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with:<br><ul style="list-style-type: none"> <li>– wax</li> <li>– a vinyl-based polymer and</li> <li>– a colouring agent</li> </ul> for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices <sup>(2)</sup> | 0 %                     | -                  | 31.12.2025                         |
| 0.4863        | ex 3402 11 90 | 10    | Sodium lauroyl methyl isethionate   | 0 %                     | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6725        | ex 3506 91 90 | 50    | Preparation containing by weight:<br><ul style="list-style-type: none"> <li>- 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers, and</li> <li>- 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers,</li> </ul> dissolved in:<br><ul style="list-style-type: none"> <li>- Methyl ethyl ketone (CAS RN 78-93-3),</li> <li>- Heptane (CAS RN 142-82-5), and</li> <li>- Toluene (CAS RN 108-88-3) or light aliphatic solvent naphtha (CAS RN 64742-89-8)</li> </ul> | 0 %                     | -                  | 31.12.2021                         |
| 0.6759        | ex 3802 10 00 | 10    | Mixture of activated carbon and polyethylene, in form of powder   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6874        | ex 3808 92 30 | 10    | Mancozeb (ISO) (CAS RN 8018-01-7) imported in immediate packings of a content of 500 kg or more <sup>(1)</sup>  | 0 %                     | -                  | 31.12.2025                         |
| 0.5048        | ex 3808 93 90 | 20    | Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight:<br>– 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine<br>of a kind used in plant growth regulators                            | 0 %                     | -                  | 31.12.2025                         |
| 0.5030        | ex 3808 93 90 | 30    | Aqueous solution containing by weight:<br>– 1,8 % of sodium para-nitrophenolate,<br>– 1,2 % of sodium ortho-nitrophenolate,<br>– 0,6 % of sodium 5-nitroguaiacolate,<br>for use in the manufacture of a plant growth regulator <sup>(2)</sup> | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5088        | ex 3808 93 90 | 50    | Preparation in the form of powder, containing by weight:<br>– 55 % or more of Gibberellin A4,<br>– 1 % or more but not more than 35 % of Gibberellin A7,<br>– 90 % or more of Gibberellin A4 and Gibberellin A7 combined,<br>– not more than 10 % of a combination of water and other naturally occurring Gibberellins,<br>of a kind used in plant growth regulators | 0 %                     | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6532        | ex 3808 94 20 | 30    | <p>Bromochloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 32718-18-6) containing:</p> <ul style="list-style-type: none"> <li>– 1,3-Dichloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 118-52-5),</li> <li>– 1,3-Dibromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 77-48-5),</li> <li>– 1-Bromo,3-chloro-5,5-dimethylimidazolidine-2,4-dione (CAS RN 16079-88-2), and/or</li> <li>– 1-Chloro,3-bromo-5,5-dimethylimidazolidine-2,4-dione (CAS RN 126-06-7)</li> </ul> | 0 %                     | -                  | 31.12.2024                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6904        | ex 3811 21 00 | 12    | <p>Dispersing agent containing :</p> <ul style="list-style-type: none"> <li>- esters of polyisobutenyyl succinic acid and pentaerythritol (CAS RN 103650-95-9),</li> <li>- 35 % or more but not more than 55 % by weight of mineral oils, and</li> <li>- with a chlorine content of not more than 0,05 % by weight,</li> </ul> <p>used in the manufacture of blends of additives for lubricating oils<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6906        | ex 3811 21 00 | 14    | <p>Dispersing agent :</p> <ul style="list-style-type: none"> <li>- containing polyisobutene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 147880-09-9),</li> <li>- containing 35 % or more but not more than 55 % by weight of mineral oils,</li> <li>- with a chlorine content by weight of not more than 0,05 %,</li> <li>- having a total base number of less than 15,</li> </ul> <p>used in the manufacture of blends of additives for lubricating oils<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6907        | ex 3811 21 00 | 16    | <p>Detergent containing :</p> <ul style="list-style-type: none"> <li>- Calcium salt of beta-aminocarbonyl alkylphenol (reaction product Mannich base of alkylphenol)</li> <li>- 40 % or more but not more than 60 % by weight of mineral oils and</li> <li>- having a total base number more than 120</li> </ul> <p>used in the manufacture of blends of additives for lubricating oils<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6905        | ex 3811 21 00 | 18    | <p>Detergent containing:</p> <ul style="list-style-type: none"> <li>- long chain alkyltoluene calcium sulphonates,</li> <li>- more than 30 % but not more than 50 % by weight of mineral oils, and</li> <li>- having a total base number of more than 310 but not more than 340,</li> </ul> <p>used in the manufacture of blends of additives for lubricating oils<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |
| 0.6671        | ex 3811 21 00 | 75    | <p>Additives containing:</p> <ul style="list-style-type: none"> <li>- Calcium (C10-C14) dialkylbenzenesulfonates,</li> <li>- more than 40 %, but not more than 60 % by weight of mineral oils,</li> </ul> <p>with a total base number of not more than 10, for use in the manufacture of blends of additives for lubricating oils<sup>(2)</sup></p>                                  | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6669        | ex 3811 21 00 | 77    | Antifoam additives consisting of:<br><ul style="list-style-type: none"> <li>- a copolymer of 2-ethylhexyl acrylate and ethyl acrylate, and</li> <li>- more than 50 % but not more than 80 % by weight of mineral oils,</li> </ul> for use in the manufacture of additive blends for lubricating oils <sup>(2)</sup>   | 0 %                     | -                  | 31.12.2022                         |
| 0.6666        | ex 3811 21 00 | 80    | Additives containing :<br><ul style="list-style-type: none"> <li>- polyisobutylene aromatic polyamine succinimide,</li> <li>- more than 40 % but not more than 60 % by weight of mineral oils,</li> </ul> with a nitrogen content of more than 0,6 % but not more than 0,9 % by weight, for use in the manufacture of additive blends for lubricating oils <sup>(2)</sup> | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6668        | ex 3811 29 00 | 65    | Additives consisting of a sulphurised mixture of vegetable oil, long chain $\alpha$ -olefins and tall oil fatty acids, with a sulphur content of 8 % or more but not more than 12 % by weight, for use in the manufacture of blends of additives for lubricating oils <sup>(2)</sup>  | 0 %                     | -                  | 31.12.2022                         |
| 0.5062        | ex 3815 90 90 | 30    | Catalyst, consisting of a suspension in mineral oil of: <ul style="list-style-type: none"> <li>- tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride, and</li> <li>- silicon dioxide,</li> <li>- containing 6,6 % (<math>\pm</math> 0,6 %) by weight of magnesium, and</li> <li>- containing 2,3 % (<math>\pm</math> 0,2 %) by weight of titanium</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.2783        | ex 3815 90 90 | 80    | Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol   | 0 %                     | -                  | 31.12.2025                         |
| 0.6810        | ex 3824 99 92 | 23    | Butylphosphato complexes of titanium(IV) (CAS RN 109037-78-7), dissolved in ethanol and propan-2-ol   | 0 %                     | -                  | 31.12.2025                         |
| 0.4909        | ex 3824 99 92 | 29    | Preparation containing by weight:<br>– 85 % or more but not more than 99 % of polyethylene glycol ether of butyl 2-cyano 3-(4-hydroxy-3-methoxyphenyl) acrylate, and<br>– 1 % or more but not more than 15 % of polyoxyethylene (20) sorbitan trioleate | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6779        | ex 3824 99 92 | 40    | Solution of 2-chloro-5-(chloromethyl)-pyridine (CAS RN 70258-18-3) in organic diluent   | 0 %                     | -                  | 31.12.2025                         |
| 0.7742        | ex 3824 99 92 | 52    | Electrolyte containing: <ul style="list-style-type: none"> <li>- 5 % or more but not more than 20 % lithium hexafluorophosphate (CAS RN 21324-40-3) or lithium tetrafluoroborate (CAS RN 14283-07-9),</li> <li>- 60 % or more but not more than 90 % of a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and/or ethyl methyl carbonate (CAS RN 623-53-0),</li> <li>- 0,5 % or more but not more than 20 % 1,3,2-dioxathiolane 2,2-dioxide (CAS RN 1072-53-3),</li> </ul> for use in the manufacture of motor vehicle batteries <sup>(2)</sup> | 3.2 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5050        | ex 3824 99 92 | 61    | 3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine   | 0 %                     | -                  | 31.12.2025                         |
| 0.6720        | ex 3824 99 92 | 68    | Preparation containing by weight:<br>- 20 % ( $\pm 1$ %) (3-(sec-butyl)-4-(decyloxy)phenyl)methanetriyl Tribenzene (CAS RN 1404190-37-9)<br>Dissolved in:<br>- 10 % ( $\pm 5$ %) 2-sec-Butylphenol (CAS RN 89-72-5)<br>- 64 % ( $\pm 7$ %) Solvent naphtha (petroleum), heavy aromatic (CAS RN 64742-94-5) and<br>- 6 % ( $\pm 1.0$ %) Naphthalene (CAS RN 91-20-3) | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6719        | ex 3824 99 92 | 69    | Preparation containing by weight:<br>– 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5)<br>– 7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and not more than 1 % triphenyl phosphate (CAS RN 115-86-6) | 0 %                     | -                  | 31.12.2021                         |
| 0.3069        | ex 3824 99 92 | 88    | 2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated (CAS RN 9014-85-1)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4719        | ex 3824 99 93 | 35    | Paraffin with a level of chlorination of 70 % or more (CAS RN 63449-39-8)   | 0 %                     | -                  | 31.12.2024                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7313        | ex 3824 99 96 | 45    | Lithium nickel cobalt aluminium oxide powder (CAS RN 177997-13-6) with:<br><ul style="list-style-type: none"> <li>– a particle size of less than 10 µm,</li> <li>– a purity by weight of more than 98 %</li> </ul>   | 3.2 %                   | -                  | 31.12.2021                         |
| 0.6628        | ex 3824 99 96 | 46    | Manganese zinc ferrite granulate, containing by weight:<br><ul style="list-style-type: none"> <li>– 52 % or more but not more than 76 % of iron(III)oxide,</li> <li>– 13 % or more but not more than 42 % of manganese oxide, and</li> <li>– 2 % or more but not more than 22 % of zinc oxide</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6749        | ex 3824 99 96 | 48    | Zirconium oxide (ZrO <sub>2</sub> ), calcium oxide stabilised (CAS RN 68937-53-1) with a zirconium oxide content by weight of 92 % or more but not more than 97 %   | 0 %                     | -                  | 31.12.2025                         |
| 0.6897        | ex 3901 40 00 | 30    | <p>Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with:</p> <ul style="list-style-type: none"> <li>- more than 10 % but not more than 20 % by weight of copolymer,</li> <li>- a melt flow rate (MFR 190 °C/2,16 kg) of 0,7 g/10 min or more but not more than 0,9 g/10 min, and</li> <li>- a density (ASTM D4703) of 0,911 g/cm<sup>3</sup> or more, but not more than 0,913 g/cm<sup>3</sup>,</li> </ul> <p>for use in the co-extrusion processing of films for flexible food packaging<sup>(2)</sup></p> | 0 %                     | m <sup>3</sup>     | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6920        | ex 3901 90 80 | 53    | <p>Copolymer of ethylene and acrylic acid (CAS RN 9010-77-9) with:</p> <ul style="list-style-type: none"> <li>- an acrylic acid content of 18,5 % or more, but not more than 49,5 % by weight (ASTM D4094), and</li> <li>- a melt flow rate of 10g/10 min or more (125 °C/2,16 kg, ASTM D1238)</li> </ul>   | 0 %                     | m <sup>3</sup>     | 31.12.2025                         |
| 0.6734        | ex 3901 90 80 | 55    | <p>Zinc or sodium salt of an ethylene and acrylic acid copolymer, with:</p> <ul style="list-style-type: none"> <li>- an acrylic acid content of 6 % or more but not more than 50 % by weight, and</li> <li>- a melt flow rate of 1g/10 min or more at 190 °C/2,16 kg (measured using ASTM D1238)</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5049        | ex 3901 90 80 | 67    | Copolymer made exclusively from ethylene and methacrylic acid monomers in which the methacrylic acid content is 11 % by weight or more | 0 %                     | -                  | 31.12.2025                         |
| 0.6736        | ex 3903 90 90 | 65    | Copolymer of styrene with 2, 5-furandione and (1-methyl(ethyl)benzene in the form of flakes or powder (CAS RN 26762-29-8)              | 0 %                     | -                  | 31.12.2025                         |
| 0.6804        | ex 3903 90 90 | 70    | Copolymer in the form of granules containing by weight:<br>– 75 % ( $\pm$ 7 %) styrene and<br>– 25 % ( $\pm$ 7 %) methylmethacrylate   | 0 %                     | m <sup>3</sup>     | 31.12.2025                         |
| 0.4981        | ex 3904 69 80 | 81    | Poly(vinylidene fluoride) (CAS RN 24937-79-9)  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6672        | ex 3906 90 90 | 33    | Core shell copolymer of butyl acrylate and alkyl methacrylate, with a particle size of 5 µm or more but not more than 10 µm                       | 0 %                     | -                  | 31.12.2025                         |
| 0.6663        | ex 3906 90 90 | 37    | Copolymer of trimethylolpropane trimethacrylate and methyl methacrylate (CAS RN 28931-67-1), in microsphere form with an average diameter of 3 µm | 0 %                     | -                  | 31.12.2025                         |
| 0.6891        | ex 3907 10 00 | 20    | Polyoxymethylene with acetyl endcaps, containing polydimethylsiloxane and fibers of a copolymer of terephthalic acid and 1,4-phenyldiamine        | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6839        | ex 3907 30 00 | 15    | Epoxide resin, halogen-free,<br><ul style="list-style-type: none"> <li>– containing by weight more than 2 % phosphorus calculated on the solid content, chemically bound in the epoxide resin,</li> <li>– not containing any hydrolysable chloride or containing less than 300 ppm hydrolysable chloride, and</li> <li>– containing solvents,</li> </ul> for use in the manufacture of prepreg sheets or rolls of a kind used for the production of printed circuits <sup>(2)</sup> | 0 %                     | -                  | 31.12.2025                         |
| 0.6840        | ex 3907 30 00 | 25    | Epoxide resin<br><ul style="list-style-type: none"> <li>– containing by weight 21 % or more of bromine,</li> <li>– not containing any hydrolysable chloride or containing less than 500 ppm hydrolysable chloride, and</li> <li>– containing solvents</li> </ul>  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.4940        | ex 3907 99 80<br>ex 3913 90 00 | 30<br>20 | Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)   | 0 %                     | -                  | 31.12.2025                         |
| 0.5057        | ex 3907 99 80                  | 80       | Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic diols                                      | 0 %                     | -                  | 31.12.2025                         |
| 0.5032        | ex 3909 40 00                  | 20       | Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices <sup>(2)</sup> | 0 %                     | -                  | 31.12.2025                         |
| 0.6921        | ex 3910 00 00                  | 15       | Dimethyl, methyl(propyl(polypropylene oxide)) siloxane (CAS RN 68957-00-6), trimethylsiloxo-terminated  | 0 %                     | -                  | 31.12.2021                         |
| 0.7217        | ex 3910 00 00                  | 45       | Dimethyl siloxane, hydroxy-terminated polymer with a viscosity of 38-100 mPa·s (CAS RN 70131-67-8)  | 0 %                     | -                  | 31.12.2021                         |



| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.5109        | ex 3911 90 99                  | 35       | Alternated copolymer of ethylene and maleic anhydride (EMA)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4953        | ex 3912 11 00                  | 40       | Cellulose diacetate powder   | 0 %                     | -                  | 31.12.2025                         |
| 0.6718        | ex 3912 39 85                  | 50       | Polyquaternium 10 (CAS RN 68610-92-4)  | 0 %                     | -                  | 31.12.2025                         |
| 0.4757        | ex 3919 10 80                  | 37       | Polytetrafluoroethylene film:<br>- with a thickness of 100 µm or more,<br>- an elongation at break of not more than 100 %,<br>- coated on one side with a pressure sensitive silicon adhesive  | 0 %                     | -                  | 31.12.2025                         |
| 0.4761        | ex 3919 10 80<br>ex 3919 90 80 | 43<br>26 | Ethylene vinyl acetate film:<br>- of a thickness of 100 µm or more,<br>- coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester or polypropylene liner | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6886        | ex 3919 10 80 | 63    | <p>Reflecting film consisting of</p> <ul style="list-style-type: none"> <li>– a layer of an acrylic resin with imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use,</li> <li>– a layer of an acrylic resin having embedded glass beads,</li> <li>– a layer of an acrylic resin hardened by a melamine cross-linking agent,</li> <li>– a metal layer,</li> <li>– an acrylic adhesive, and</li> <li>– a release film</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.4947        | ex 3919 90 80 | 65    | Self-adhesive film with a thickness of 40 µm or more, but not more than 475 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner | 0 %                     | -                  | 31.12.2025                         |
| 0.4925        | ex 3919 90 80 | 70    | Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.4964        | ex 3919 90 80 | 82    | <p>Reflecting film consisting of:</p> <ul style="list-style-type: none"> <li>– a polyurethane layer,</li> <li>– a glass microspheres layer,</li> <li>– a metallised aluminium layer, and</li> <li>– an adhesive, covered on one or both sides with a release liner,</li> <li>– whether or not a poly(vinyl chloride) layer,</li> <li>– a layer whether or not incorporating security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6640        | ex 3920 10 40 | 40    | <p>Tubular layered film predominately of polyethylene:</p> <ul style="list-style-type: none"> <li>– consisting of a tri-layer barrier with a core layer of ethylene vinyl alcohol covered on either side with a layer of polyamide, covered on either side with at least one layer of polyethylene,</li> <li>– having a total thickness of 55 µm or more,</li> <li>– having a diameter of 500 mm or more but not more than 600 mm</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.3357        | ex 3920 62 19 | 48    | <p>Sheets or rolls of poly(ethylene terephthalate):</p> <ul style="list-style-type: none"> <li>– coated on both sides with a layer of epoxy acrylic resin,</li> <li>– of a total thickness of 37 µm (<math>\pm</math> 3 µm)</li> </ul>   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.2589        | ex 3920 62 19 | 52    | Film of polyethylene terephthalate, polyethylene naphthalate or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 µm and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D257 method) | 0 %                     | -                  | 31.12.2023                         |
| 0.6911        | ex 3921 19 00 | 40    | Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, with: <ul style="list-style-type: none"> <li>– a width of 98 mm or more but not more than 170 mm,</li> <li>– a thickness of 15 µm or more but not more than 36 µm,</li> </ul> of a kind used for the manufacture of alkaline battery separators            | 3.2 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7263        | ex 3921 19 00 | 45    | <p>Microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with:</p> <ul style="list-style-type: none"> <li>– zero transversal production direction (TD) shrinkage,</li> <li>– a total thickness of 8 µm or more, but not more than 50 µm,</li> <li>– a width of 15 mm or more, but not more than 900 mm,</li> <li>– a length of more than 200 m, but not more than 8 000 m,</li> <li>– an average pore size between 0,02 µm and 0,1 µm,</li> <li>– laminated or not with a Polypropylene non-woven mat of 50 to 200 µm thickness,</li> </ul> | 3.2 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6742        | ex 3921 90 55 | 40    | <p>coated or not with surfactant,</p> <p>coated or not on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm,</p> <p>coated or not on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm</p> <p>Three layered fabric sheet, in rolls,</p> <p>comprising a core layer of 100 % Nylon Taffeta or Nylon/Polyester blended Taffeta,</p> <p>coated on both sides with polyamide,</p> <p>of a total thickness not more than 135 µm,</p> <p>of a total weight not more than 80 g/m<sup>2</sup></p> | 0 %                     | m <sup>2</sup>     | 31.12.2025                         |



| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7335        | ex 3926 30 00<br>ex 3926 90 97 | 50<br>48 | Coated interior or exterior decorative parts consisting of:<br>– a copolymer of acrylonitrile-butadiene-styrene (ABS), whether or not mixed with polycarbonate, and<br>– a PVC foil,<br>– not containing layers of copper, nickel or chromium,<br>for use in the manufacturing of parts for motor vehicles of heading 8701 to 8705(2) | 0 %                     | p/st               | 31.12.2022                         |
| 0.6717        | ex 3926 90 97                  | 23       | Plastic cover with clips for the exterior rear-view mirror of motor vehicles  | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.3850        | ex 3926 90 97 | 43    | Mixture of water and by weight 19 % or more but not more than 35 % of expanded hollow microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate or other methacrylate, of a diameter of 3 µm or more but not more than 4,95 µm                                 | 0 %                     | -                  | 31.12.2023                         |
| 0.6708        | ex 4009 42 00 | 20    | Rubber brake hose with: <ul style="list-style-type: none"> <li>- textile strings,</li> <li>- a wall thickness of 3,2 mm,</li> <li>- a metal hollow terminal pressed on both ends, and</li> <li>- one or more mounting brackets,</li> </ul> for use in the manufacture of goods of Chapter 87(2) | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6844        | ex 4016 93 00 | 30    | Rectangular ethylene-propylene-diene rubber gasket, with: <ul style="list-style-type: none"> <li>– a length of 72 mm or more but not more than 825 mm,</li> <li>– a width of 18 mm or more but not more than 155 mm,</li> <li>– a peak temperature of 150°C or more but not more than 240 °C,</li> <li>– a permissible material outflow at the place of the mold split of not more than 0,3 mm</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.6884        | ex 5403 39 00 | 10    | Biodegradable (norm EN 14995) monofilament of not more than 33 dtex, containing at least 98 % by weight polylactide (PLA), for use in the manufacture of filtration fabrics for the food industry <sup>(2)</sup>  | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5059        | ex 5603 13 10 | 20    | <p>Non-woven of spunbonded polyethylene, with a coating,</p> <ul style="list-style-type: none"> <li>– of a weight of more than 80 g/m<sup>2</sup> but not more than 105 g/m<sup>2</sup> and</li> <li>– an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)</li> </ul>                            | 0 %                     | m <sup>2</sup>     | 31.12.2025                         |
| 0.5987        | ex 5603 14 90 | 60    | <p>Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media:</p> <ul style="list-style-type: none"> <li>– of weight of 160 g/m<sup>2</sup> or more but not more than 300 g/m<sup>2</sup>,</li> <li>– not laminated,</li> <li>– with filtration efficiency according to DIN 60335-2-69:2008 minimum Filter class M,</li> <li>– pleatable</li> </ul> | 0 %                     | m <sup>2</sup>     | 31.12.2023                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.4978        | ex 6909 19 00 | 20    | Silicon nitride (Si <sub>3</sub> N <sub>4</sub> ) rollers or balls  | 0 %                     | -                  | 31.12.2025                         |
| 0.7619        | ex 7006 00 90 | 40    | Plates of sodalime or borosilicate glass of STN (Super Twisted Nematic) or TN (Twisted Nematic) quality having: <ul style="list-style-type: none"> <li>- a length of 300 mm or more but not more than 1 500 mm,</li> <li>- a width of 300 mm or more but not more than 1 500 mm,</li> <li>- a thickness of 0,5 mm or more but not more than 1,1 mm,</li> <li>- an indium-tin-oxide coating with a resistance of 80 Ω or more, but not more than 160 Ω on one side,</li> <li>- with or without a passivation layer of silicon dioxide (SiO<sub>2</sub>) between indium-tin-oxide layer and glass surface,</li> <li>- with or without a multi layer anti-reflection-coating on the other side, and</li> <li>- machined (chamfered) edges</li> </ul> | 0 %                     | -                  | 31.12.2023                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6870        | ex 7009 10 00 | 40    | Electrochromic self-dimming inside rear-view mirror, consisting of: <ul style="list-style-type: none"> <li>- a mirror support</li> <li>- a plastic casing and</li> <li>- an integrated circuit</li> </ul> for use in the manufacture of motor vehicles of Chapter 87(2) | 0 %                     | -                  | 31.12.2025                         |
| 0.5021        | ex 7019 19 10 | 20    | Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate   | 0 %                     | -                  | 31.12.2025                         |
| 0.5020        | ex 7019 19 10 | 25    | Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.4853        | ex 7202 99 80 | 10    | Ferro-dysprosium, containing by weight:<br><ul style="list-style-type: none"> <li>- 78 % or more of dysprosium, and</li> <li>- 18 % or more but not more than 22 % of iron</li> </ul>  | 0 %                     | -                  | 31.12.2025                         |
| 0.7502        | ex 7318 24 00 | 40    | Tube or pipe restraint joint elements:<br><ul style="list-style-type: none"> <li>- of stainless steel according to specification 17-4PH or of steel according to specification tool steel S7,</li> <li>- produced by metal injection moulding,</li> <li>- with a rockwell hardness of 38 HRC (<math>\pm 1</math>) or 53 HRC (+2/ - 1),</li> <li>- measuring 7 mm x 4 mm x 5 mm or more, but not more than 40 mm x 20 mm x 10 mm</li> </ul> | 0 %                     | -                  | 31.12.2023                         |

| Serial Number | CN code   | TARIC          | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---|----------------|--|-------------------------|--------------------|------------------------------------|
| 0.6680        | ex 7326 90 98                                   | 40             | Iron and steel weights<br>– whether or not with parts of other material<br>– whether or not with parts of other metals<br>– whether or not surface treated<br>– whether or not printed<br>of a kind used for the production of remote controls | 0 %                     | -                  | 31.12.2025                         |
| 0.5029        | ex 7604 29 10<br>ex 7606 12 99<br>ex 7606 12 99 | 10<br>21<br>25 | Sheets and bars of aluminium-lithium alloys  | 0 %                     | -                  | 31.12.2022                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5487        | ex 7607 11 90 | 48    | Aluminium foil in rolls:                                       | 0 %                     | -                  | 31.12.2021                         |
|               | ex 7607 11 90 | 49    | - having a purity of 99,99 % by weight,                        |                         |                    |                                    |
|               | ex 7607 11 90 | 51    | - of a thickness of 0,021 mm or more but not more than 0,2 mm, |                         |                    |                                    |
|               | ex 7607 11 90 | 52    | - with a width of 500 mm,                                      |                         |                    |                                    |
|               | ex 7607 11 90 | 53    | - with a surface oxide layer by 3 to 4 nm thick,               |                         |                    |                                    |
|               | ex 7607 11 90 | 56    | - and with a cubic texture of more than 95 %                   |                         |                    |                                    |
| 0.4050        | ex 7607 11 90 | 60    | Plain aluminium foil with the following parameters:            | 3.7 %                   | -                  | 31.12.2021                         |
|               |               |       | - an aluminium content of 99,98 % or more,                     |                         |                    |                                    |
|               |               |       | - a thickness of 0,070 mm or more but not more than 0,125 mm,  |                         |                    |                                    |
|               |               |       | - with a cubic texture,  |                         |                    |                                    |
|               |               |       | of a kind used for high voltage etching                        |                         |                    |                                    |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7698        | ex 7607 20 90 | 10    | Aluminium foil, in rolls:<br><ul style="list-style-type: none"> <li>– coated on one side with polypropylene or polypropylene and acid-modified polypropylene and on the other with polyamide and polyethylene terephthalate, with adhesive layers between them,</li> <li>– with a width of 200 mm or more, but not more than 400 mm,</li> <li>– with a thickness of 0,138 mm or more, but not more than 0,168 mm,</li> </ul> for use in the manufacture of lithium-ion battery cell covers <sup>(2)</sup> | 3.7 %                   | -                  | 31.12.2021                         |
| 0.6730        | ex 8101 96 00 | 10    | Tungsten wire containing by weight 99 % or more of tungsten with:<br><ul style="list-style-type: none"> <li>– a maximum cross-sectional dimension of not more than 50 µm</li> <li>– a resistance of 40 Ω or more but not more than 300 Ω at length of 1 metre</li> </ul>  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5097        | ex 8104 30 00 | 35    | Magnesium powder<br>– of purity by weight of more than 99,5 %<br>– with a particle size of 0,2 mm or more but not more than 0,8 mm  | 0 %                     | -                  | 31.12.2025                         |
| 0.4904        | ex 8108 90 30 | 45    | Titanium-aluminium-vanadium alloy (TiAl6V4) wire, of a diameter less than 20 mm and complying with AMS standards 4928, 4965 or 4967 | 0 %                     | -                  | 31.12.2025                         |
| 0.6805        | ex 8113 00 90 | 20    | Cuboid spacer made of aluminium silicon carbide (AlSiC) composite used for packaging in IGBT-modules                                | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5024        | ex 8301 60 00 | 30    | Silicone or plastic keyboards, comprising:           | 0 %                     | p/st               | 31.12.2025                         |
|               | ex 8419 90 85 | 40    | – parts of common metal, and                         |                         |                    |                                    |
|               | ex 8479 90 70 | 30    | – whether or not comprising parts of plastic,        |                         |                    |                                    |
|               | ex 8481 90 00 | 50    | – epoxy resin reinforced with fiberglass or wood,    |                         |                    |                                    |
|               | ex 8503 00 99 | 43    | – whether or not printed or surface-treated,         |                         |                    |                                    |
|               | ex 8515 90 80 | 40    | – with or without electrical conductors,             |                         |                    |                                    |
|               | ex 8537 10 98 | 55    | – with or without a membrane bonded to the keyboard, |                         |                    |                                    |
|               | ex 8538 90 99 | 70    | – with or without mono or multilayer protective film |                         |                    |                                    |
|               | ex 8708 99 10 | 55    |  |                         |                    |                                    |
|               | ex 8708 99 97 | 22    |  |                         |                    |                                    |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.4996        | ex 8407 90 90 | 20    | <p>Compact Liquid Petroleum Gas (LPG) Engine System, with:</p> <ul style="list-style-type: none"> <li>- 6 cylinders,</li> <li>- an output of 75 kW or more, but not more than 80 kW,</li> <li>- inlet and exhaust valves modified to operate continuously in heavy duty applications,</li> </ul> <p>for use in the manufacture of vehicles of heading 8427<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.6160        | ex 8414 30 81<br>ex 8414 80 73 | 60<br>30 | <p>Hermetic rotary compressors for either hydrofluorocarbon (HFC) or hydrocarbon refrigerants:</p> <ul style="list-style-type: none"> <li>– driven by "on-off" single phase alternate current (AC) or "brushless direct current" (BLDC) variable speed motors,</li> <li>– with a nominal power rating of not more than 1,5 kW,</li> <li>– a rated voltage of 100 V or more but not more than 240 V,</li> <li>– with a height of not more than 300 mm,</li> <li>– an external diameter of not more than 150 mm,</li> <li>– with a unit weight of not more than 15 kg,</li> </ul> <p>for use in the manufacture of heat pumps for household appliances, including clothes dryers<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2023                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7317        | ex 8414 80 22 | 20    | Air membrane compressor with:<br><ul style="list-style-type: none"> <li>– a flow of 4,5 l/min or more, but not more than 7 l/min,</li> <li>– power input of not more than 8,1 W, and</li> <li>– a gauge pressure capacity not exceeding 400 hPa (0,4 bar),</li> </ul> of a kind used in the production of motor vehicle seats                     | 0 %                     | -                  | 31.12.2022                         |
| 0.6842        | ex 8415 90 00 | 60    | Flame-soldered aluminium block, for connecting tube with condenser in car air-conditioning systems, with:<br><ul style="list-style-type: none"> <li>– extruded, bent connector lines of aluminium with an external diameter of 5 mm or more, but not more than 25 mm,</li> <li>– a weight of 0,02 kg or more but not more than 0,25 kg</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6860        | ex 8415 90 00 | 65    | <p>Aluminium arc-welded removable receiver dryer, with polyamide and ceramic elements with:</p> <ul style="list-style-type: none"> <li>– a length of 143 mm or more but not more than 292 mm,</li> <li>– a diameter of 31 mm or more but not more than 99 mm, with a weight of not less than 0,12 kg and not more than 0,9 kg,</li> <li>– a spangle length of not more than 0,2 mm and a thickness of not more than 0,06 mm, and</li> <li>– a solid particle diameter of not more than 0,06 mm,</li> </ul> <p>for use in the manufacture of car air-conditioning systems<sup>(2)</sup></p> | 0 %                     | p/st               | 31.12.2022                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6821        | ex 8436 99 00 | 10    | Part containing: <ul style="list-style-type: none"> <li>– a single-phase AC motor,</li> <li>– an epicyclic gearing,</li> <li>– a cutter blade,</li> </ul> and whether or not containing: <ul style="list-style-type: none"> <li>– a capacitor,</li> <li>– a part fitted with a threaded bolt,</li> </ul> for use in the manufacture of garden shredders <sup>(2)</sup> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7380        | ex 8481 80 59 | 30    | Two-way flow control valve with housing, with: <ul style="list-style-type: none"> <li>- at least 5, but not more than 16 outlet holes with at least 0,05 mm, but not more than 0,5 mm diameter,</li> <li>- at least 330 cm<sup>3</sup>/minute, but not more than 5 000 cm<sup>3</sup>/minute flow rate,</li> <li>- at least 19, but not more than 300 MPa operating pressure</li> </ul> | 0 %                     | -                  | 31.12.2022                         |
| 0.7518        | ex 8481 90 00 | 40    | Valve armature: <ul style="list-style-type: none"> <li>- for the opening and closing of the flow of fuel,</li> <li>- consisting of a shaft and a blade,</li> <li>- with at least 3 but not more than 8 holes on the blade,</li> <li>- made of metal and/or metal alloy(s)</li> </ul>  | 0 %                     | -                  | 31.12.2023                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.4997        | ex 8483 40 90 | 80    | <p>Transmission gearbox, with:</p> <ul style="list-style-type: none"> <li>– not more than 3 gears,</li> <li>– an automatic deceleration system, and</li> <li>– a power reversal system,</li> </ul> <p>for use in the manufacture of goods of heading 8427(2)</p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6854        | ex 8501 10 10 | 20    | <p>Synchronous motor for a dishwasher with a water flow control mechanism with</p> <ul style="list-style-type: none"> <li>– a length without axle of 24 mm (<math>\pm 0,3</math>),</li> <li>– a diameter of 49,3 mm (<math>\pm 0,3</math>),</li> <li>– a rated voltage of 220 V AC or more but not more than 240 V AC,</li> <li>– a rated frequency of 50 Hz or more but not more than 60 Hz,</li> <li>– an input power of not more than 4 W,</li> <li>– a rotation speed of 4rpm or more but not more than 4,8rpm,</li> <li>– an output torque of not less than 10kgf/cm</li> </ul> | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6858        | ex 8501 10 99 | 64    | <p>DC motor to control angular position of the flap to adjust gas flow in the Air Throttle and EGR valve:</p> <ul style="list-style-type: none"> <li>– with Ingress Protection (IP) standard of IP69,</li> <li>– with a rotor speed of not more than 6 500 rpm when not loaded,</li> <li>– with a rated voltage of 12,0 V (<math>\pm 0,1</math>),</li> <li>– of a specified temperature range of <math>- 40</math> °C or more, but not more than <math>+ 165</math> °C,</li> <li>– with or without a connecting pinion,</li> <li>– with or without an engine connector,</li> <li>– with or without a flange,</li> <li>– with a diameter of not more than 40 mm (not including the flange),</li> <li>– with an overall height of not more than 90 mm (from the base to the pinion)</li> </ul> | 0 %                     | -                  | 30.06.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6880        | ex 8501 10 99 | 65    | <p>Electric turbocharger actuator, with:</p> <ul style="list-style-type: none"> <li>– a DC motor,</li> <li>– an integrated gear mechanism,</li> <li>– a (pulling) force of 200 N or more at a minimum of 140 °C elevated ambient temperature,</li> <li>– a (pulling) force of 250 N or more in each position of its stroke,</li> <li>– an effective stroke of 15 mm or more but not more than 25 mm,</li> <li>– with or without an on-board diagnostics interface</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6627        | ex 8501 10 99 | 75    | Permanently excited DC motor with <ul style="list-style-type: none"> <li>– a multiple-phase winding,</li> <li>– an external diameter of 28 mm or more but not more than 35 mm,</li> <li>– a rated speed of not more than 12 000 rpm,</li> <li>– a power supply voltage of 8 V or more but not more than 27 V</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.4731        | ex 8501 31 00 | 37    | Permanently excited DC motor with <ul style="list-style-type: none"> <li>– a multiple-phase winding,</li> <li>– an external diameter of 30 mm or more but not more than 90 mm, including mounting flange,</li> <li>– a rated speed of not more than 15 000 rpm,</li> <li>– an output of 45 W or more but not more than 400 W, and</li> <li>– a supply voltage of 9 V or more but not more than 50 V, whether or not with a drive disc,</li> <li>– whether or not with a crankcase,</li> <li>– whether or not with a fan,</li> </ul> | 0 %                     | -                  | 31.12.2024                         |



| Serial Number | CN code | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------|-------|---|-------------------------|--------------------|------------------------------------|
|               |         |       | <ul style="list-style-type: none"> <li>– whether or not with a cap assembly,</li> <li>– whether or not with a sun gear,</li> <li>– whether or not with a speed and rotational direction encoder,</li> <li>– whether or not with or without a speed or rotational direction sensor of resolver type or Hall effect type,</li> <li>– whether or not with a mounting flange</li> </ul> |                         |                    |                                    |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.5577        | ex 8501 31 00 | 50    | <p>DC motors, brushless, with:</p> <ul style="list-style-type: none"> <li>– an external diameter of 80 mm or more, but not more than 200 mm,</li> <li>– a supply voltage of 9 V or more, but not more than 16 V, an output at 20 °C of 300 W or more, but not more than 750 W,</li> <li>– a torque at 20 °C of 2,00 Nm or more, but not more than 7,00 Nm,</li> <li>– a rated speed at 20 °C of 600 rpm or more, but not more than 3 100 rpm,</li> <li>– with or without a pulley,</li> <li>– with or without an electronic power steering sensor/controller</li> </ul> | 0 %                     | -                  | 31.12.2022                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6809        | ex 8501 31 00<br>ex 8501 32 00 | 53<br>45 | Automotive-ready, brushless and permanently excited direct current motor with: <ul style="list-style-type: none"> <li>– a specified speed of not more than 4 100 rpm,</li> <li>– a minimum output of 400 W, but not more than 1,3 kW (at 12 V),</li> <li>– a flange diameter of 85 mm or more, but not more than 200 mm,</li> <li>– a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending,</li> <li>– a housing length of not more than 265 mm, measured from the flange to the outer ending,</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------|-------|---|-------------------------|--------------------|------------------------------------|
|               |         |       | <ul style="list-style-type: none"> <li data-bbox="339 714 528 1637">– a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease),</li> <li data-bbox="539 714 612 1637">– a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and</li> <li data-bbox="624 714 667 1637">– surface magnets,</li> <li data-bbox="678 714 722 1637">– whether or not with electronic power steering controller</li> </ul> |                         |                    |                                    |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6161        | ex 8503 00 99 | 55    | <p>Stator for brushless motor, with:</p> <ul style="list-style-type: none"> <li>– an internal diameter of 206,6 mm (<math>\pm 0,5</math>),</li> <li>– an external diameter of 265,0 mm (<math>\pm 0,2</math>), and</li> <li>– a width of 37,2 mm or more but not more than 47,8 mm,</li> </ul> <p>of a kind used in the manufacture of washing machine, washer-dryer or dryer equipped with direct drive drums</p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7764        | ex 8504 31 80 | 55    | <p>Electrical transformer with:</p> <ul style="list-style-type: none"> <li>– a capacity of 0,22 kVA or more, but not more than 0,24 kVA,</li> <li>– an operating temperature range of + 10°C or more, but not more than + 125°C,</li> <li>– four or five inductively coupled copper wire windings, 11 or 12 connection pins at the bottom, and</li> <li>– dimensions of not more than 32 mm x 37,8 mm x 25,8 mm</li> </ul> | 0 %                     | -                  | 31.12.2024                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7788        | ex 8505 11 00 | 68    | <p>Blocks made of neodymium, iron and boron or an alloy of samarium and cobalt, whether or not covered with zinc, intended to become permanent magnets after magnetisation with:</p> <ul style="list-style-type: none"> <li>– a length of 13,8 mm or more but not more than 45,2 mm,</li> <li>– a width of 7,8 mm or more but not more than 25,2 mm,</li> <li>– a height of 1,3 mm or more but not more than 4,7 mm</li> </ul> | 0 %                     | -                  | 31.12.2024                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6857        | ex 8505 11 00<br>ex 8505 19 90 | 73<br>35 | Articles in shape of flat bars, arched bars or quarter sleeves, made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, whether or not overmolded with polymers, intended to become permanent magnets after magnetisation with: <ul style="list-style-type: none"> <li>– a length of 5 mm or more, but not more than 60 mm,</li> <li>– a width of 5 mm or more, but not more than 40 mm,</li> <li>– a thickness of 3 mm or more, but not more than 15 mm</li> </ul> | 0 %                     | p/st               | 31.12.2022                         |



| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7641        | ex 8507 60 00 | 13    | <p>Prismatic lithium-ion electric accumulators with:</p> <ul style="list-style-type: none"> <li>– a width of 173,0 mm (<math>\pm 0,3</math> mm),</li> <li>– a thickness of 45,0 mm (<math>\pm 0,3</math> mm),</li> <li>– a height 125,0 mm (<math>\pm 0,3</math> mm),</li> <li>– a nominal voltage of 3,67 V (<math>\pm 0,01</math> V), and</li> <li>– a nominal capacity of 94 Ah and/or 120 Ah,</li> </ul> <p>for use in the manufacture of rechargeable electric vehicle batteries<sup>(2)</sup></p> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6685        | ex 8507 60 00 | 15    | <p>Cylindrical lithium-ion-accumulators or modules with:</p> <ul style="list-style-type: none"> <li>- a nominal capacity of 8,8 Ah or more, but not more than 18 Ah,</li> <li>- a nominal voltage of 36 V or more, but not more than 48 V,</li> <li>- a power of 300 Wh or more, but not more than 648 Wh,</li> </ul> <p>for use in the manufacture of electric bicycles<sup>(2)</sup></p> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6625        | ex 8507 60 00 | 17    | <p>Lithium-ion starter accumulator, consisting of four rechargeable lithium-ion secondary cells, with:</p> <ul style="list-style-type: none"> <li>– a rated voltage of 12 V,</li> <li>– a length of 350 mm or more but not more than 355 mm,</li> <li>– a width of 170 mm or more but not more than 180 mm,</li> <li>– a height of 180 mm or more but not more than 195 mm,</li> <li>– weighing 10 kg or more but not more than 15 kg,</li> <li>– a nominal charge of 60 Ah or more, but not more than 80 Ah</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7663        | ex 8507 60 00 | 18    | <p>Lithium-ion polymer accumulator equipped with a battery management system and can-bus interface with:</p> <ul style="list-style-type: none"> <li>– a length of not more than 1600 mm,</li> <li>– a width of not more than 448 mm,</li> <li>– a height of not more than 395 mm,</li> <li>– a nominal voltage of 280 V or more but not more than 400 V,</li> <li>– a nominal capacity of 9,7 Ah or more but not more than 10,35 Ah,</li> <li>– a charging voltage of 110 V or more but not more than 230 V, and</li> <li>– containing 6 modules with 90 cells or more but not more than 96 cells enclosed in a steel casing,</li> </ul> <p>for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703(2)</p> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7717        | ex 8507 60 00 | 22    | <p>Integrated battery system in a metal case with holders, consisting of:</p> <ul style="list-style-type: none"> <li>- a lithium-ion battery with voltage of 48 V (<math>\pm 5</math> V) and capacity of 0,44 kWh (<math>\pm 0,05</math> kWh),</li> <li>- Battery Management System,</li> <li>- a relay,</li> <li>- a low voltage converter (DC/DC),</li> <li>- at least one connector,</li> </ul> <p>for use in the manufacture of hybrid motor vehicles<sup>(2)</sup></p> | 1.3 %                   | -                  | 31.12.2021                         |
| 0.2907        | ex 8507 60 00 | 30    | <p>Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries<sup>(2)</sup></p>  | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6703        | ex 8507 60 00 | 33    | <p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> <li>– a length of 150 mm or more, but not more than 1,000 mm,</li> <li>– a width of 100 mm or more, but not more than 1,000 mm,</li> <li>– a height of 200 mm or more, but not more than 1,500 mm,</li> <li>– a weight of 75 kg or more, but not more than 200 kg,</li> <li>– a nominal capacity not less than 150Ah and not more than 500 Ah,</li> <li>– a nominal output voltage of 230V AC (Line to neutral) or a nominal voltage of 64V (<math>\pm 10\%</math>)</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6702        | ex 8507 60 00 | 37    | <p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> <li>– a length of 1 200 mm or more, but not more than 2 000 mm,</li> <li>– a width of 800 mm or more, but not more than 1 300 mm,</li> <li>– a height of 2 000 mm or more, but not more than 2 800 mm,</li> <li>– a weight of 1 800 kg or more, but not more than 3 000 kg,</li> <li>– a nominal capacity of 2 800 Ah or more but not more than 7 200 Ah</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5548        | ex 8507 60 00 | 50    | <p>Modules for the assembly of batteries of ion lithium electric accumulators with:</p> <ul style="list-style-type: none"> <li>– a length of 298 mm or more, but not more than 500 mm,</li> <li>– a width of 33,5 mm or more, but not more than 209 mm,</li> <li>– a height of 75 mm or more, but not more than 228 mm,</li> <li>– a weight of 3,6 kg or more, but not more than 17 kg, and</li> <li>– a nominal energy of 458 Wh or more, but not more than 2 158 Wh</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5342        | ex 8507 60 00 | 65    | <p>Cylindrical lithium ion cell with</p> <ul style="list-style-type: none"> <li>- 3,5 VDC to 3,8 VDC,</li> <li>- 300 mAh to 900 mAh, and</li> <li>- a diameter of 10,0 mm to 14,5 mm</li> </ul>  | 1.3 %                   | -                  | 31.12.2021                         |
| 0.7888        | ex 8507 60 00 | 68    | <p>Lithium-ion accumulator in a metal housing, with</p> <ul style="list-style-type: none"> <li>- a length of 65 mm or more, but not more than 225 mm,</li> <li>- a width of 10 mm or more, but not more than 75 mm,</li> <li>- a height of 60 mm or more, but not more than 285 mm,</li> <li>- a nominal voltage of 2,1 V or more, but not more than 3,8 V, and</li> <li>- a nominal capacity of 2,5 Ah or more, but not more than 325 Ah</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5356        | ex 8507 60 00 | 75    | <p>Rectangular lithium-ion-accumulator, with</p> <ul style="list-style-type: none"> <li>- a metal casing,</li> <li>- a length of 173 mm (<math>\pm 0,15</math> mm),</li> <li>- a width of 21 mm (<math>\pm 0,1</math> mm),</li> <li>- a height of 91 mm (<math>\pm 0,15</math> mm),</li> <li>- a nominal voltage of 3,3 V, and</li> <li>- a nominal capacity of 21 Ah or more</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6753        | ex 8507 60 00 | 77    | <p>Lithium-ion rechargeable batteries, with:</p> <ul style="list-style-type: none"> <li>– a length of 700 mm or more, but not more than 2 820 mm,</li> <li>– a width of 935 mm or more, but not more than 1 660 mm,</li> <li>– a height of 85 mm or more, but not more than 700 mm,</li> <li>– a weight of 250 kg or more, but not more than 700 kg,</li> <li>– a power of not more than 175 kWh,</li> <li>– a nominal voltage of 400 V</li> </ul> | 1.3 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.5014        | ex 8508 70 00<br>ex 8537 10 98 | 20<br>98 | <p>Electronic circuit cards that:</p> <ul style="list-style-type: none"> <li>– are connected by wire or radio frequency to each other and the motor controller card, and</li> <li>– regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program, whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full)</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6856        | ex 8512 20 00 | 30    | Lighting module, containing at least: <ul style="list-style-type: none"> <li>– two LEDs,</li> <li>– glass or plastic lenses, focusing/scattering the light emitted by the LEDs,</li> <li>– reflectors redirecting the light emitted by the LEDs, in an aluminium housing with a radiator, mounted at a bracket with an actuator</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |
| 0.6863        | ex 8512 30 90 | 20    | Warning buzzer for parking sensor system in a plastic casing operating on the piezo-mechanic principle, containing: <ul style="list-style-type: none"> <li>– a printed circuit board,</li> <li>– a connector,</li> <li>– whether or not a metal holder,</li> </ul> for use in the manufacture of goods of chapter 87 <sup>(2)</sup>        | 0 %                     | p/st               | 31.12.2022                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6689        | ex 8529 90 65 | 28    | <p>Electronic assembly comprising at least:</p> <ul style="list-style-type: none"> <li>– a printed circuit board with,</li> <li>– one or more FPGAs (Field Programmable Gate Array) and/or processors for multi-media applications and video signal processing,</li> <li>– flash memory,</li> <li>– operating memory,</li> <li>– with or without one or more USB, HDMI, VGA-, RJ-45 and/or other multimedia interfaces,</li> <li>– sockets and plugs for connecting a LCD-display, a LED lighting and a control panel</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.4893        | ex 8529 90 65<br>ex 8529 90 92 | 65<br>53 | Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module  | 0 %                     | p/st               | 31.12.2025                         |
| 0.4890        | ex 8529 90 92                  | 25       | LCD modules, not combined with touch screen facilities, solely consisting of: <ul style="list-style-type: none"> <li>– one or more TFT glass or plastic cells,</li> <li>– a die cast heat sink,</li> <li>– a backlight unit,</li> <li>– one printed circuit board with micro controller, and</li> <li>– LVDS (Low Voltage Differential Signalling) interface,</li> </ul> for use in the manufacture of radios for motor vehicles <sup>(2)</sup> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6654        | ex 8529 90 92 | 37    | Fastening and covering ledges of aluminium alloy containing:<br>– silicon and magnesium,<br>– with a length of 300 mm or more but not more than 2 200 mm,<br>specifically shaped for use in the manufacture of TV sets <sup>(2)</sup> | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6629        | ex 8529 90 92 | 63    | <p>LCD module</p> <ul style="list-style-type: none"> <li>– with a diagonal measurement of the screen of 14,5 cm or more but not more than 38,5 cm,</li> <li>– with or without a touch screen,</li> <li>– with an LED backlight,</li> <li>– with a printed circuit board with EEPROM, microcontroller, LVDS receiver and other active and passive components,</li> <li>– with a plug for power supply and CAN and LVDS interfaces,</li> <li>– with or without electronic components for dynamic adjustments of colour,</li> <li>– in a housing, with or without mechanical, touch-sensitive or contactless control functions and with or without active cooling system,</li> </ul> <p>suitable for installation in motor vehicles of Chapter 87<sup>(2)</sup></p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.5018        | ex 8529 90 92 | 67    | <p>Colour LCD display panel for LCD monitors of heading 8528:</p> <ul style="list-style-type: none"> <li>- with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,</li> <li>- with or without a touch screen,</li> <li>- with backlight, micro-controller,</li> <li>- with a CAN (Controller area network)-controller with one or more LVDS (Low-voltage differential signalling) interfaces and one or more CAN/power supply sockets or with an APIX (Automotive Pixel Link) controller with APIX interface,</li> <li>- in a housing with or without a heat sink at the back of the housing,</li> <li>- without a signal-processing module,</li> <li>- whether or not with haptic and acoustical feedback,</li> </ul> <p>for use in the manufacture of vehicles of Chapter 87<sup>(2)</sup></p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6781        | ex 8529 90 92 | 85    | <p>Colour LCD module in a housing:</p> <ul style="list-style-type: none"> <li>– with a diagonal screen measurement of 14.48 cm or more but not more than 26 cm,</li> <li>– without touch screen,</li> <li>– with a backlight and micro-controller,</li> <li>– with a CAN (Controller Area Network) controller, an LVDS (Low-Voltage Differential Signalling) interface and a CAN/power connector,</li> <li>– without a signal processing module,</li> <li>– with control electronics for pixel addressing only,</li> <li>– with a motorised mechanism for moving the display screen,</li> </ul> <p>for permanent installation in vehicles of Chapter 87<sup>(2)</sup></p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6849        | ex 8536 69 90 | 60    | Electrical sockets and plugs with a length of not more than 12,7 mm or a diameter of not more than 10,8 mm, for use in the production of hearing aids and speech processors <sup>(2)</sup>  | 0 %                     | p/st               | 31.12.2022                         |
| 0.5028        | ex 8536 69 90 | 84    | Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528 <sup>(2)</sup>   | 0 %                     | p/st               | 31.12.2025                         |
| 0.6864        | ex 8537 10 91 | 50    | Fuse control module in a plastic housing with mounting brackets comprising: <ul style="list-style-type: none"> <li>– sockets with or without fuses,</li> <li>– connecting ports,</li> <li>– a printed circuit board with embedded microprocessor, micro switch and relay,</li> </ul> of a kind used in the manufacture of goods of chapter 87 | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.6889        | ex 8537 10 98 | 35    | <p>Electronic control unit without memory, for a voltage of 12 V, for information exchange systems in vehicles (for connection of audio, telephony, navigation, camera and wireless car service) containing:</p> <ul style="list-style-type: none"> <li>– 2 rotary knobs</li> <li>– 27 or more pushbuttons</li> <li>– LED lights</li> <li>– 2 integrated circuits for receiving and sending of control signals via the LIN-bus</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6866        | ex 8538 90 91<br>ex 8538 90 99 | 20<br>50 | Interior antenna for a car door locking system, comprising:<br>– an antenna module in a plastic housing,<br>– a connection cable with a plug,<br>– at least two mounting brackets,<br>whether or not PCB including integrated circuits, diodes and transistors,<br>for use in the manufacture of goods of Chapter 87(2) | 0 %                     | p/st               | 31.12.2025                         |
| 0.6710        | ex 8544 30 00<br>ex 8544 42 90 | 60<br>50 | Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and audio systems to a USB connector, for use in the manufacture of goods of Chapter 87(2)  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6867        | ex 8544 30 00 | 85    | <p>Extension two-core cable with two connectors, containing at least:</p> <ul style="list-style-type: none"> <li>– a rubber grommet,</li> <li>– a metal attachment bracket,</li> </ul> <p>of a kind used to connect vehicle speed sensors in the manufacture of vehicles of Chapter 87</p>                     | 0 %                     | p/st               | 31.12.2025                         |
| 0.6853        | ex 8544 42 90 | 70    | <p>Electric conductors:</p> <ul style="list-style-type: none"> <li>– of a voltage of not more than 80 V,</li> <li>– with a length of not more than 120 cm,</li> <li>– fitted with connectors,</li> </ul> <p>for use in the manufacture of hearing aids, accessory kits and speech processors<sup>(2)</sup></p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6861        | ex 8544 49 93 | 30    | <p>Electric conductors:</p> <ul style="list-style-type: none"> <li>- of a voltage of not more than 80 V,</li> <li>- of a platinum-iridium-alloy,</li> <li>- coated with poly(tetrafluoroethylene),</li> <li>- without connectors,</li> </ul> <p>for use in the manufacture of hearing aids, implants and speech processors<sup>(2)</sup></p>   | 0 %                     | m                  | 31.12.2025                         |
| 0.5002        | ex 8545 90 90 | 40    | <p>Corrosion resistant, layered technical fibre substrate of a gas diffuser layer with:</p> <ul style="list-style-type: none"> <li>- controlled fibre length, flex strength, porosity, thermal conductance, electrical resistance,</li> <li>- a thickness of less than 600 µm,</li> <li>- a weight of less than 500 g/m<sup>2</sup></li> </ul> | 0 %                     | m <sup>2</sup>     | 31.12.2021                         |



| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.6707        | ex 8708 30 10<br>ex 8708 30 91 | 70<br>40 | Ductile cast iron brake caliper jaw, of a kind used in the manufacture of goods of Chapter 87  | 0 %                     | p/st               | 31.12.2025                         |
| 0.6869        | ex 8708 40 20<br>ex 8708 40 50 | 20<br>10 | Automatic hydrodynamic gearbox<br>– with a hydraulic torque converter,<br>– without transfer box and cardan shaft,<br>– whether or not with front differential,<br>for use in the manufacture of motor vehicles of Chapter 87 <sup>(2)</sup> | 0 %                     | p/st               | 31.12.2025                         |
| 0.6648        | ex 8708 50 20<br>ex 8708 50 99 | 20<br>10 | Transmission shaft in carbon fibre reinforced plastics consisting of a unique piece without any joint in the middle<br>– of a length of 1 m or more but not more than 2 m,<br>– of a weight of 6 kg or more but not more than 9 kg           | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6711        | ex 8708 80 20<br>ex 8708 80 35 | 10<br>10 | Upper strut insulator containing:<br>– a metal holder with three mounting screws, and<br>– a rubber bump,<br>for use in the manufacture of goods of Chapter 87(2)   | 0 %                     | p/st               | 31.12.2025                         |
| 0.6859        | ex 8708 91 20<br>ex 8708 91 99 | 30<br>30 | Aluminium alloy inlet or outlet air tank manufactured to standard EN AC 42100 with:<br>– an insulating area flatness of not more than 0,1 mm,<br>– a permissible particle quantity of 0,3 mg per tank,<br>– a distance between pores of 2 mm or more,<br>– pore sizes of not more than 0,4 mm, and<br>– not more than 3 pores larger than 0,2mm,<br>of a kind used in heat exchangers for car cooling systems | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7716        | ex 8708 91 35                  | 20       | <p>Turbocharger cooling duct containing:</p> <ul style="list-style-type: none"> <li>- an aluminum alloy duct with at least one metal holder and at least two mounting holes,</li> <li>- a rubber pipe with clips,</li> <li>- a stainless steel flange highly resistant to corrosion [SUS430JIL],</li> </ul> <p>for use in the manufacture of compression ignition engines of motor vehicles<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2024                         |
| 0.6687        | ex 8708 95 10<br>ex 8708 95 99 | 10<br>20 | <p>Inflatable safety cushion of high strength polyamide fibre:</p> <ul style="list-style-type: none"> <li>- sewn,</li> <li>- folded into three-dimensional packing form, fixed by thermal forming, or flat (unfolded) safety cushion with or without thermal forming</li> </ul>   | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.6688        | ex 8708 95 10<br>ex 8708 95 99 | 20<br>30 | Inflatable safety cushion of high strength polyamide fibre:<br>– sewn,<br>– folded,<br>– with three-dimensionally applied silicone bonding for air bag cavity forming and load-regulated air bag sealing,<br>– suitable for cool inflator technology                          | 0 %                     | p/st               | 31.12.2025                         |
| 0.7581        | ex 8708 50 20<br>ex 8708 50 99 | 60<br>15 | Car transfer case with single input, dual output, to distribute torque between front and rear axles in an aluminium housing, with dimension of not more than 565 × 570 × 510 mm, comprising:<br>– at least an actuator,<br>– whether or not an interior distribution by chain | 0 %                     | -                  | 31.12.2024                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6686        | ex 8714 10 90 | 10    | Motorcycle fork rod inner tubes:<br><ul style="list-style-type: none"> <li>- of SAE1541 carbon steel,</li> <li>- with a hard chromium layer of 20 µm (+ 15 µm/ - 5 µm),</li> <li>- having a wall thickness of 1,3 mm or more, but not more than 1,6 mm,</li> <li>- having an elongation at break of 15 %,</li> <li>- perforated</li> </ul> | 0 %                     | p/st               | 31.12.2025                         |
| 0.6848        | ex 8714 10 90 | 70    | Motor bikes radiators in consignment of 100 pieces or more   | 0 %                     | p/st               | 31.12.2022                         |
| 0.6879        | ex 8714 96 10 | 10    | Pedals, for use in the manufacture of bicycles (including electric bicycles) <sup>(2)</sup>  | 0 %                     | -                  | 31.12.2025                         |
| 0.6878        | ex 8714 99 90 | 30    | Seat posts, for use in the manufacture of bicycles (including electric bicycles) <sup>(2)</sup>  | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.4883        | ex 9001 90 00 | 85    | Light guide panel made of poly(methyl methacrylate):<br><ul style="list-style-type: none"> <li>– whether or not cut,</li> <li>– whether or not printed,</li> </ul> for use in the manufacture of backlight units for flat screen TV <sub>S</sub> (2)  | 0 %                     | -                  | 31.12.2025                         |
| 0.7590        | ex 9002 11 00 | 18    | Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with:<br><ul style="list-style-type: none"> <li>– a horizontal field of view range to a maximum of 120 deg,</li> <li>– a diagonal field of view range to a maximum of 92 deg,</li> <li>– a focal length to a maximum of 7,50 mm,</li> <li>– a relative aperture of a maximum of F/2,90,</li> <li>– a maximum diameter of 22 mm</li> </ul> | 0 %                     | -                  | 31.12.2023                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.5692        | ex 9002 11 00                  | 20       | Lenses:<br>- measuring not more than 95 mm × 55 mm × 50 mm,<br>- with a resolution of 160 lines/mm or better, and<br>- with a zoom ratio of 3 or more times | 0 %                     | -                  | 31.12.2022                         |
| 0.5025        | ex 9401 90 80                  | 10       | Ratchet disk for use in the manufacture of reclining car seats <sup>(2)</sup>   | 0 %                     | p/st               | 31.12.2025                         |
| 0.4846        | ex 9503 00 75<br>ex 9503 00 95 | 10<br>10 | Plastic cable car scale models, whether or not with a motor, for printing <sup>(2)</sup>  | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.6950        | ex 9607 20 10 | 10    | Sliders, narrow tape with mounted zipper teeth, pin/boxes and other parts of slide fasteners, of base metal for use in the manufacture of zippers <sup>(2)</sup> | 0 %                     | -                  | 31.12.2022                         |
| 0.6949        | ex 9607 20 90 | 10    | Narrow strips mounted with plastic chain scoops for use in the manufacture of zippers <sup>(2)</sup>   | 0 %                     | -                  | 31.12.2025                         |

- (1) However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.
- (2) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1).
- (3) Only the *ad valorem* duty is suspended. The specific duty shall continue to apply<sup>1</sup>;



(3) the following entries are added or inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.8021        | 2804 70 10    |       | Red phosphorus  | 0 %                     | -                  | 31.12.2022                         |
| 0.8022        | 2804 70 90    |       | Phosphorus, other than red phosphorus   | 0 %                     | -                  | 31.12.2023                         |
| 0.7974        | ex 2903 39 19 | 40    | 3-(Bromomethyl)pentane (CAS RN 3814-34-4) with a purity by weight of 99 % or more                               | 0 %                     | -                  | 31.12.2025                         |
| 0.8017        | ex 2903 99 80 | 25    | 2,2'-Dibromobiphenyl (CAS RN 13029-09-9) with a purity by weight of 95 % or more                                | 0 %                     | -                  | 31.12.2025                         |
| 0.8018        | ex 2903 99 80 | 35    | 2-Bromo-9,9'-spirob[9H-fluoren] (CAS RN 171408-76-7) with a purity by weight of 95 % or more                    | 0 %                     | -                  | 31.12.2025                         |
| 0.7957        | ex 2904 99 00 | 55    | 2,4-dichloro-1,3-dinitro-5-(trifluoromethyl)benzene (CAS RN 29091-09-6) with a purity by weight of 96 % or more | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7963        | ex 2906 29 00 | 70    | 1,2,3,4-Tetrahydro-1-naphthol (CAS RN 529-33-9) with a purity by weight of 95 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.8015        | ex 2914 29 00 | 35    | 4-( <i>trans</i> -4-Propylcyclohexyl)cyclohexanone (CAS RN 82832-73-3) with a purity by weight of 95 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.7955        | ex 2915 24 00 | 10    | Acetic anhydride (CAS RN 108-24-7) with a purity by weight of 97 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.7980        | ex 2916 19 95 | 60    | Methyl 2-fluoroprop-2-enoate (CAS RN 2343-89-7) with a purity by weight of 93 % or more, whether or not with not more than 7 % of the stabiliser 2,6-di- <i>tert</i> -butyl- <i>p</i> -cresol (CAS RN 128-37-0) and Tetrabutylammonium nitrite (CAS RN 26501-54-2) | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7940        | ex 2916 19 95 | 70    | Methyl 3-methyl-2-butenate (CAS RN 924-50-5) with a purity by weight of 99,0 % or more            | 0 %                     | -                  | 31.12.2025                         |
| 0.7931        | ex 2916 20 00 | 25    | Cyclohexanecarbonyl chloride (CAS RN 2719-27-9) with a purity by weight of 99 % or more           | 0 %                     | -                  | 31.12.2025                         |
| 0.7933        | ex 2916 20 00 | 35    | 2-Cyclopropylacetic acid (CAS RN 5239-82-7) with a purity by weight of 95 % or more               | 0 %                     | -                  | 31.12.2025                         |
| 0.7929        | ex 2916 39 90 | 16    | 3-Fluoro-5-iodo-4-methylbenzoic acid (CAS RN 861905-94-4) with a purity by weight of 97 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.8008        | ex 2918 29 00 | 40    | 3-Hydroxy-4-nitrobenzoic acid (CAS RN 619-14-7) with a purity by weight of more than 96,5 %       | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7934        | ex 2918 99 90 | 43    | Vanillic acid (CAS RN 121-34-6) with a purity by weight of 98,5 % or more                             | 0 %                     | -                  | 31.12.2025                         |
| 0.7947        | ex 2921 29 00 | 70    | N,N,N',N'-tetramethylethylenediamine (CAS RN 110-18-9) with a purity by weight of 99 % or more        | 0 %                     | -                  | 31.12.2025                         |
| 0.8019        | ex 2921 49 00 | 45    | 2-(4-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 897671-69-1) with a purity by weight of 95 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.8020        | ex 2921 49 00 | 55    | 2-(2-Biphenyl)amino-9,9-dimethylfluoren (CAS RN 1198395-24-2) with a purity by weight of 95 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.7946        | ex 2922 19 00 | 29    | N-Methyl-N-(2-hydroxyethyl)-p-toluidine (CAS RN 2842-44-6) with a purity by weight of 99 % or more    | 0 %                     | -                  | 31.12.2025                         |
| 0.7935        | ex 2922 19 00 | 70    | 2-Benzylaminoethanol (CAS 104-63-2) with a purity by weight of 98 % or more                           | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.8000        | ex 2924 19 00 | 18    | 2-(((Butylamino)carbonyloxy)ethyl acrylate (CAS RN 63225-53-6) with a purity by weight of 97 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.8013        | ex 2925 19 95 | 40    | <i>N</i> -Iodosuccinimide (CAS RN 516-12-1) with a purity by weight of 98,5 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.7985        | ex 2930 90 98 | 88    | 1-4-[(4-Benzoylphenyl)sulphonyl]phenyl}-2-methyl-2-[(4-methylphenyl)sulphonyl]propan-1-one (CAS RN 272460-97-6) with a purity by weight of 94 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.7951        | ex 2931 90 00 | 25    | <i>N</i> -(3-(dimethoxymethylsilyl)propyl)ethylenediamine (CAS RN 3069-29-2) with a purity by weight of 98 % or more                                    | 0 %                     | -                  | 31.12.2025                         |
| 0.7958        | ex 2932 20 90 | 18    | 4-Hydroxycoumarin (CAS-RN 1076-38-6) with a purity by weight of 98 % or more  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7984        | ex 2932 20 90 | 23    | 1,4-Dioxane-2,5-dione (CAS RN 502-97-6) with a purity by weight of 99,5 % or more                                | 0 %                     | -                  | 31.12.2025                         |
| 0.7978        | ex 2932 99 00 | 68    | 3,9-Diethylidene-2,4,8,10-tetraoxaspiro[5.5]undecane (CAS RN 65967-52-4) with a purity by weight of 98 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.7930        | ex 2932 99 00 | 73    | 5-Fluoro-3-methylbenzofuran-2-carboxylic acid (CAS RN 81718-76-5) with a purity by weight of 97 % or more        | 0 %                     | -                  | 31.12.2025                         |
| 0.7936        | ex 2932 99 00 | 78    | Methyl 2,2-difluoro-1,3-benzodioxole-5-carboxylate (CAS RN 773873-95-3) with a purity by weight of 98 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.7954        | ex 2932 99 00 | 83    | 6,11-Dihydrodibenz[b,e]oxepin-11-one (CAS RN 4504-87-4) with a purity by weight of 98 % or more                  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7938        | ex 2933 19 90 | 43    | tert-Butyl 2-(3,5-dimethyl-1H-pyrazol-4-yl)acetate (CAS RN 1082827-81-3) with a purity by weight of 95 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.7937        | ex 2933 29 90 | 23    | 1,1'-Thiocarbonylbis(imidazole) (CAS RN 6160-65-2) with a purity by weight of 95 % or more                         | 0 %                     | -                  | 31.12.2025                         |
| 0.7976        | ex 2933 39 99 | 83    | 2-Hydroxy-4-azoniaspiro[3,5]nonane chloride (CAS RN 15285-58-2) with a purity by weight of 97 % or more            | 0 %                     | -                  | 31.12.2025                         |
| 0.7925        | ex 2933 39 99 | 84    | Diethyl(3-pyridyl)borane (CAS RN 89878-14-8) with a purity by weight of 98 % or more                               | 0 %                     | -                  | 31.12.2025                         |
| 0.7981        | ex 2933 39 99 | 86    | 3-(N-hydroxycarbamimidoyl)pyridine 1-oxide (CAS RN 92757-16-9) with a purity by weight of 97 % or more             | 0 %                     | -                  | 31.12.2025                         |
| 0.7939        | ex 2933 39 99 | 87    | 6-Chloro-N-(2,2-dimethylpropyl)pyridine-3-carboxamide (CAS RN 585544-20-3) with a purity by weight of 97 % or more | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7986        | ex 2933 39 99 | 88    | Benzyl 4-amino-3-chloro-6-(4-chloro-2-fluoro-3-methoxyphenyl)-5-fluoropyridine-2-carboxylate (CAS RN 1390661-72-9) with a purity by weight of 92 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.7952        | ex 2933 69 80 | 33    | 2,4,6-Trichloro-1,3,5-triazine (CAS RN 108-77-0) with a purity by weight of 99 % or more   | 0 %                     | -                  | 31.12.2025                         |
| 0.7927        | ex 2933 99 80 | 60    | 2-[(6,11-Dihydro-5H-dibenz[b,e]azepin-6-yl)-methyl]-1H-isoindole-1,3(2H)-dione (CAS RN 143878-20-0) with a purity by weight of 99 % or more                | 0 %                     | -                  | 31.12.2025                         |
| 0.7971        | ex 2933 99 80 | 70    | 5-(Bis-(2-hydroxyethyl)-amino)-1-methyl-1H-benzimidazole-2-butanoic acid ethyl ester (CAS RN 3543-74-6) with a purity by weight of 98 % or more            | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.8014        | ex 2933 99 80 | 80    | Pyrrole-2-carboxaldehyde (CAS RN 1003-29-8) with a purity by weight of 97 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.7926        | ex 2934 99 90 | 65    | Benzo[b]thiophen-10-methoxycycloheptanone (CAS RN 59743-84-9) with a purity by weight of 98 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.7944        | ex 2934 99 90 | 70    | 1,3,4-thiadiazolidine-2,5-dithione (CAS RN 1072-71-5) with a purity by weight of 95 % or more  | 0 %                     | -                  | 31.12.2025                         |
| 0.7928        | ex 2935 90 90 | 44    | 4-[2-(7-Methoxy-4,4-dimethyl-1,3-dioxo-3,4-dihydroisoquinolin-2(1H)-yl)ethyl]benzenesulphonamide (CAS RN 33456-68-7) with a purity by weight of 99,5 % or more | 0 %                     | -                  | 31.12.2025                         |
| 0.7943        | ex 3201 90 20 | 10    | <i>Rhus chinensis</i> gall ( <i>Galla chinensis</i> ) water-based extract, with a tannin content by weight of 85 % or less                                     | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7975        | ex 3801 10 00 | 10    | <p>Artificial graphite in powder form, (CAS RN 7782-42-5) with:</p> <ul style="list-style-type: none"> <li>- a secondary particle structure which is aggregated from smaller primary particles,</li> <li>- without coating on the surface,</li> <li>- particle size represented by d50 value of 13,5 µm (± 0,5),</li> <li>- specific surface area (measured by BET) less than 2,0 m<sup>2</sup>/g,</li> <li>- tap density: 1,10 ~ 1,70 g/cm<sup>3</sup>,</li> <li>- specific Discharge Capacity of 351,0 mAh/g (± 3,0),</li> <li>- initial efficiency of 94,0 % (± 1,0)</li> </ul> | 1.8 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7994        | ex 3801 10 00 | 20    | Artificial graphite (CAS RN 7782-42-5) powder form, with: <ul style="list-style-type: none"> <li>- specific surface area (measured by BET) of 0,8 m<sup>2</sup>/g (± 0,25),</li> <li>- tap density: 0,85 g/cm<sup>3</sup> (± 0,10),</li> <li>- particle size represented by d50 value of 21,0 µm (± 2,0),</li> <li>- specific discharge capacity of 351,0 mAh/g (± 3,0),</li> <li>- initial efficiency of 94,0 % (± 2,0)</li> </ul> | 1.8 %                   | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7998        | ex 3815 90 90 | 38    | <p>Photoinitiator, containing by weight:</p> <ul style="list-style-type: none"> <li>- 80 % or more of polyethylene glycol di[β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate (CAS RN 886463-10-1),</li> <li>- not more than 17 % of polyethylene glycol [β-4-[4-(2-dimethylamino-2-benzyl)butanoylphenyl]piperazine]propionate</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.7999        | ex 3815 90 90 | 48    | <p>Photoinitiator containing by weight:</p> <ul style="list-style-type: none"> <li>- 88 % or more of α-(2-benzoylbenzoyl)-ω-[(2-benzoylbenzoyl)oxy]-poly(oxy-1,2-ethanediyl) (CAS RN 1246194-73-9),</li> <li>- not more than 12 % of α-(2-benzoylbenzoyl)-ω-hydroxy-poly(oxy-1,2-ethanediyl) (CAS RN 1648797-60-7)</li> </ul>                                   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7950        | ex 3902 90 90 | 65    | Brominated butadiene-styrene copolymer (CAS RN 1195978-93-8) with a bromine content of 60 % by weight or more but not more than 68 %, in forms as defined in Note 6 (b) to Chapter 39  | 0 %                     | -                  | 31.12.2025                         |
| 0.7953        | ex 3910 00 00 | 65    | Liquid copolymer based on polydimethylsiloxane with terminal epoxide groups CAS RN 2102536-93-4)   | 0 %                     | -                  | 31.12.2025                         |
| 0.8009        | ex 3911 90 99 | 38    | Mixture containing by weight:<br>- 90 % ( $\pm$ 1 %) of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and<br>- 10 % ( $\pm$ 1 %) of a hydrogenated styrene butadiene copolymer (CAS RN 66070-58-4) | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.8010        | ex 3911 90 99 | 48    | Mixture containing by weight:<br>– 90 % ( $\pm 1$ %) of 1,4:5,8-dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and<br>– 10 % ( $\pm 1$ %) of an ethylene-propylene copolymer (CAS RN 9010-79-1) | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7949        | ex 3920 61 00 | 40    | <p>Extruded thermoplastic foils or films of polycarbonate with:</p> <ul style="list-style-type: none"> <li>– matt surface texture on both sides,</li> <li>– a thickness of more than 50 µm but not more than 200 µm,</li> <li>– a width of 800 mm or more, but not more than 1 500 mm, and</li> <li>– a length of 915 m or more, but not more 2 500 m,</li> </ul> <p>for use in the production of retroreflective products<sup>(2)</sup></p> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.8011        | ex 3920 62 19<br>ex 3920 62 90 | 68<br>20 | Poly(ethylene terephthalate) film in rolls:<br>– with a thickness of 50 µm or more but not more than 350 µm, and<br>– covered with a layer of sputtered precious metal such as gold or palladium with a thickness of 0,02 µm or more but not more than 0,06 µm | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.8005        | ex 3920 99 28 | 48    | <p>Thermoplastic polyurethane foil in rolls, with:</p> <ul style="list-style-type: none"> <li>– a width of 900 mm or more but not more than 1016 mm,</li> <li>– a matt finish,</li> <li>– a thickness of 0,4 mm (<math>\pm 8\%</math>),</li> <li>– an elongation at break of 480 % or more (ASTM D412 (Die C)),</li> <li>– a tensile strength in machine direction of 470 (<math>\pm 10</math>) kg/cm<sup>2</sup> (ASTM D412 (Die C)),</li> <li>– a Shore A hardness of 90 (<math>\pm 3</math>) (ASTM D2240),</li> <li>– a tear strength of 100 (<math>\pm 10</math>) kg/cm<sup>2</sup> (ASTM D624 (Die C)),</li> <li>– a melting point of 165°C (<math>\pm 10</math> °C)</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.8024        | ex 5603 14 10 | 20    | <p>Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media:</p> <ul style="list-style-type: none"> <li>– of weight of 160 g/m<sup>2</sup> or more but not more than 300 g/m<sup>2</sup></li> <li>– laminated on one side with a membrane or a membrane and aluminium</li> <li>– with filtration efficiency according to DIN 60335-2-69:2008 minimum Filter class M</li> <li>– pleatable</li> </ul> | 0 %                     | m <sup>2</sup>     | 31.12.2023                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.8028        | ex 6909 19 00 | 40    | <p>Ceramic-carbon absorption cartridges with the following characteristics:</p> <ul style="list-style-type: none"> <li>– extruded fired ceramic bound multicellular cylindrical structure,</li> <li>– 10 % or more by weight but not more than 35 % by weight of activated carbon,</li> <li>– 65 % or more by weight but not more than 90 % by weight of ceramic binder,</li> <li>– with a diameter of 29 mm or more but not more than 41 mm,</li> <li>– a length of not more than 150 mm,</li> <li>– fired at temperature of 800 °C or more, and</li> <li>– for vapours adsorption,</li> </ul> <p>of a kind used for assembly in fuel vapours absorbers in fuel systems of motor vehicles</p> | 0 %                     | p/st               | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7913        | ex 7506 20 00 | 20    | <p>Sheets and strips in coils of nickel alloy to standard ASME SB-582/UNS N06030 with:</p> <ul style="list-style-type: none"> <li>– a thickness of 0,5 mm or more but not more than 3 mm,</li> <li>– a width of 250 mm or more but not more than 1 219 mm</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7997        | ex 7616 99 90 | 35    | <p>Aluminum plate with:</p> <ul style="list-style-type: none"> <li>– a length of 36 mm or more but not more than 49 mm,</li> <li>– a width of 29,8 mm or more but not more than 45,2 mm,</li> <li>– a thickness of 0,18 mm or more but not more than 0,66 mm,</li> </ul> <p>equipped with a polypropylene tape with:</p> <ul style="list-style-type: none"> <li>– a length of 6,5 mm or more but not more than 16,5 mm,</li> <li>– a width of 39 mm or more but not more than 56 mm,</li> <li>– characteristic allowing to create solid joint with Pouch external layer by melting process assuring leak and pressure proof sealing of Cell,</li> <li>– resistance to influence of electrolyte,</li> </ul> <p>for use in the manufacture of lithium-ion battery cells for motor vehicle batteries<sup>(2)</sup></p> | 3 %                     | -                  | 31.12.2021                         |

| Serial Number | CN code       | TARIC | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|---|-------------------------|--------------------|------------------------------------|
| 0.7966        | ex 8104 19 00 | 10    | Unwrought magnesium containing 93 % or more but not more than 99,7 % by weight of magnesium   | 0 %                     | -                  | 31.12.2025                         |
| 0.7942        | ex 8108 90 30 | 35    | Bars and wires of titanium with a titanium content of 98,8 % or more but not more than 99,9 % of a diameter less than 20 mm   | 0 %                     | -                  | 31.12.2025                         |
| 0.8012        | ex 8406 82 00 | 10    | Industrial steam turbine with: <ul style="list-style-type: none"> <li>- an output of 5 MW or more but not more than 40 MW,</li> <li>- designed for a pressure of not more than 140 bar and a temperature of not more than 540 °C,</li> <li>- equipped with double seat valves on the live steam side which are operated with a hydraulic servo of not more than 12 bar</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7961        | ex 8409 91 00<br>ex 8481 90 00 | 55<br>60 | Nozzle body for the regulation of angle and distribution of fuel injection:<br><ul style="list-style-type: none"> <li>– of a cylindrical shape,</li> <li>– made of stainless steel,</li> <li>– with 4 or more, but not more than 16 holes,</li> <li>– with a flow rate of 100 cm<sup>3</sup>/minute or more, but not more than 500 cm<sup>3</sup>/minute</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7965        | ex 8409 91 00 | 75    | <p>Housing of fuel injection valve for generating an electromagnetic field to actuate the injection valve with:</p> <ul style="list-style-type: none"> <li>– an inlet diameter of 2 mm or more, but not more than 10 mm,</li> <li>– an outlet diameter of 2 mm or more, but not more than 10 mm,</li> <li>– an electric coil with a resistance of 10 <math>\Omega</math> or more, but not more than 15 <math>\Omega</math>, which ends in an electrical connection,</li> <li>– a plastic covering moulded around a stainless steel tube</li> </ul> | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7967        | ex 8409 91 00<br>ex 8481 90 00 | 80<br>70 | Nozzle needle for opening and closing the flow of fuel in the engine, with:<br>– 2 holes,<br>– 4 grooves,<br>– a diameter of 3 mm or more, but not more than 6 mm,<br>– a length of 25 mm or more, but not more than 35 mm,<br>– made of stainless steel with hard-chrome plating | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7969        | ex 8413 30 20 | 40    | High-pressure plunger pump for direct diesel injection, with: <ul style="list-style-type: none"> <li>– an operating pressure of not more than 275 MPa,</li> <li>– a camshaft,</li> <li>– a fluid discharging of 15 cm<sup>3</sup> per minute or more, but not more than 1 800 cm<sup>3</sup> per minute,</li> <li>– an electric pressure regulating valve</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.7970        | ex 8413 30 20 | 50    | High-pressure plunger pump for direct diesel injection: <ul style="list-style-type: none"> <li>– with an operating pressure of not more than 275 MPa,</li> <li>– designed to contact the crankshaft,</li> <li>– with an electromagnetic valve</li> </ul>   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7996        | ex 8418 99 90 | 20    | Aluminium connecting block for connecting to a condenser manifold in welding process: <ul style="list-style-type: none"> <li>– hardened to T6 or T5 temper,</li> <li>– with a weight of not more than 150 g,</li> <li>– with a length of 20 mm or more but not more than 150 mm,</li> <li>– with a fixing rail in one piece</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.8004        | ex 8418 99 90 | 30    | Receiver dryer profile for connecting to a condenser manifold in welding process with: <ul style="list-style-type: none"> <li>– a braze flatness of not more than 0,2 mm,</li> <li>– a weight of 100 g or more but not more than 600 g,</li> <li>– a fixing rail in one piece</li> </ul>   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7979        | ex 8479 89 97 | 55    | Integrated automated turnkey machinery line for manufacturing jelly rolls of cylindrical lithium ion battery cells by winding, tab assembly and cutting of cathode, separator and anode  | 0.8 %                   | -                  | 31.12.2021                         |
| 0.7982        | ex 8479 89 97 | 65    | Integrated automated turnkey machinery line for the assembly of battery cells to cylindrical lithium ion batteries with a speed of 300 parts per minute and production line  | 0.8 %                   | -                  | 31.12.2021                         |
| 0.7964        | ex 8479 90 70 | 40    | Housing of the rotor part of the mechanical unit ensuring the adjustment of movement of the camshaft compared to the crankshaft: <ul style="list-style-type: none"> <li>- of a circular shape,</li> <li>- made of steel alloy with sintering process,</li> <li>- with not more than 8 oil chambers,</li> <li>- with a Rockwell hardness of 55 or more,</li> <li>- with a density of 6,5 g/cm<sup>3</sup>, or more, but not more than 6,7 g/cm<sup>3</sup></li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7968        | ex 8481 30 91<br>ex 8481 30 99 | 30<br>50 | Mechanical check (non-return) valve for opening and closing of the flow of fuel:<br><ul style="list-style-type: none"> <li>– with an operating pressure of not more than 250 MPa,</li> <li>– with a flow rate of 45 cm<sup>3</sup>/minute or more, but not more than 55 cm<sup>3</sup>/minute,</li> <li>– with 4 input holes, each of them with a diameter of 1,2 mm or more, but not more than 1,6 mm,</li> <li>– made of steel</li> </ul> | 0 %                     | -                  | 31.12.2025                         |
| 0.7960        | ex 8481 80 59<br>ex 8481 90 00 | 70<br>80 | Flow-control valve<br><ul style="list-style-type: none"> <li>– made of steel,</li> <li>– with an outlet hole with a diameter of at least 0,05 mm, but not more than 0,5 mm,</li> <li>– with an inlet hole with a diameter of at least 0,1 mm, but not more than 1,3 mm</li> </ul>   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.7972        | ex 8527 29 00<br>ex 8529 90 65 | 10<br>38 | Satellite radio receiver module:<br>– with a rectangular shape of dimensions 70,5 x 44,9 x 10,5 mm,<br>– comprising of heat sink and a printed circuit board with resistors, capacitors, transistors, coils, diodes and IC,<br>– being able to process radio frequency signals,<br>– with a medium frequency unit,<br>for use in the manufacture of products falling under heading 8527(2) | 0 %                     | -                  | 31.12.2025                         |
| 0.7987        | ex 8708 50 20<br>ex 8708 50 55 | 15<br>50 | Spherical outboard constant velocity joint ball bearing cage, part of the vehicle's drive system, made of material suitable to be carburized with a carbon content of 0,14 % or more but not more than 0,57 %, forged, turned, punched, milled and hardened  | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7988        | ex 8708 50 20<br>ex 8708 50 99 | 25<br>45 | <p>Ball-type outboard constant velocity joint housing for transmitting a torque from the engine and transmission to the wheels of motor vehicles, in a form of an outer race, with:</p> <ul style="list-style-type: none"> <li>– 6 ball tracks or more but not more than 8, with a thread,</li> <li>– an external involute spline with 21 or more but not more than 38 teeth,</li> <li>– for running with bearing balls made of steel with a carbon content of 0,48 % or more but not more than 0,57 %,</li> <li>– forged, turned, milled and hardened</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code                        | TARIC    | Description   | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|---|-------------------------|--------------------|------------------------------------|
| 0.7989        | ex 8708 50 20<br>ex 8708 50 99 | 35<br>50 | Inboard constant velocity joint tripod housing, with:<br>– an outer diameter of 67,0 mm or more but not more than 99,0 mm,<br>– 3 cold calibrated roller tracks with a diameter of 29,95 mm or more but not more than 49,2 mm,<br>– an external spline with 21 teeth or more but not more than 41,<br>– forged, turned, rolled and hardened | 0 %                     | -                  | 31.12.2025                         |



| Serial Number | CN code                        | TARIC    | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|--------------------------------|----------|--|-------------------------|--------------------|------------------------------------|
| 0.7990        | ex 8708 50 20<br>ex 8708 50 99 | 45<br>55 | Outboard constant velocity joint inner race, part of the vehicle's drive system, with:<br>– 6 or more but not more than 8 ball tracks, suitable for bearing balls with a diameter of 12,0 mm or more but not more than 24,0 mm,<br>– forged, turned, milled, broached and hardened | 0 %                     | -                  | 31.12.2025                         |
| 0.7991        | ex 8708 50 20<br>ex 8708 50 99 | 55<br>60 | Inboard constant velocity joint tripod spider, part of the vehicle's drive system, with:<br>– 3 trunnions with a diameter of 17,128 mm or more but not more than 25,468 mm,<br>– forged, turned, broached and hardened   | 0 %                     | -                  | 31.12.2025                         |

| Serial Number | CN code       | TARIC | Description  | Rate of autonomous duty | Supplementary Unit | Date foreseen for mandatory review |
|---------------|---------------|-------|--|-------------------------|--------------------|------------------------------------|
| 0.7973        | ex 9002 11 00 | 23    | Lenses with: <ul style="list-style-type: none"> <li>– motorized focus, zoom, aperture,</li> <li>– electronically switchable infrared cut filter,</li> <li>– an adjustable focal length not less than 2,7 mm and not more than 55 mm,</li> <li>– a weight of not more than 100 g,</li> <li>– a length of less than 70 mm,</li> <li>– a diameter of not more than 60 mm</li> </ul> | 0 %                     | -                  | 31.12.2025                         |

(2) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1):.