



Council of the
European Union

Brussels, 30 April 2021
(OR. en)

Interinstitutional File:
2021/0112(NLE)

8358/21
ADD 1

UD 132

PROPOSAL

From:	Secretary-General of the European Commission, signed by Ms Martine DEPREZ, Director
date of receipt:	29 April 2021
To:	Mr Jeppe TRANHOLM-MIKKELSEN, Secretary-General of the Council of the European Union
No. Cion doc.:	COM(2021) 217 final
Subject:	ANNEX to the Proposal for a COUNCIL REGULATION amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products

Delegations will find attached document COM(2021) 217 final.

Encl.: COM(2021) 217 final



Brussels, 29.4.2021
COM(2021) 217 final

ANNEX

ANNEX

to the

Proposal for a COUNCIL REGULATION

**amending Regulation (EU) No 1387/2013 suspending the autonomous Common Customs
Tariff duties on certain agricultural and industrial products**

ANNEX

The Annex to Regulation (EU) No 1387/2013 is amended as follows:

- (1) the entries with the following serial numbers are deleted: 0.2938, 0.3108, 0.3139, 0.3141, 0.4179, 0.4197, 0.4734, 0.4735, 0.4883, 0.5312 and 0.5470;
- (2) the following entries replace those entries that have the same serial numbers:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.3341	ex 1515 90 99	92	Vegetable oil, refined or semi-refined, containing by weight 35 % or more but not more than 57 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	0 %	-	31.12.2023
0.7674	ex 2905 32 00	20	(2S)-propane-1,2-diol (CAS RN 4254-15-3) with a purity by weight of 98 % or more	0 %	-	31.12.2023
0.6003	ex 2915 90 70	27	Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more	0 %	-	31.12.2023
0.3468	ex 2916 13 00	40	Zinc Dimethacrylate (CAS RN 13189-00-9) in the form of powder with a purity by weight of 99 % or more, with not more than 1 % of a stabiliser	0 %	-	31.12.2023
0.2941	ex 2920 19 00	40	Tolclofos-methyl (ISO) (CAS RN 57018-04-9) with a purity by weight of 96 % or more	0 %	-	31.12.2023
0.4298	ex 2930 20 00	40	Prosulfocarb (ISO) (CAS RN 52888-80-9) with purity by weight of 97 % or more	0 %	-	31.12.2022
0.5920	ex 2933 29 90	28	Prochloraz (ISO) (CAS RN 67747-09-5) with purity by weight of 97 % or more	0 %	-	31.12.2023
0.6987	ex 2933 59 95	52	6-Benzyladenine (CAS RN 1214-39-7) with a purity by weight of 97 % or more	0 %	-	31.12.2021
0.7815	ex 2934 99 90	82	Rel-(3aR,12bR)-11-Chloro-2,3,3a,12b-tetrahydro-2-methyl-1H-dibenz[2,3:6,7]oxepino[4,5-c]pyrrol-1-one (CAS RN 129385-59-7) with a purity by weight of 97 % or more	0 %	-	31.12.2024
0.7975	ex 3801 10 00	30	Artificial graphite in powder form, (CAS RN 7782-42-5) with: — with or without coating on the surface, — particle size represented by d50 value of 15 µm (± 4), — specific surface area (measured by BET) less than 3,5 m ² /g, — tap density: 1,3 g/m ³ (± 0,5), — specific Discharge Capacity of 348 mAh/g (± 13), — initial efficiency above 93,0 %	1.8 %	-	31.12.2021

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.4459	ex 3919 90 80	83	Reflector or diffuser sheets, in rolls, — for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or — for equal transmission and distribution of light, intended for LCD modules	0 %	-	31.12.2022
0.5139	ex 3920 10 89	55	Ethylene vinyl acetate (EVA) film: — with a raised relief surface with embossed undulations, — not laminated, — not cross-linked, and — with a thickness of more than 0,3 mm	0 %	-	31.12.2021
0.5167	ex 3920 20 29	94	Mono-axial oriented, co-extruded film: — consisting of 3 to 5 layers, — each layer mainly consisting of polypropylene and/or polyethylene, — each layer containing not more than 10 % by weight of other polymers, — whether or not containing titanium dioxide in the core layer, — of an overall thickness of not more than 75 µm	0 %	-	31.12.2022
0.2546	ex 6903 90 90	40	Silicon carbide reactor tubes and holders having a maximum service temperature of 1370 °C or more	0 %	-	31.12.2023
0.8028	ex 6909 19 00	40	Ceramic-carbon absorption or adsorption cartridges of fuel motor vehicle systems, with the following characteristics: — extruded fired ceramic bound multicellular cylindrical structure, — 5 % or more by weight but not more than 70 % by weight of activated carbon, — 30 % or more by weight but no more than 90 % by weight of ceramic binder, — with a diameter of 29 mm or more but no more than 41 mm, — a length of not more than 150 mm, — fired at temperature of 800 °C or more	0 %	p/st	31.12.2025
0.6680	ex 7326 90 98 ex 7907 00 00	40 10	Iron, steel and/or zinc alloy weights: — with a weight of not more than 500 grams and measuring not more than 107 mm x 107 mm x 11 mm, — whether or not with parts of other material, — whether or not with parts of other metals, — whether or not surface treated, — whether or not printed, of a kind used for the production of remote controls	0 %	-	31.12.2025
0.4050	ex 7607 11 90 ex 7607 11 90	65 67	Plain aluminium foil with the following parameters: — an aluminium content of 99,98 % or more, — a thickness of 0,070 mm or more but not more than 0,125 mm, — with a cubic texture, of a kind used for high voltage etching	3.7 %	-	31.12.2021
0.7966	ex 8104 19 00	10	Unwrought magnesium containing 90 % or more but not	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			more than 99,7 % by weight of magnesium			
0.5097	ex 8104 30 00	35	Magnesium powder: — of purity by weight of more than 99,5 %, and — with a particle size of not more than 0,8 mm	0 %	-	31.12.2025
0.4133	ex 8418 99 10 ex 8418 99 10	71 79	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (1)	0 %	p/st	31.12.2021
0.6858	ex 8501 10 99	64	DC motor to control angular position of the flap to adjust gas flow in the Air Throttle and EGR valve: — with Ingress Protection (IP) standard of IP69, — with a rotor speed of not more than 6 500 rpm when not loaded, — with a rated voltage of 12,0 V ($\pm 0,1$), — of a specified temperature range of $- 40$ °C or more but not more than $+ 165$ °C, — with or without a connecting pinion, — with or without an engine connector, — with or without a flange, — with a diameter of not more than 40 mm (not including the flange), — with an overall height of not more than 90 mm (from the base to the pinion)	0 %	-	31.12.2021
0.6809	ex 8501 31 00 ex 8501 32 00	43 55	Automotive-ready, brushless and permanently excited direct current motor with: — a specified speed of not more than 4 100 rpm, — a minimum output of 400 W, but not more than 1,3 kW (at 12V), — a flange diameter of 85 mm or more but not more than 200 mm, — a maximum length of 335 mm, measured from the beginning of the shaft to the outer ending, — a housing length of not more than 265 mm, measured from the flange to the outer ending, — a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease), — a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology, and — surface magnets, — whether or not with electronic power steering controller, — whether or not with pulley, — whether or not with rotor position sensor	0 %	-	31.12.2025
0.7641	ex 8507 60 00	58	Prismatic lithium-ion electric accumulator with: — a width of 120,0 mm or more but not more than 305,0 mm, — a thickness of 12,0 mm or more but not more than 67,0 mm, — a height of 72,0 mm or more but not more than	1,3 %	-	31.12.2021

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			126,0 mm, — a nominal voltage of 3,6 V or more but not more than 3,75 V, and — a nominal capacity of 6,9 Ah or more not more than 265 Ah, for use in the manufacture of rechargeable electric vehicle batteries (1)			
0.5356	ex 8507 60 00	75	Rectangular lithium-ion-accumulator with: — a metal casing, — a length of 147,85 mm or more but not more than 173,15 mm, — a width of 17,4 mm or more but not more than 21,1 mm, — a height of 90,85 mm or more but not more than 95,15 mm, — a nominal voltage of 3,3 V or more but not more than 3,65 V, and — a nominal capacity of 17,5 Ah or more	1.3 %	-	31.12.2021
0.7856	ex 8708 40 20 ex 8708 40 50	70 60	Manual gearbox in cast aluminium housing for transverse installation with: — a width of not more than 480 mm, — a height of not more than 400 mm, — a length of not more than 550 mm, — five or six gears, — a differential gear, — an engine torque of 400 Nm or less, for use in the manufacture of motor vehicles of Heading 8703 (1)	0 %	-	31.12.2024
0.6583	ex 8708 99 10 ex 8708 99 97	60 50	Aluminium engine bracket, with dimensions of: — height of more than 10 mm but not more than 200 mm, — width of more than 10 mm but not more than 250 mm, — length of more than 10 mm but not more than 200 mm, equipped with at least two fixing holes, made of aluminium alloys ENAC-46100 or ENAC-42100 (based on the norm EN:1706) with following characteristics: — internal porosity not more than 1 mm, — outer porosity not more than 2 mm, — rockwell hardness HRB 10 or more, of a kind used in the production of suspensions systems for engines in motor vehicles	0 %	p/st	31.12.2024
0.7101	ex 9001 10 90	40	Fibre optic plates: — uncoated and unpainted, — of a length of 30 mm or more, but not more than 234,5 mm, — of a width of 7 mm or more, but not more than 28 mm, and — of a height of 0,5 mm or more, but not more than 3 mm, of a kind used in dental x-ray systems	0 %	-	31.12.2021

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.7590	ex 9002 11 00	18	Lens assembly consisting of a cylinder-shaped cover made of metal or plastic and optical elements with: — a horizontal field of view range to a maximum of 120 deg, — a diagonal field of view range to a maximum of 105 deg, — a focal length to a maximum of 7,50 mm, — a relative aperture of a maximum of F/2,90, — a maximum diameter of 22 mm	0 %	-	31.12.2023

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)

(3) the following entries are added or inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8144	ex 2710 12 25	20	Mixture of C6 aliphatic hydrocarbons (CAS RN 92112-69-1), containing by weight 60 % or more but not more than 80 % of n-hexane (CAS RN 110-54-3), with: — a specific gravity of 0,666 or more but not more than 0,686, — a total of carbonyl compounds of less than 1 ppm, — a total of acetylenic compounds of less than 2 ppm	0 %	-	31.12.2025
0.8076	ex 2903 99 80	45	1-Bromo-4-(<i>trans</i> -4-propylcyclohexyl)benzene (CAS RN 86579-53-5) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8101	ex 2903 99 80	55	1-Bromo-4-(<i>trans</i> -4-ethylcyclohexyl)benzene (CAS RN 91538-82-8) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8042	ex 2910 90 00	40	[(2 <i>R</i>)-Oxiran-2-yl]methyl 3-nitrobenzenesulphonate (CAS RN 115314-17-5) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.8073	ex 2912 19 00	20	Acrylaldehyde (CAS RN 107-02-8) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8147	2912 42 00		Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde)	0 %	-	31.12.2025
0.8058	ex 2914 29 00	45	4-Propylcyclohexan-1-one (CAS RN 40649-36-3) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8146	ex 2915 90 70	23	Tin bis(2-ethylhexanoate) (CAS RN 301-10-0) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.8057	ex 2916 20 00	45	Cyclopentanecarboxylic acid (CAS RN 3400-45-1) with a purity by weight of 98 % or more	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8039	ex 2916 39 90	78	(2,5-dibromophenyl)acetic acid (CAS RN 203314-28-7) with a purity by weight of 98,0 % or more	0 %	-	31.12.2025
0.8044	ex 2918 19 98	60	(<i>R</i>)- <i>tert</i> -butyl 2'-(1-hydroxyethyl)-3-methyl-[1,1'-biphenyl]-4-carboxylate (CAS RN 1246560-92-8) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8075	ex 2918 30 00	45	Methyl 5-oxo-6,7,8,9-tetrahydro-5H-benzo[7]annulene-2-carboxylate (CAS RN 150192-89-5) with a purity by weight of 96 % or more	0 %	-	31.12.2025
0.8066	ex 2918 99 90	48	2-Bromo-5-methoxybenzoic acid (CAS RN 22921-68-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8045	ex 2921 29 00	15	(2 <i>S</i>)-propane-1,2-diamine dihydrochloride (CAS RN 19777-66-3) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8067	ex 2921 29 00	25	<i>N,N'</i> -Diallylpropane-1,3-diamine dihydrochloride (CAS RN 205041-15-2) with a purity by weight or 96 % or more	0 %	-	31.12.2025
0.8059	ex 2921 49 00	65	Bis-(9,9-dimethylfluoren-2-yl)amine (CAS RN 500717-23-7) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8027	ex 2924 19 00	28	(2 <i>S</i>)-2-amino-5-(carbamoylamino)pentanoic acid ; 2-hydroxybutanedioic acid (2:1) (CAS RN 54940-97-5) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8030	ex 2924 19 00	33	(2 <i>S</i>)-2-amino-5-(carbamoylamino)pentanoic acid ; 2-hydroxybutanedioic acid (1:1) (CAS RN 70796-17-7) with a purity by weight of 98,5 % or more	0 %	-	31.12.2025
0.8041	ex 2924 19 00	38	Diethyl acetamidomalonate (CAS RN 1068-90-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8049	ex 2924 19 00	43	N6-(<i>tert</i> -butoxycarbonyl)-L-lysine methyl ester hydrochloride (CAS RN 2389-48-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8043	ex 2924 29 70	58	2-chloro- <i>N</i> -[1-(4-chloro-3-fluorophenyl)-2-methylpropan-2-yl]acetamide (CAS RN 787585-35-7) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8060	ex 2924 29 70	78	5-amino-3-(4-chlorophenyl)-5-oxopentanoic acid (CAS RN 1141-23-7) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8033	ex 2925 29 00	60	Formamidine acetate (CAS RN 3473-63-0) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8040	ex 2925 29 00	70	Bromomethylidene(dimethyl)azanium bromide (CAS RN 24774-61-6) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.8061	ex 2928 00 90	38	Aqueous solution of methoxyammonium chloride (CAS-RN 593-56-6), containing by weight: — 30 % or more but not more than 40 % of methoxyammonium chloride — not more than 4 % of hydrochloric acid	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8093	ex 2928 00 90	43	2-(3-methoxy-3-oxopropyl)-1,1,1-trimethylhydrazinium bromide (CAS RN 106966-25-0) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8036	ex 2930 90 98	11	Benzyl (2S)-2-amino-3-[3-(methanesulphonylphenyl)]propanoate hydrochloride (CAS RN 1194550-59-8) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8047	ex 2930 90 98	14	(E)-N'-(2-Cyano-4-(3-(1-hydroxy-2-methylpropan-2-yl)thioureido)phenyl)-N,N-dimethyl-formimidamide (CAS RN 1429755-57-6) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8050	ex 2930 90 98	19	4-Amino-5-(ethanesulphonyl)-2-methoxybenzoic acid (CAS RN 71675-87-1) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8069	ex 2930 90 98	28	Mesotrione (ISO) (CAS RN 104206-82-8) in form of wet cake or wet paste, with — a purity of 74 % or more but not more than 87 % by weight, and — a maximum water content of 23 % by weight	0 %	-	31.12.2025
0.8051	ex 2931 90 00	23	Ixazomib citrate (INNM) (CAS RN 1239908-20-3) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8063	ex 2931 90 00	28	Triethoxy(3-isocyanatopropyl)silane (CAS RN 24801-88-5) with a purity by weight of 96 % or more	0 %	-	31.12.2025
0.8035	ex 2932 99 00	38	1-Benzofuran-6-carboxylic acid (CAS RN 77095-51-3) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8046	ex 2933 19 90	48	1-(3-iodo-1-isopropyl-1H-pyrazol-4-yl)ethanone (CAS RN 1269440-49-4) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8068	ex 2933 39 99	30	4-amino-3-(4-phenoxyphenyl)-1-[(3R)-piperidin-3-yl]-1,3-dihydro-2H-imidazo[4,5-c]pyridin-2-one (CAS RN 1971921-35-3) mono oxalate with a purity by weight of the free base of 70 % or more	0 %	-	31.12.2025
0.8072	ex 2933 39 99	75	Clodinafop-propargyl (ISO) (CAS RN 105512-06-9) with a purity by weight of 90 % or more	0 %	-	31.12.2025
0.8074	ex 2933 39 99	80	Tert-Butyl (3R)-3-(4-amino-2-oxo-2,3-dihydro-1H-imidazo[4,5-c]pyridin-1-yl)piperidine-1-carboxylate (CAS RN 1971921-33-1) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8096	ex 2933 39 99	89	1-Benzyl-4-phenylpiperidine-4-carbonitrile monohydrochloride (CAS RN 71258-18-9) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8037	ex 2933 49 90	55	2-(tert-butoxycarbonyl)-5,7-dichloro-1,2,3,4-tetrahydroisoquinoline-6-carboxylic acid (CAS RN 851784-82-2) with a purity by weight of 98 % or more	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8056	ex 2933 59 95	42	2-Chloropyrimidine (CAS RN 1722-12-9) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8038	ex 2933 79 00	45	1-phenyl-3H-indol-2-one (CAS RN 3335-98-6) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8089	ex 2933 99 80	25	6-(4-Benzylamino-3-nitrophenyl)-5-methyl-4,5-dihydro-2H-pyridazin-3-one (CAS RN 77469-62-6) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8032	ex 2933 99 80	65	1,2,4-Triazole (CAS RN 288-88-0) with a purity by weight of 99 % or more	0 %	-	31.12.2025
0.8053	ex 2933 99 80	69	5-Formyl-2,4-dimethyl-1H-pyrrole-3-carboxylic acid (CAS RN 253870-02-9) with a purity by weight of 96 % or more	0 %	-	31.12.2025
0.8054	ex 2933 99 80	76	2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8064	ex 2933 99 80	77	9-[1,1'-Biphenyl]-3-yl-9'-[1,1'-biphenyl]-4-yl-3,3'-bi-9H-carbazole (CAS RN 1643479-47-3) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8094	ex 2934 99 90	40	2,3-Pyrazinedicarboxylic anhydride (CAS RN 4744-50-7) with a purity by weight of 95 % or more	0 %	-	31.12.2025
0.8031	ex 2934 99 90	55	Uridine (CAS RN 58-96-8) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8048	ex 2934 99 90	81	1-(4-aminophenyl)-5-(morpholin-4-yl)-2,3-dihydropyridin-6-one (CAS RN 1267610-26-3) with a purity by weight of 98 % or more	0 %	-	31.12.2025
0.8055	ex 2935 90 90	80	4-Chloro-3-sulphamoylbenzoic acid (CAS RN 1205-30-7) with a purity by weight of 97 % or more	0 %	-	31.12.2025
0.8137	ex 3208 90 19 ex 3911 90 99	13 63	Mixture, containing by weight: — 30 % or more but not more than 40 % of a copolymer of methyl vinyl ether and monobutyl maleate (CAS RN 25119-68-0), — 10 % or more but not more than 20 % of a copolymer of methyl vinyl ether and monoethyl maleate (CAS RN 25087-06-3), — 40 % or more, but not more than 55 % of ethanol (CAS RN 64-17-5), — 1 % or more but not more than 7 % of butan-1-ol (CAS RN 71-36-3)	0 %	-	31.12.2025
0.8083	ex 3824 99 92	92	Solution consisting of: — 50 (± 2) % by weight sodium mentholate (CAS RN 19321-38-1), and — 50 (± 2) % by weight light aliphatic solvent naphtha (petroleum) (CAS RN 64742-89-8)	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8121	ex 3824 99 92	93	Solution of not more than 15 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3) in a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and ethyl methyl carbonate (CAS RN 623-53-0), contains organic carbonate derivatives as additives	3.2 %	-	31.12.2021
0.8062	ex 3824 99 93	51	Tris(hydroxymethyl)phosphine oxide (CAS RN 1067-12-5) with a purity by weight of 85 % or more	0 %	-	31.12.2025
0.8122	ex 3824 99 96	68	Lithium nickel dioxide (CAS RN 12325-84-7) containing by weight: — less than 5 % of lithium hydroxide (CAS RN 1310-65-2), — less than 5 % of lithium carbonate (CAS RN 554-13-2), and — less than 15 % of nickel oxide (CAS RN 11099-02-8)	3.2 %	-	31.12.2021
0.8125	ex 3902 30 00	20	Hydrogenated block copolymer of styrene and isoprene (CAS RN 68648-89-5), containing by weight less than 37 % of styrene	0 %	-	31.12.2025
0.8126	ex 3905 91 00	50	Aqueous solution consisting by weight of: — 10 % or more but not more than 20 % of a copolymer of vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3 (methacryloylamino)propyllauryldimethylammonium chloride (CAS RN 306769-73-3), — not more than 1 % preservatives	0 %	-	31.12.2025
0.8145	ex 3905 91 00	60	Copolymer of vinylpyrrolidone, vinyl caprolactam and dimethylaminoethyl methacrylate (CAS RN 102972-64-5) in solid form, or as an aqueous solution containing by weight: — 27 % or more but not more than 33 % of copolymer, — not more than 1,5 % of ethanol (CAS RN 64-17-5), — not more than 1 % of preservatives	0 %	-	31.12.2025
0.8138	ex 3905 91 00	70	Aqueous solution, containing by weight: — 25 % or more but not more than 35 % of a copolymer of vinyl caprolactam, vinyl pyrrolidone, N,N-dimethylaminopropyl methacrylamide and 3-(methacryloylamino)propyllauryldimethylammonium chloride (CAS RN 748809-45-2), — 10 % or more but not more than 16 % of ethanol (CAS RN 64-17-5) whether or not denatured with tert-butyl alcohol (CAS RN 75-65-0) and/or denatonium benzoate (CAS RN 3734-33-6)	0 %	-	31.12.2025
0.8139	ex 3905 91 00	80	Copolymer of vinylpyrrolidone, acrylic acid and dodecyl methacrylate (CAS RN 83120-95-0)	0 %	-	31.12.2025
0.8097	ex 3910 00 00	75	Copolymer of 80 % dimethylsiloxane, 10 % methyl methacrylate and 10 % butyl acrylate in the form of a white powder	0 %	-	31.12.2025
0.8116	ex 3917 31 00	30	Tubings:	0 %	-	31.12.2021

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
	ex 3917 32 00 ex 3917 39 00	20 20	— with an outer diameter of 0,33 mm or more but not more than 3,3 mm, — with an inner diameter of 0,01 mm or more but not more than 2,1 mm, — suitable for a maximum working pressure rate from 2,7 MPa up to 70 MPa, — suitable for all solutions used in chromatography, — whether or not with fused silica, — whether or not covered with PEEK, for use in chromatographic system (1)			
0.8117	ex 3917 40 00	20	Plastic fittings (kit of nuts and ferrules or nuts) and connectors: — threaded, — supported with or without a stainless steel ring, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, for tubings with: — outer diameter of 0,33 mm or more but not more than 3,3 mm, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, — suitable for all solutions used in chromatography, for use in the production of chromatographic systems (1)	0 %	-	31.12.2021
0.8109	ex 3919 10 80	48	Plastic strips of polypropylene, — self-adhesive, — unilaterally adhesive-coated with an Acrylic Polymer, — in rolls with a width of 20 cm or less, — with a thickness including adhesion layer of 0,03 mm or less, for use in the manufacturing of lithium-ion electric rechargeable batteries (1)	3.2 %	-	31.12.2021
0.8149	ex 3920 10 89	45	Octene and ethylene copolymer plastic film of a thickness of 0,45 mm or more but not more than 0,75 mm, for use in the manufacture of glass to glass photovoltaic solar panels (1)	0 %	-	31.12.2022
0.8118	ex 3926 90 97	58	Plastic ferrules and/or plugs: — supported with or without a stainless steel ring, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, for tubings with: — outer diameter of 0,33 mm or more but not more than 3,3 mm, — suitable for a maximum working pressure rate of 2,7 MPa or more but not more than 114 MPa, — suitable for all solutions used in chromatography, for use in the production of chromatographic systems (1)	0 %	-	31.12.2021
0.8108	ex 5403 31 00	10	Continuous viscose rayon filament yarn of 105 dtex or	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			more but not more than 117 dtex, and consisting of 36 monofilaments or more but not more than 40 monofilaments			
0.8105	ex 8108 90 30	55	Wires of an alloy of titanium: — with a niobium content by weight of 42 % or more but not more than 47 %, — with a diameter of not more than 6 mm, — complying with standard AMS 4982, for use in the production of aerospace fasteners ⁽¹⁾	0 %	-	31.12.2025
0.8148	ex 8412 90 80	20	Bedplate made of solution strengthened ductile iron castings (SSDI), for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine with: — a length of 3,5 m or more but not more than 4,3 m, — a width of 2 m or more but not more than 3,5 m, — a height of 1 m or more but not more than 1,3 m, — a weight of 11 tons or more but not more than 20 tons, — mounting bores for yaw drive, — mounting flange for gearbox support, — drivetrain mount, — different screw sockets	0 %	p/st	31.12.2025
0.8079	ex 8412 90 80	30	Gearbox support used as a support and load-carrying component between the gearbox and the bedplate of a wind turbine, made of solution strengthened ductile iron castings (SSDI), with: — a diameter of 2 m or more, but not more than 5 m, — a weight of 2 tons or more but not more than 7 tons	0 %	p/st	31.12.2025
0.8111	ex 8414 30 20	20	Hermetic reciprocating refrigeration compressor, for isobutane: — with a 3-phase permanent magnet brushless motor, — having left side suction connection and Power Factor Correction (PFC) inverter, — with a maximum cooling capacity of 150 W or more but not more than 240 W, at ASHRAE conditions	0 %	-	31.12.2025
0.8112	ex 8414 30 20	30	Hermetic reciprocating refrigeration compressor for isobutane as refrigerant: — with a 3-phase permanent magnet brushless motor, — having left side suction connection and Power Factor Correction (PFC) inverter feasible to work from 1 300 rpm up to 4 500 rpm, — with a maximum cooling capacity of 150 W or more but not more than 240 W, at ASHRAE conditions	0 %	-	31.12.2025
0.8134	ex 8414 30 20	40	Hermetic reciprocating compressor, for isobutane as refrigerant with: — a Resistance Start Capacitor Run (RSCR) single phase motor, — a general coefficient of performance factor not lower than 1,93 at ASHRAE conditions, — a maximum cooling capacity of 150 W or more but not more than 180 W, at ASHRAE conditions	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
0.8135	ex 8414 30 20	50	Hermetic reciprocating compressor, for isobutane as refrigerant with: — a Resistance Start Capacitor Run (RSCR) single phase motor, — a general coefficient of performance factor not higher than 1,5 at ASHRAE conditions, — a maximum cooling capacity of 150 W or more but not more than 180 W, at ASHRAE conditions	0 %	-	31.12.2025
0.8133	ex 8414 80 73	40	Hermetic heat pump compressor, for R134A or R450A as refrigerant: — with the Single Phase Induction Motor PSC (Permanent Split Capacitor), — having bottom side suction connection and top side discharge connection, — 8,1 cm ³ or 8,2 cm ³ displacement, — running at 3000 rpm, — with a cooling capacity of 920 W or higher, but not higher than 970 W in ASHRAE conditions	0 %	-	31.12.2025
0.8123	ex 8479 89 97	28	Integrated electric brake unit for immediate generation of the hydraulic pressure during braking, full electronic brake control and enabling regenerative braking of motor vehicles with: — electronic brake assistants, — hydraulic unit driven by brushless electric motor, — brake fluid reservoir, for use in the manufacture of plug-in hybrid passenger cars ⁽¹⁾	0 %	-	31.12.2025
0.7962	ex 8479 90 70	50	Rotor part of the mechanical unit ensuring the movement of the camshaft compared to the crankshaft: — with 4 blades that end in grooves, — made of steel alloy with sintering process	0 %	-	31.12.2025
0.8098	ex 8482 50 00	20	Axial roller bearing made of steel: — the retainer is made of cold-rolled steel with a carbon content of up to 0,25 percent, complying with standard ASTM A109-98, — the rollers are made of anti-friction steel according to ASTM 295-94, — with an external diameter of 63 mm or more but not more than 66 mm, — with an internal diameter of 44 mm or more but not more than 46 mm, — with a weight of 23 g or more but not more than 27 g, — with 36 rollers or more but not more than 38 rollers	0 %	p/st	31.12.2025
0.8088	ex 8482 99 00	40	Inner and outer rings made of steel, not grinded, with an internal raceway, with diameters of: — 14,66 mm or more but not more than 76,2 mm for the inner ring, and — 26 mm or more but not more than 100 mm for the outer ring	0 %	-	31.12.2025
0.8100	ex 8483 50 80	20	Pulley blocks of non-cast steel: — made of structural carbon steel complying with standard JIS G4051,	0 %	p/st	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			<ul style="list-style-type: none"> — with an external diameter of 114 mm or more but not more than 118 mm, — with an internal diameter of 33 mm or more but not more than 37 mm, — with a width of 29 mm or more but not more than 33 mm, — with a weight of 0,6 kg or more but not more than 0,9 kg, — with 6 trapezoidal grooves 			
0.8130	ex 8501 62 00	40	<p>AC, 3-phase generator, with:</p> <ul style="list-style-type: none"> — a continuous power of 147 kVA or more but not more than 222 kVA, — a continuous torque of 650 Nm or more but not more than 900 Nm, — a maximum working speed of 2700 revolutions per minute (rpm), — a liquid cooled system, — a length of 100 mm or more but not more than 200 mm, — a width of 550 mm or more but not more than 650 mm, — a height of 550 mm or more but not more than 650 mm, — weighing of not more than 150 kg 	0 %	-	31.12.2025
0.8095	ex 8505 90 90	20	<p>Electromagnetic clutch coil in a cylindrical metal housing:</p> <ul style="list-style-type: none"> — the metal housing is made of hot-rolled steel complying with standard JIS G 3131 - SPHE, — the coil is made of copper wire, — with a weight of 0,4 kg or more but not more than 0,7 kg, — with a width of 22 mm or more but not more than 25 mm, — with a plate reinforced to the coil (coil backplate) with an internal diameter of 44 mm or more but not more than 46 mm, — with an external diameter of 88 mm or more but not more than 96 mm, — without plunger, — with one connector 	0 %	p/st	31.12.2025
0.8115	ex 8507 60 00	48	<p>Integrated battery system in a metal case with holders, consisting of:</p> <ul style="list-style-type: none"> — a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy of 0,6 kWh, — Battery Management System, — a power relay, — a cooling system, — four connectors, <p>for use in the manufacture of Mild-hybrid (mHEV) motor vehicles (1)</p>	1.3 %	-	31.12.2021
0.8140	ex 8529 90 92	73	<p>CMOS-Image sensor</p> <ul style="list-style-type: none"> — with a micro lens on every pixel (micro lens coverage at least 99 % of all pixel), — to capture infra-red light reflected from objects, <p>in order to capture depth images in the cameras built for</p>	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			distance measurements (Time-of-Flight)			
0.8085	ex 8537 10 91	45	Main hybrid system controller, diagnosing and controlling the elements of the hybrid propulsion system, with: <ul style="list-style-type: none"> — a programmable memory, — a microprocessor, — at least one composite connector, — a voltage of 24 V, — with a length of 350 mm or more but not more than 400 mm, — with a width of 200 mm or more but not more than 250 mm, — with a height of 80 mm or more but not more than 120 mm, — in a metal housing 	0 %	-	31.12.2025
0.8132	ex 8537 10 98	80	Propulsion Control System with at least: <ul style="list-style-type: none"> — a DC/AC inverter, — a power of 190 kW or more but not more than 220 kW, — a high voltage circuits with AC and DC interfaces for connecting a traction motor, generator and energy storage system, — an integral control of all drive motor and generator traction system functions, — a CAN communications interface with System Control Unit, — a liquid cooled system, — a length of 300 mm or more but not more than 950 mm, — a width of 350 mm or more but not more than 600 mm, — a height of 200 mm or more but not more than 350 mm, — a weight of 40 kg or more but not more than 90 kg 	0 %	p/st	31.12.2025
0.8124	ex 8537 10 98	88	Control panel for car radio and/or navigation control with: <ul style="list-style-type: none"> — electronic passive components, — at least two switches, — LEDs, — at least one connector, — whether or not warning triangle switch, — for a voltage not exceeding 16 V, for use in the manufacture of goods of Chapter 87 ⁽¹⁾	0 %	-	31.12.2025
0.8127	ex 8708 99 97	28	A set of Type 4 H2 cylinders, in accordance with the EC 79 standard, consisting of two to eight cylinders on aluminum frames: <ul style="list-style-type: none"> — cylinders made of high density polyethylene (HDPE) composite reinforced with a braid of glass and carbon fibers in epoxy resin, — with an operating pressure of not less than 35 MPa, — with a durability declared by the manufacturer of not less than 20 years, — with a cylinder capacity of 180 liters or more but not more than 375 liters, — equipped with a set of solenoid, manual and safety PRD valves, — with a total width of 1 800 mm or more but not more than 2 300 mm, 	0 %	-	31.12.2025

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Date foreseen for mandatory review
			<ul style="list-style-type: none"> — with a total height of 400 mm or more but not more than 500 mm, — with a total length of 1 200 mm or more but not more than 3 600 mm 			
0.8128	ex 8708 99 97	38	<p>A set of Compressed Natural Gas (CNG) cylinders type CNG-4, in accordance with the ECE R110 standard, consisting of four or five cylinders on aluminum frames:</p> <ul style="list-style-type: none"> — made of high density polyethylene (HDPE) composite reinforced with a braid of glass and carbon fibers in epoxy resin, — with an operating pressure of not less than 20 MPa, — with a shelf life declared by the manufacturer of not less than 20 years, — with a cylinder capacity of 315 liters or more but not more than 375 liters, — equipped with a set of solenoid, manual and safety PRD valves, — with a total width of 2 200 mm or more but not more than 2 300 mm, — with a total height of 450 mm or more but not more than 460 mm, — with a total length of 3 500 mm or more but not more than 3 600 mm 	0 %	-	31.12.2025'

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)'
