



Brussels, 28 May 2025  
(OR. en)

9433/25  
ADD 1

ENER 165  
ENV 408

## COVER NOTE

From:	European Commission
date of receipt:	23 May 2025
To:	General Secretariat of the Council
No. Cion doc.:	D/105469/03 ANNEX
Subject:	ANNEX to the COMMISSION REGULATION (EU) .../... amending Commission Regulation (EU) 2023/826 to clarify definitions and some aspects of the measurement conditions and amending Commission Regulation (EU) 2023/2533 in relation to the methodology for calculating the average final moisture content, the identification and availability of spare parts and of repair information among other aspects

Delegations will find attached document D/105469/03 ANNEX.

Encl.: D/105469/03 ANNEX



EUROPEAN  
COMMISSION

Brussels, XXX  
D105469/03  
[...] (2025) XXX draft

ANNEX

ANNEX

to the

COMMISSION REGULATION (EU) .../...

**amending Commission Regulation (EU) 2023/826 to clarify definitions and some aspects of the measurement conditions and amending Commission Regulation (EU) 2023/2533 in relation to the methodology for calculating the average final moisture content, the identification and availability of spare parts and of repair information among other aspects**

## ANNEX

(1) Regulation (EU) 2023/826 is amended as follows:

(a) Annex I is amended as follows:

(i) the definition of ‘motor-operated building element’ under point 21 is replaced by the following:

‘21. ‘Motor-operated building element’ means opening or comfort equipment for use in buildings or related structures, excluding ventilation equipment, that can move or rotate, or both, by using input from the mains power source. The motor-operated building element incorporates an electric motor or an actuator and a control unit, and is operated by the end-user through cabled and/or wireless control(s), via a network, or controlled automatically with the use of sensors;’;

(ii) the following definition is inserted after point 21:

‘22. ‘Control unit’ means a unit that receives signals from the end-user through cabled and/or wireless control(s), via a network, or from sensors, and enables the required operation of the motor or actuator of the motor-operated building element. Sensors connected to the unit and receiving power from the same mains input point as the rest of motor-operated building element are considered part of the control unit;’;

(b) In Annex II, point 1), the eighth indent is replaced by the following:

‘- grinders used in the kitchen for the processing of food;’;

(c) Annex IV is amended as follows:

(i) the following paragraph is inserted after the first paragraph:

‘For all types of household coffee machines, the measurement shall be performed after completion of the last brewing cycle, or, where applicable, after completion of a descaling process, a self-cleaning process or any operation performed by the user, unless an alarm has been triggered requiring user intervention to prevent any possible damage or accident.’;

(ii) in point (c), the first sentence is replaced by ‘The following procedure shall be used for measuring energy consumption in networked standby for the energy efficiency requirements of Annex III point 1(c), and for testing the power management function:’;

(iii) point (d) is deleted.

(2) Regulation (EU) 2023/2533 is amended as follows:

(a) Annex I is amended as follows:

(i) points (10) and (11) are replaced by the following:

‘(10) ‘off mode’ means a condition where the household tumble dryer is connected to the mains power source and is not providing any function, or it is in a condition providing only:

(a) an indication of off mode condition;

- (b) functionalities intended to ensure electromagnetic compatibility under Directive 2014/30/EU of the European Parliament and of the Council<sup>1</sup>;
- (11) ‘standby mode’ means a condition where the household tumble dryer is connected to the mains power source, depends on energy input from the mains power source to work as intended and provides only one or more of the following functions, which may persist for an indefinite time:
  - (a) reactivation function;
  - (b) reactivation function and only an indication of enabled reactivation function;
  - (c) information or status display;’;
- (ii) the following points are added:
  - ‘(19) ‘average final moisture content’ means the average amount of moisture contained in the load at the end of the drying cycles for the eco programme at full and at half load;
  - (20) ‘reactivation function’ means a function that via a remote switch, a remote control, an internal sensor or timer provides a switch from standby mode to another mode, including active mode, providing additional functions;
  - (21) ‘information or status display’ means a continuous function providing information or indicating the status of the equipment on a display, including clocks. A simple light indicator is not considered a status display;
  - (22) ‘active mode’ means a condition in which the equipment is connected to the mains power source and at least one of the main functions has been activated;
  - (23) ‘main function’ means a function delivering the main service(s) for which the equipment is designed, tested and marketed, and which corresponds to the intended use of the equipment;
  - (24) ‘commercially available tool’ means a tool that is available for purchase by the general public and is neither a basic tool nor a proprietary tool;
  - (25) ‘basic tool’ means a screwdriver for slotted heads, a screwdriver for cross recess screws, a screwdriver for hexalobular recess heads, a hexagon socket key, a combination wrench, combination pliers, combination pliers for wire stripping and terminal crimping, half round nose pliers, diagonal cutters, multigrip pliers, locking pliers, a prying lever, tweezers, magnifying glass, a spudger and a pick;

---

<sup>1</sup> Directive 2014/30/EU of the European Parliament and of the Council of 26 February 2014 on the harmonisation of the laws of the Member States relating to electromagnetic compatibility (OJ L 96, 29.3.2014, p. 79).

- (26) 'proprietary tool' means a tool that is not available for purchase by the general public or for which any applicable patents are not available to licence under fair, reasonable and non-discriminatory terms.';
- (b) Annex II is amended as follows:
- (i) point 5 is amended as follows
- (1) point (1) is amended as follows:
- point (a) is amended as follows:
    - item (iii) is replaced by the following:  
'(iii) water pump;';
    - item (v) is replaced by the following:  
'(v) transmissions between motor and drum, such as the drum belt;';
    - item (vii) is replaced by the following:  
'(vii) drums and drum bearings;';
    - the following item is added:  
'(xx) motor capacitor;';
  - point (b) is replaced by the following:  
'(b) availability of spare parts referred to in point (a) shall be ensured for a minimum period starting at the latest on 1 July 2025 or two years after the placing on the market of the first unit of the model, whichever is the later date, and ending at least 10 years after placing on the market the last unit of the model concerned. For that purpose, the list of spare parts and the procedure for ordering them shall be publicly available on the free access website of the manufacturer, importer or authorised representative, at least during the same period and starting at the date referred to in this point;';
  - point (e) is replaced by the following:  
'(e) manufacturers, importers or authorised representatives of household tumble dryers shall ensure that the spare parts referred to in points (a) and (c) can be replaced without tools or with the use of tools that are not proprietary tools, and without permanent damage to the household tumble dryer;'
- (2) in point (6), point (a) is replaced by the following:
- '(a) manufacturers, importers or authorised representatives shall ensure that household tumble dryers are designed in such a way that the materials and components referred to in Annex VII to Directive 2012/19/EU of the

European Parliament and of the Council<sup>2</sup> can be removed from the appliance without tools or with the use of tools that are not proprietary tools;’;

(ii) in point 6, point (2) is replaced by the following:

‘(2) Values for the following parameters:

- (a) capacity in kg;
- (b) programme duration, expressed in hours and minutes;
- (c) electricity, and where applicable, gas consumption in kWh/drying cycle;
- (d) acoustic airborne noise emission of the drying cycle.

For the eco programme, the values of the parameters under points (a) to (c), shall be provided both at full load and at partial load; the value for the parameter under point (d) shall be provided only at full load.

For programmes other than the eco programme, when they are available, indicative values shall be provided as follows:

- (a) for synthetics dry programme, values for parameters under points (a) to (c) shall be provided at full load;
- (b) for delicates/wool drying programme, values for the parameters under points (a) to (c) shall be provided at full load;
- (c) for synthetics extra/very dry programme, values for the parameters under points (a) to (c) shall be provided at full load;
- (d) for synthetics iron dry programme, values for the parameters under points (a) to (c) shall be provided at full load;
- (e) for cotton extra/very dry programme, values for the parameters under points (a) to (c) shall be provided both at full load and at partial load;
- (f) for cotton iron dry programme, values for the parameters under points (a) to (c) shall be provided both at full load and at partial load;’;

(c) Annex III is amended as follows:

(i) in the introductory part, the third and the fourth paragraphs are replaced by the following:

‘The eco programme as identifiable on the programme selection, on the display and through the network connection, depending on the functionalities provided by the household tumble dryer, and with no

---

<sup>2</sup> Directive 2012/19/EU of the European Parliament and of the Council of 4 July 2012 on waste electrical and electronic equipment (OJ L 197 24.07.2012 p.38-71)

further modification of the final moisture content setting, shall be used for the measurement and calculation of the EEI, the condensation efficiency, the programme duration and the airborne acoustic noise emissions. The energy consumption, condensation efficiency and programme duration shall be measured concurrently.

The calculation of the weighted energy consumption, the weighted programme duration and the condensation efficiency shall be done on the basis of three drying cycles at full load and four drying cycles at partial load.’;

- (ii) in point 1, point (f) on the calculation of the average final moisture content is deleted;
- (d) Annex IV is amended as follows:
  - (i) points 1 and 2 are replaced by the following:
    - ‘1. The verification tolerances set out in Table 2 relate only to the verification of the declared values by Member State authorities and shall not be used by the manufacturer, importer or authorised representatives as an allowed tolerance to establish those values in the technical documentation or in interpreting these values with a view to achieving compliance or to communicate better performance by any means.
    - 2. Where a model is not in conformity with the requirements laid down in Article 40 of Regulation (EU) 2024/1781, the model and all equivalent models shall be considered not compliant.’;
  - (ii) in point 3(b), point (v) is replaced by the following:
    - ‘(v) when the Member State authorities test the unit of the model, the determined values, that is to say the values of the relevant parameters as measured in testing and the values calculated from these measurements, comply with:
      - (a) the validity criteria set out in Table 1;
      - (b) the respective verification tolerances set out in Table 2.’;
  - (iii) point 7 is replaced by the following:
    - ‘7. The model shall be considered to comply with the applicable requirements where, for the three units referred to in point (5), the arithmetical mean of the determined values complies with the respective verification tolerances set out in Table 2.’;
  - (iv) point 11 is replaced by the following:
    - ‘11. The Member State authorities shall only apply the validity criteria set out in Table 1 and the verification tolerances set out in Table 2 and shall only use the procedure described in points (3) to (8) for the requirements referred to in this Annex. For the parameters in Table 1 and in Table 2 no other validity criteria or verification tolerances, such as those set out in harmonised standards or in any other measurement method, shall be applied.’;
  - (v) Table 1 is replaced by the following:
    - ‘

Table 1 - Validity criteria

Parameter	Validity criteria
Average final moisture content of the eco programme $\mu_t$	The determined value shall be measured and calculated and be lower than 1,5 %.

’;

vi) the following table is added:

‘

Table 2 - Verification tolerances

Parameter	Verification tolerances
$E_{dry}$ and $E_{dry^{1/2}}$	The determined value (*) shall not exceed the declared value of $E_{dry}$ and $E_{dry^{1/2}}$ by more than 6 %.
$E_{g_{dry}}$ and $E_{g_{dry^{1/2}}}$	The determined value (*) shall not exceed the declared value of $E_{g_{dry}}$ and $E_{g_{dry^{1/2}}}$ by more than 6 %.
$E_{g_{dry,a}}$ and $E_{g_{dry^{1/2},a}}$	The determined value (*) shall not exceed the declared value of $E_{g_{dry,a}}$ and $E_{g_{dry^{1/2},a}}$ by more than 6 %.
$C_t$	The determined value (*) shall not be less than the declared value of $C_t$ by more than 6 %.
$T_{dry}$ and $T_{dry^{1/2}}$	The determined value (*) shall not exceed the declared value of $T_{dry}$ and $T_{dry^{1/2}}$ by more than 6 %.
$P_o$	The determined value (*) of $P_o$ shall not exceed the declared value by more than 0,10 W.
$P_{sm}$	The determined value (*) of $P_{sm}$ shall not exceed the declared value by more than 10 % if the declared value is higher than 1,00 W, or by more than 0,10 W if the declared value is lower than or equal to 1,00 W.
$P_{ds}$	The determined value (*) of $P_{ds}$ shall not exceed the declared value by more than 10 % where the declared value is higher than 1,00 W, or by more than 0,10 W if the declared value is lower than or equal to 1,00 W.
Acoustic airborne noise emissions	The determined value (*) shall not exceed the declared value by more than 2 dB with respect to 1 pW.

\* Where three additional units are tested in accordance with point (5), the determined value means the arithmetical mean of the values determined for those three additional units.