



Brussels, 28 April 2026
(OR. en)

Interinstitutional File:
2026/0095 (NLE)

8660/26
ADD 1

UD 113

PROPOSAL

From: Secretary-General of the European Commission, signed by Ms Martine DEPREZ, Director

date of receipt: 27 April 2026

To: Ms Thérèse BLANCHET, Secretary-General of the Council of the European Union

No. Cion doc.: COM(2026) 176 annex

Subject: ANNEX to the Proposal for a COUNCIL REGULATION amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

Delegations will find attached document COM(2026) 176 annex.

Encl.: COM(2026) 176 annex



Brussels, 27.4.2026
COM(2026) 176 final

ANNEX

ANNEX

to the

Proposal for a COUNCIL REGULATION

amending Regulation (EU) 2021/2278 suspending the Common Customs Tariff duties referred to in Article 56(2), point (c), of Regulation (EU) No 952/2013 of the European Parliament and of the Council on certain agricultural and industrial products

ANNEX

The Annex is amended as follows:

- (1) the entries with the following serial numbers are deleted: 0.3341, 0.8865, 0.7594, 0.8425, 0.5110, 0.8425, 0.7540, 0.7541, 0.5495, 0.6802, 0.8795, 0.8877, 0.5987, 0.7056, 0.7056, 0.8668, 0.8669, 0.8680, 0.8675, 0.8647;
- (2) the following entries replace those entries that have the same serial numbers:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.4080	ex 1517 90 99	30	Microbial oil, refined, containing by weight: — 25 % or more but not more than 70 % arachidonic acid and no more than 5 % docosahexenoic acid — standardised with vegetable oil	0 %	-	31.12.2026
0.6144	ex 2835 10 00	50	Sodium hypophosphite (CAS RN 7681-53-0) with a purity by weight of 97 % or more or as aqueous solution containing by weight 55 % or more but not more than 65 % of sodium hypophosphite	0 %	-	31.12.2029
0.6482	ex 2841 70 00	50	Hexaammonium heptamolybdate, anhydrous (CAS RN 12027-67-7) or as tetrahydrate (CAS RN 12054-85-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.5936	ex 2841 90 70	20	Potassium titanium oxide (CAS RN 12056-51-8) in powder form with a purity of 99 % or more	0 %	-	31.12.2029
0.7097	ex 2842 10 00	60	Aluminosilicate (CAS RN 1318-02-1) with — a purity by weight of 94 % or more, — a zeolite structure of aluminophosphate-eighteen (AEI), and — a phase purity of 90 % or more for use in the manufacture of copper zeolite or washcoat used in the automotive catalyst production ⁽¹⁾	0 %	-	31.12.2026
0.4529	ex 2903 99 80	28	Fluorobenzene (CAS RN 462-06-6) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.6560	ex 2904 99 00	78	1-Chloro-2-nitrobenzene (CAS RN 88-73-3) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.6257	ex 2906 19 00	80	4- <i>tert</i> -Butylcyclohexanol (CAS RN 98-52-2) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.5503	ex 2909 30 39	20	1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2)	0 %	-	31.12.2026
0.6649	ex 2909 30 39	30	1,1'-(1-Methylethylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)]-benzene (CAS RN 97416-84-7)	0 %	-	31.12.2030
0.7828	ex 2909 30 39	50	2-(1-Adamantyl)-4-Bromoanisole (CAS RN 104224-63-7) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.4274	ex 2914 19 90	80	3-Methylbutanone (CAS RN 563-80-4) with a purity by weight of 97 % or more	0 %	-	31.12.2027
0.4227	ex 2914 39 00	35	Benzophenone (CAS RN 119-61-9) with a purity by weight of 99 % or more	0 %	-	31.12.2027

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.7407	ex 2915 90 90	20	Methyl (R)-2-fluoropropionate (CAS RN 146805-74-5)	0 %	-	31.12.2027
0.7542	ex 2915 90 90	25	Methyl octanoate (CAS RN 111-11-5), methyl decanoate (CAS RN 110-42-9) or methyl myristate (CAS RN 124-10-7)	0 %	-	31.12.2029
0.6003	ex 2915 90 90	27	Triethyl orthoformate (CAS RN 122-51-0) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.5767	ex 2915 90 90	30	3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5)	0 %	-	31.12.2027
0.8154	ex 2915 90 90	33	Ethyl 8-bromooctanoate (CAS RN 29823-21-0) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.8423	ex 2915 90 90	43	Trifluoroacetic anhydride (CAS RN 407-25-0) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.6255	ex 2915 90 90	45	Trimethyl orthoformate (CAS RN 149-73-5)	0 %	-	31.12.2029
0.8457	ex 2915 90 90	53	3-Chloro-2,2-dimethylpropanoyl chloride (CAS RN 4300-97-4) with a purity by weight of 98 % or more	0 %	-	31.12.2027
0.4954	ex 2915 90 90	60	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)	0 %	-	31.12.2030
0.3638	ex 2918 29 00	85	Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.3978	ex 2921 42 00	38	2-Nitroaniline (CAS RN 88-74-4) with a purity by weight of 99 % or more	0 %	-	31.12.2029
0.2609	ex 2921 45 00	15	<i>N</i> -1-Naphthylaniline (CAS RN 90-30-2) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.4160	ex 2924 19 00	58	<i>N,N</i> -Dimethylacrylamide (CAS RN 2680-03-7) with a purity by weight of 97 % or more	0 %	-	31.12.2026
0.6266	ex 2924 29 70	59	2-(Trifluoromethyl)benzamide (CAS RN 360-64-5) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.3526	ex 2925 11 00	40	1,2-Benzisothiazol-3(2 <i>H</i>)-one 1,1-dioxide (CAS RN 81-07-2) or its sodium salt (CAS RN 128-44-9) or its sodium salt dihydrate (CAS RN 6155-57-3) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.2661	ex 2928 00 90	73	3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide (CAS RN 32687-78-8) with a purity by weight of 97 % or more	0 %	-	31.12.2029
0.5918	ex 2928 00 90	78	Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1) with a purity by weight of 99 % or more	0 %	-	31.12.2029

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.8701	ex 2929 90 90	80	Wet paste or powder — with a content by weight of <i>N,N'</i> -[(2 <i>S</i> ,3 <i>E</i> ,5 <i>S</i>)-1,6-diphenylhex-3-ene-2,5-diyl]bis(<i>N,N</i> -dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 70 % or more, — with a content by weight of water of not more than 30 % — and with a dry weight purity of <i>N,N'</i> -[(2 <i>S</i> ,3 <i>E</i> ,5 <i>S</i>)-1,6-diphenylhex-3-ene-2,5-diyl]bis(<i>N,N</i> -dimethylsulfuric diamide) (CAS RN 1247119-27-2) of 90 % or more	0 %	-	31.12.2029
0.7464	ex 2933 69 80	48	2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) with a purity by weight of 98 % or more	0 %	-	31.12.2029
0.8054	ex 2933 99 80	76	2-Methylindoline (CAS RN 6872-06-6) with a purity by weight of 98 % or more	0 %	-	31.12.2026
0.4942	ex 2934 99 90	47	2,4-Diethyl-9 <i>H</i> -thioxanthen-9-one (CAS RN 82799-44-8) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8830	ex 3809 91 00	30	Aqueous antimony pentoxide mixture containing by weight: — 46 % or more but not more than 55 % of antimony pentoxide (CAS RN 1314-60-9), and — 1 % or more but not more than 10 % of triethanolamine (CAS RN 102-71-6), or — 1 % or more but not more than 10 % of triethanolamine phosphate (CAS RN 10017-56-8)	0 %	-	31.12.2029
0.3448	ex 3811 21 00 ex 3811 90 00	38 60	Solution of mineral oils (CAS RN 64742-52-5, 64742-53-6, 64742-56-9 or blends thereof) containing by weight: — 25 % or more but not more than 55 % of the barium, calcium, magnesium or zinc salt of dinonylnaphthylsulphonic acid (CAS RN 25619-56-1, 28015-99-8, 28016-00-4, or 57855-77-3) — whether or not, not more than 25 % of the barium, calcium, magnesium or zinc salt of a mixture of C3-C24 carboxylic acids (CAS RN 68990-37-4)	0 %	-	31.12.2029
0.2800	ex 3815 12 00	50	Catalyst in the form of granules, wheels or ring-shaped structures — of a diameter of 3 mm or more, but not exceeding 10 mm, — containing 8 % or more but not more than 40 % by weight of silver — on a carrier based on aluminium oxide, — with one or more promoters	0 %	-	31.12.2029
0.2783	ex 3815 90 90	60	Dinonylnaphthalenedisulfonic acid (CAS RN 60223-95-2) with a content by weight of 50 % or more but not more than 65 %, in the form of a solution in isobutanol (CAS RN 78-83-1)	0 %	-	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.6672	ex 3906 90 90	28	Mixture containing by weight: — 80 % or more but not more than 90 % of a core shell polymer of butyl acrylate, ethyl acrylate, methyl-acrylate and allyl methacrylate (CAS RN 73026-23-0) and — 10 % or more but not more than 20 % of a copolymer of methyl methacrylate and ethyl acrylate (CAS RN 9010-88-2)	0 %	-	31.12.2030
0.5507	ex 3919 90 80	58	Biaxially-oriented film of poly(methyl methacrylate), with a thickness of 20 µm or more but not more than 90 µm, covered on one side with an adhesive layer and a release sheet	0 %	-	31.12.2029
0.7949	ex 3920 61 00	40	Extruded thermoplastic foils or films of polycarbonate with: — matt surface texture on both sides — a thickness of more than 50 µm but not more than 200 µm, — a width of 800 mm or more, but not more than 1 500 mm, and — a length of 300 m or more, but not more 2500 m for use in the production of retroreflective products ⁽¹⁾	0 %	-	31.12.2030
0.7196	ex 3926 90 97	77	Silicone decoupling ring with an inner diameter of 13,2 mm or more but no more than 17,2 mm, in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems	0 %	p/st	31.12.2026
0.8024	ex 5911 40 00	10	Non-wovens, consisting of poly(ethylene terephthalate) spun bonded media: — in the piece, cut to length or simply cut to rectangular (including square) shape, — of weight of 160 g/m ² or more but not more than 300 g/m ² , — with a filtration efficiency of class L or better (according to DIN 60335-2-69), — pleatable, with or without following treatments: — a coating or covering with polytetrafluoroethylene (PTFE), — a coating with aluminium particles, — a coating of phosphorous based flame retardants, — a nano fiber coating of a polyamide, a polyurethane or a fluorine-containing polymer — an expanded polytetrafluoroethylene (ePTFE) membrane	0 %	m ²	31.12.2029
0.5024	ex 8301 60 00 ex 8419 90 85 ex 8479 90 70 ex 8481 90 00 ex 8485 90 90 ex 8503 00 98 ex 8515 90 80 ex 8537 10 98 ex 8538 90 99 ex 8708 99 10 ex 8708 99 97	30 40 30 50 30 43 40 55 70 55 22	Silicone or plastic keyboards, comprising: — parts of common metal, and — whether or not comprising parts of plastic, — epoxy resin reinforced with fiberglass or wood, — whether or not printed or surface-treated, — with or without electrical conductors, — with or without a membrane bonded to the keyboard, — with or without mono or multilayer protective film	0 %	p/st	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.8818	ex 8406 81 00	10	Industrial steam turbine with: — an output of more than 40 MW but not more than 90 MW, — designed for a pressure of not more than 165 bar and a temperature of not more than 565 °C, — equipped with individually controlled single or double seat valves on the live steam side which are operated with a hydraulic servo of not more than 30 bar	0 %	-	31.12.2029
0.8148	ex 8412 90 70	20	Bedplate made of solution strengthened ductile iron castings (SSDI), for anchoring and aligning the drive train (gearbox, pedestal bearing, rotor shaft) of a wind turbine with: — a length of 3,5 m or more but not more than 4,5 m, — a width of 2 m or more but not more than 4,2 m, — a height of 1 m or more, but not more than 1,3 m, — a weight of 11 tons or more but not more than 21,5 tons, — mounting bores for yawdrive, — a mounting flange for gearbox support, — drivetrain mount, — different screw sockets	0 %	p/st	31.12.2027
0.8856	ex 8418 99 90	80	An evaporator being a type of heat exchanger, consisting of aluminium pipes with copper ends enclosed with aluminium radiators: — measuring 337 x 237 x 17 mm or more, but not more than 868 x 399 x 78 mm, — with a total weight of a set of 236 g or more, but not more than 1 750 g, — with a fixed sensor, — with or without noise absorber, — with 2, 5 or 7 control and power connection pins terminated with sensor temperature type of socket, with or without heater and fuse type of socket, for use in the manufacture of products of subheadings 8418 10, 8418 21, 8418 40 (1)	0 %	-	31.12.2029
0.4855	ex 8501 33 90 ex 8501 40 80 ex 8501 53 50	30 50 10	Electric drive for motor vehicles, with an output of not more than 315 kW: — with an AC or DC motor with or without transmission, — with or without power electronics	0 %	-	31.12.2026
0.4450	ex 8504 31 80	30	Transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters and goods of heading 8537 (1)	0 %	-	31.12.2029
0.8660	ex 8507 60 00	26	Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: — a length of 670 mm or more, but not more than 882 mm, — a width of 390 mm or more, but not more than 655 mm, — a height of 110 mm or more, but not more than 155 mm, — a weight of 60 kg or more, but not more than 165 kg, and — a power of 11 300 Wh or more, but not more than 29 360 Wh	1.3 %	-	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.6753	ex 8507 60 00	77	Lithium-ion rechargeable batteries, with: — a length of 700 mm or more, but not more than 2 820 mm, — a width of 935 mm or more, but not more than 1 660 mm, — a height of 85 mm or more, but not more than 700 mm, — a weight of 250 kg or more, but not more than 700 kg, — a power of not more than 175 kWh, — a nominal voltage of 320 V or more, but not more than 430 V for use in the manufacture of vehicles of subheadings 8701 to 8705 (1)	1.3 %	-	31.12.2026
0.8841	ex 8537 10 91	75	Printed circuit board equipped with a microcontroller for operating and/or control purposes — with or without operating components, signal components and display, — for operating voltages of 5V DC or more but not more than 24V DC or 220V AC or more but not more than 400V AC, — with or without housing for use in the manufacture of household appliances of subheadings 7321 11, 8414 60, 8418 10, 8418 21, 8418 29, 8418 40, 8422 11, 8450 11, 8450 12, 8450 19, 8450 20, 8451 21, 8451 29, 8516 60 (1)	0 %	-	31.12.2029
0.6377	ex 8544 30 00 ex 8544 42 90	53 75	Electrical wiring harness or cable for the steering system: — with a rated voltage of 12 V, — fitted with connectors on both ends or/and with special adapter providing sealing and anti-rotation feature, — with or without plastic anchoring jaws for mounting the steering gear housing of motor vehicles, for use in the manufacture of power steering systems for motor vehicles (1)	0 %	p/st	31.12.2029
0.8292	ex 8708 95 99	50	Airbag inflator containing pyrotechnics, whether or not cold gas, as propellant for safety airbags of vehicles, in each individual consignment of 1 000 pieces or more	0 %	p/st	31.12.2026
0.6572	ex 9002 11 00	85	Lens with — a horizontal field of view of 20° or more, but not more than 220°, — a focal length of 1.16 mm or more, but not more than 20 mm, — a relative aperture of f/1.2 or more, but not more than f/4, and — a diameter of 5 mm or more, but not more than 40 mm, for use in the manufacture of CMOS vehicle-mounted cameras or IP network cameras (1)	0 %	-	31.12.2029

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.;

(3) the following entries are inserted according to the numerical order of the CN and TARIC codes in the second and third columns:

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9085	ex 1515 60 99	20	Microbial oil, refined or semi-refined, but not chemically modified, containing by weight in the form of triglycerides: — 35 % or more but not more than 70 % of arachidonic acid — not more than 3 % by weight of docosahexaenoic acid	0 %	-	31.12.2030
0.9064	ex 2904 99 00	75	Trifluoromethanesulfonic acid (CAS RN 1493-13-6) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9088	ex 2905 29 90	50	Prop-2-yn-1-ol (CAS RN 107-19-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9071	ex 2921 43 00	45	α,α,α -Trifluoro- <i>o</i> -toluidine (CAS RN 88-17-5) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9016	ex 2922 29 00	53	<i>m</i> -Anisidine (CAS RN 536-90-3) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9012	ex 2924 29 70	44	4-(2,2-Diethoxyacetyl)-3,5-difluoro- <i>N</i> -methylbenzamide (CAS RN 3089027-90-4) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9010	ex 2928 00 90	68	Ethyl hydrazinoacetate hydrochloride (CAS RN 6945-92-2) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9006	ex 2930 90 95	22	4,4,5,5,5-Pentafluoropentyl carbamimidothioate—methanesulfonate (1:1) (CAS RN 1107606-68-7) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9011	ex 2930 90 95	24	Trimethyloxosulfonium chloride (CAS RN 5034-06-0) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9004	ex 2931 90 00	21	(2-Fluoro-4-phenoxyphenyl)boronic acid (CAS RN 1414356-30-1) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9013	ex 2932 19 00	38	(2,2-Diphenyltetrahydrofuran-3-yl)methanol (CAS RN 93651-75-3) with a purity by weight of 98 % or more	0 %	-	31.12.2030
0.9015	ex 2933 19 90	78	3-(3-Methyl-5-oxo-4,5-dihydro-1 <i>H</i> -pyrazol-1-yl)benzenesulfonic acid (CAS RN 119-17-5) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9075	ex 2933 19 90	83	Isomeric mixture containing by weight 97 % or more of the two isomers — 2-(3,4-Dimethyl-1 <i>H</i> -pyrazol-1-yl)succinic acid and — 2-(4,5-Dimethyl-1 <i>H</i> -pyrazol-1-yl)succinic acid (CAS RN 2241455-89-8)	0 %	-	31.12.2030
0.9008	ex 2933 39 99	19	5-Chloro-1-(4-piperidyl)-1 <i>H</i> -benzimidazol-2(3 <i>H</i>)-one (CAS RN 53786-28-0) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9060	ex 2933 39 99	94	Cyantraniliprole (ISO) (CAS RN 736994-63-1) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.8997	ex 2933 59 95	35	3-Iodo-1 <i>H</i> -pyrazolo[3,4- <i>d</i>]pyrimidin-4-amine (CAS RN 151266-23-8) with a purity by weight of 98 % or more	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9061	ex 2933 59 95	40	Pirimiphos-methyl (ISO) (CAS RN 29232-93-7) with a purity by weight of 90 % or more	0 %	-	31.12.2030
0.9058	ex 2933 69 80	38	Tris([1,1'-biphenyl]-4-yl)-1,3,5-triazine (CAS RN 31274-51-8) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.9009	ex 2933 99 80	83	1-(3-Chloropropyl)-1,3-dihydro-2H-benzimidazol-2-one (CAS RN 62780-89-6) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8994	ex 2933 99 80	84	Allyl (2S,4S)-4-benzoylsulfanyl-2-(dimethylcarbamoyl)pyrrolidine-1-carboxylate (CAS RN 141818-73-7) with a purity by weight of 96 % or more	0 %	-	31.12.2030
0.8996	ex 2934 99 90	32	(6R,7R)-Benzhydryl 3-hydroxy-8-oxo-7-(2-phenylacetamido)-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylate (CAS RN 54639-48-4) with a purity by weight of 95 % or more	0 %	-	31.12.2030
0.9005	ex 2934 99 90	34	Benzyl 4-(oxetan-3-yl)piperazine-1-carboxylate (CAS RN 1254115-22-4) with a purity by weight of 99 % or more	0 %	-	31.12.2030
0.9007	ex 2934 99 90	36	Nadide phosphate (INNM) disodium salt (CAS RN 24292-60-2) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.8993	ex 2934 99 90	46	(6R-trans)-7-Amino-8-oxo-3-[[[(1,2,5,6-tetrahydro-2-methyl-5,6-dioxo-1,2,4-triazin-3-yl)thio]methyl]-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 58909-56-1) with a purity by weight of 97 % or more	0 %	-	31.12.2030
0.9056	ex 3204 17 00	32	Colourant C.I. Pigment Violet 23 (CAS RN 215247-95-3) and preparations based thereon with a colourant C.I. Pigment Violet 23 content of 70 % or more by weight	0 %	-	31.12.2030
0.9074	ex 3810 10 00	10	Tin or zinc based, halide free, surface mount technology processing solder paste: — with metal contents of 87,5 % or more, but not more than 90,1 % by weight, — with an alloy solidus temperature of 210°C or more, — with a viscosity of 178 Pa·s or more, but not more than 235 Pa·s, — with a particle size of 40 µm or less, — with a silver content either of 3,15 % or more, but not more than 3,5 % by weight for tin based paste or of 0,25 % or more, but not more than 0,28 % by weight for zinc based paste, — with or without bismuth content of 2,55 % or more, but not more than 2,71 % by weight, — with or without copper content of 0,6 % or more, but not more than 0,7 % by weight	0 %	-	31.12.2030
0.9073	ex 3815 12 00	40	Catalyst used to obtain paraxylene and orthoxylene by isomerization of methaxylene containing by weight: — 60 % or more but not more than 95 % of aluminum oxide (CAS RN 1344-28-1), — 5 % or more but not more than 15 % of aluminosilicate (CAS RN 1327-36-2), — not more than 2 % of platinum (CAS RN 7440-06-4), — not more than 2 % aluminum chloride hydroxide (CAS RN 12042-91-0), — not more than 0,2 % of hydrogen sulfide (CAS RN 7783-06-4)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9086	ex 3815 19 90	33	Catalyst, in powder form, consisting of a mixture of metal oxides fixed to a silicon dioxide support, with a total content by weight of molybdenum, bismuth and iron of 20 % or more but not more than 50 %, for use in the manufacture of acrylonitrile (1)	0 %	-	31.12.2030
0.9062	ex 3824 99 96	38	Low outgassing thermally conductive silicone paste: — with thermal conductivity when cured of 3,45 W/(m·K) or more but not more than 3,55 W/(m·K), — with continuous use temperature minimum range from -60 °C to 200 °C, — with heat capacity when cured of 0,75 J/g·K or more but not more than 0,85 J/g·K, — with volume resistivity when cured of 1010 Ω·m or more, — packaged in containers of 30 kg or more	0 %	-	31.12.2030
0.8999	ex 3902 90 90	63	Hydrogenated poly(1-octene) (CAS RN 70693-43-5)	0 %	-	31.12.2030
0.9078	ex 3907 29 20	63	Preparation containing by weight — 5 % or more but not more than 15 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6) and — 85 % or more but not more than 95 % of oxirane, 2-methyl-, polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5)	0 %	-	31.12.2030
0.9079	ex 3907 29 20	65	Preparation containing by weight — 40 % or more but not more than 60 % of oxirane, 2-methyl-, polymer with oxirane, ether with 2,2-[[3-methyl-4-[(4-methyl-2-benzothiazolyl)azo]phenyl]imino]bis[ethanol] (2:1) (CAS RN 229306-55-2) and — 40 % or more but not more than 60 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9077	ex 3907 29 20	68	Preparation containing by weight — 90 % or more but not more than 99 % of oxirane, 2-methyl-, polymer with oxirane, ether with ethyl 3-(4-(bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3) and — 1 % or more but not more than 10 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9081	ex 3907 29 20	70	Preparation containing by weight — 50 % or more but not more than 70 % of oxirane, methyl-polymer with oxirane, ether with bis(4-[bis(2-hydroxyethyl)amino]phenyl) (2-sulfophenyl)methyl (4:1), monosodium salt block (CAS RN 126042-89-5) and — 30 % or more but not more than 50 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9082	ex 3907 29 20	73	Preparation containing by weight of — 23 % or more but not more than 36 % of oxirane, 2-methyl-,polymer with oxirane, ether with bis(4-(bis(2-hydroxyethyl)amino)phenyl)(2-sulfophenyl)methyl (4:1), monosodium salt, block (CAS RN 126042-89-5), — 4 % or more but not more than 20 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6), — 25 % or more but not more than 30 % of oxirane, 2-methyl-,polymer with oxirane, ether with 2,2'-((3-methyl-4-((4-methyl-2-benzothiazolyl)azo)phenyl)imino)bis(ethanol)(2:1) (CAS RN 229306-55-2), — 5 % or more but not more than 10 % of oxirane, 2-methyl-,polymer with oxirane, ether with 5-(2-(4-(bis(2-hydroxyethyl)amino)-2-methylphenyl)diazanyl)-3-methyl-2,4-thiophenedicarbonitrile (2:1) (CAS RN 515857-23-5) and — 15 % or more but not more than 25 % of oxirane, 2-methyl-,polymer with oxirane, ether with ethyl 3-(4-bis(2-hydroxyethyl)amino)phenyl)-2-cyano-2-propenoate (2:1) (CAS RN 152286-82-3)	0 %	-	31.12.2030
0.9080	ex 3907 29 20	75	Preparation containing by weight — 60 % or more but not more than 80 % of Oxirane, 2-methyl-,polymer with oxirane, ether with 2,2',2'',2'''-(sulfonylbis(4,1-phenylene)-2,1-diazenediyl(3-methyl-4,1-phenylene)nitrilo))tetrakis(ethanol) (4:1) (CAS RN 927432-39-1) and — 20 % or more but not more than 40 % of polyethylene-polypropylene glycol (CAS RN 9003-11-6)	0 %	-	31.12.2030
0.9001	ex 3919 90 80	57	Self-adhesive polycarbonate film, printed, whether or not arched, with: — a thickness of 0,3 mm or more, but not more than 0,4 mm, — minimum dimensions of 63 mm x 15 mm, — maximum dimensions of 278 mm x 117 mm, — a weight of not more than 5 g per piece, intended for integration into combined instrument panels of passenger cars	0 %	-	31.12.2030
0.9057	ex 3920 62 19	70	Poly(ethylene terephthalate) film in rolls with: — a thickness of 35 µm or more, but not more than 75 µm, — a tensile strength of 40 MPa or more in the machine direction (MD) and 200 MPa or more in the transverse direction (TD), — an elongation at break of 400 % or more in MD and 30 % or more in TD, — a heat shrinkage (in water at 90 °C/10s) in MD of 0,49 % or more, but not more than 0,51 %, — a dynamic heat shrinkage (between 55 °C and 70 °C) in TD of not more than 20 percentage points, — a light transmittance of 85 % or more, — a haze ratio of not more than 6 %, — a surface tension of 38 mN/m or more, — a density of 1,30 g/cm ³ or more, but not more than 1,34 g/cm ³ , — a shelf life declared by the manufacturer of not less than 12 months	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9055	ex 3921 19 00	53	Sheets of closed-cell silicone foam with: — a thickness of 2,0 mm or more but not more than 4,8 mm, — a thermal insulation of more than 0,25 Km ² /W but not more than 0,4 Km ² /W (according to ASTM-C518) — a dielectric strength of more than 3,0 Kv/mm but not more than 3,8 Kv/mm (according to ASTM- D149)	0 %	-	31.12.2030
0.9048	ex 5401 10 14	10	Core yarn of high tenacity polyester filament surrounded by polyester staple fibres: — with a twist of 410 TPM or more but not more than 1200 TPM, — with a linear density of 200 dtex or more but not more than 1500 dtex, — with an average tenacity of 46 cN/tex or more, — with an elongation at break of 13 % or more but not more than 23 %, — wound on a perforated dyeing tube, — with a weight, including tube, of 900 g or more	0 %	-	31.12.2030
0.9003	ex 5402 20 00	07	High tenacity polyester multifilament yarn: — with final twist in Z direction; — with a linear density of 100 dtex or more, but not more than 4000 dtex — with an average minimum tenacity of 64 cN/tex; — with an elongation at break of 12 % or more, but not more than 28 %; — with a shrinkage in 98 °C of 0 % or more, but not more than 3,5 %; — wound on the perforated dyeing tube with 0,9 kg of yarn or more ready for dyeing	0 %	-	31.12.2030
0.9063	ex 5503 90 00	40	Staple fibres with a poly(ethylene terephthalate) core fully encapsulated by polyethylene with: — a linear density of 0,60 dtex or more but not more than 1,60 dtex, — a staple fibre length of 37 mm or more but not more than 44 mm, — an elongation at break of 80 % or more, — a tenacity of 1 cN/dtex or more	0 %	-	31.12.2030
0.8939	ex 5603 94 80	50	Needle-punched spunbond nonwovens, consisting of polyamide fibres individually coated with polyvinylalcohol, containing by weight 20 % or more but not more than 40 % of polyvinylalcohol weighing 400 g/m ² or more	0 %	-	31.12.2030
0.9053	ex 6804 21 00	50	Wheels suitable for grinding, rounding, polishing, aligning or cutting: — composed of metal base and agglomerated synthetic or natural diamonds, — whether or not containing a hole in the centre, — with an external diameter not more than 870 mm, for machines for the manufacture of semiconductor wafers (1)	0 %	-	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.8998	ex 6814 10 00	20	Phlogopite mica tape bonded with silicone resin to a glass fabric reinforced polyethylene film, — with a thickness of 0,10 mm or more but not more than 1,60 mm, — with a width of 500 mm or more but not more than 1200 mm, — a mica content of 80 g/m ² or more but not more than 165 g/m ² , — a tensile strength of 110 N/cm or more but not more than 130 N/cm	0 %	-	31.12.2030
0.9059	ex 7002 20 90	10	Cylindrical shaped glass preforms of high-purity silica glass (quartz): — with an optical core made of germanium-doped silica glass (quartz), intended for the production of low-loss optical fiber: — with a length of not more than 2500 mm, — with a diameter of 115 mm or more but not more than 139 mm, — on one side with a conical end — on the other side with a handle with a diameter of 25,4 mm, coated at the end with aluminium oxide	0 %	-	31.12.2030
0.9054	ex 7019 61 00	60	Flexible prepreg in sheets or rolls, — of modified epoxy resin with embedded glass fabric, — without halogenated flame retardants — with a TMA glass transition of 145 °C or more but not more than 200 °C (ASTM E1545) — specified according to IPC-4101/128, 130, 153 or 154	0 %	-	31.12.2030
0.9087	ex 7410 21 00	65	Sheets or Plates — consisting of at least one layer of fiberglass fabric impregnated with modified epoxy resin, without the use of halogenated flame retardants, — covered on one or both sides with copper foil with a thickness of 0,15 mm or less, — and with a TG of 145°C or more but not more than 280°C according to TMA, in agreement with IPC-4101/128 or 4101/130 or IPC-4101/153 or 4101/154	0 %	-	31.12.2030
0.9049	ex 8110 90 00	10	Antimony-Beryllium pellets containing by weight : — 20 % or more but not more than 25 % of beryllium (CAS 7440-41-7) — 77 % or more but not more than 83 % of antimony (CAS 7440-36-0)	0 %	-	31.12.2030
0.9018	ex 8414 30 20	60	Hermetic compressor for R290 refrigerant for the production of refrigerators and freezers: — with a power not exceeding 0.4 kW, — pre-filled with lubricant from 190 ml to 210 ml, — suction and processing pipe inner diameter from 6.40 mm to 6.60 mm, — discharge pipe inner diameter from 4.80 mm to 5.00 mm, — driven by a brushless DC motor, — cooling capacity from 340 to 360 W at ASHRAE LBP 3000 rpm, — displacement from 6.5 cm ³ to 7.5 cm ³ , — speed range from 1,600 rpm to 4,200 rpm (1)	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9045	ex 8414 59 35	50	DC motor centrifugal fan with: — a nominal voltage of 8 V or more, but not more than 13 V, — a nominal maximum speed of 1400 rpm or more, but not more than 1950 rpm, — a horizontal or vertical position of the fan blades shaft, — a boosting time of not more than 10 seconds, — a cable with a length of 30 cm or more, but not more than 50 cm, with RAST 2,5 connector, — a nominal power of 0,7 W or more, but not more than 3,5 W, — a tacho or feedback signal to monitor the speed	0 %	p/st	31.12.2030
0.9044	ex 8418 99 90	70	Household appliances condenser, being a type of heat exchanger, made entirely of aluminium A3102, A3003, A4045 or A4343, consisting of two vertical pipes and arranged horizontally between them 16 parallel flat tubes with fins, with: — one vertical pipe with inlet and outlet tubes, — a width of 297 mm or more, but not more than 373 mm, — a height of 154 mm or more, but not more than 158 mm, — a depth of 17 mm or more, but not more than 23 mm, — a flatness tolerance of less than 2 mm for the fin pack within the condenser core, — a weight of 224 g or more, but not more than 283 g	0 %	-	31.12.2030
0.9023	ex 8483 30 80	30	Commutator end shield (bearing housing with plain shaft bearing) for starter motors of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN AC-46000 or EN AC-46000 S, according to the DIN EN 1706 and GB/T 16116 standards), — with sintered plain bearing	0 %	-	31.12.2030
0.9040	ex 8483 50 80	50	Metal spun single or double pulley: — made of DC03 steel or similar non alloy steel or free cutting steel, — with a pitch diameter of 67 mm or more but not more than 145 mm, — with an inner hole designed for bearing mounting or key mounting	0 %	-	31.12.2030
0.9039	ex 8483 50 80	60	Metal spun triple pulley: — made of DC03 steel or similar non-alloy steel or free cutting steel, — with a pitch diameter of 60 mm or more, but not more than 130 mm, — with an inner hole designed for bearing mounting	0 %	-	31.12.2030
0.9025	ex 8483 60 80	20	Overrunning clutch for passenger car and commercial vehicle starter motors with: — a total length of 49,4 mm or more but not more than 210 mm, — a starter motor pinion with 9 or more but not more than 16 teeth	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9037	ex 8501 52 20	55	Brushless synchronous alternating current electric motors with permanent magnets, with: <ul style="list-style-type: none"> — an output power of 1000 W or more, but not more than 1400 W, — a rotor containing 8 poles, generated by permanent magnets composed mainly of praseodymium-neodymium-iron-boron (GB/T 13560-2017 standard), enclosed in a stainless steel cover, — a motor magnet shaft end outer diameter of 10,001 mm or more, but not more than 10,007 mm, — motor terminals located across the 37,00 mm radius and separated by an angle of 30,00 °, — a motor housing made of ADC12 or EN AC46000 aluminium alloy die casting with composition of aluminium-silicon-copper (per JIS H5302-2000 or EN 1706 standard), — a back electromotive force constant (Ke) of 0,0265 V-sec/rad or more, but not more than 0,0293 V-sec/rad, — a back electromotive force (EMF) harmonic order – 5th of no more than 0,4 % (of fundamental) and 7th of no more than 0,2 % (of fundamental), — a synchronous inductance of 33,49 µH or more, but not more than 37,01 µH, — a cogging torque of not more than 15 mNm, — a friction torque in ambient temperature of not more than 20 mNm, — a maximum motor operation temperature of not more than 200 °C, — with or without a spline on the motor shaft 	0 %	p/st	31.12.2030
0.9020	ex 8503 00 20	20	Plated steel core of the electric motor rotor of electric air conditioning compressors for motor vehicles: <ul style="list-style-type: none"> — with an outer diameter of 65 mm or more but not more than 80 mm, — with an inner diameter of 15 mm or more but not more than 25 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,5 kg or more but not more than 0,8 kg, — without windings 	0 %	-	31.12.2030
0.9019	ex 8503 00 20	30	Plated steel core of the electric motor stator of electric air conditioning compressors for motor vehicles: <ul style="list-style-type: none"> — with an outer diameter of 90 mm or more but not more than 120 mm, — with an inner diameter of 65 mm or more but not more than 80 mm, — with a height of 30 mm or more but not more than 45 mm, — with a weight of 0,7 kg or more but not more than 1,2 kg, — without windings 	0 %	-	31.12.2030
0.9021	ex 8503 00 98	45	Armature for the electric motor in starter motors of passenger cars and commercial vehicles with: <ul style="list-style-type: none"> — an outer diameter of 52 mm or more but not more than 80 mm, — a commutator copper wire diameter of 2 mm or more but not more than 4 mm 	0 %	-	31.12.2030

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9026	ex 8511 90 00	20	Drive end shield for starter motors and alternators of passenger cars and commercial vehicles — produced with high pressure precision die casting technology, — made of aluminium alloy (EN 1706 grade AC-47100 or AC-47100 S or AC-46000 or AC-46000 S or AC-44300), — whether or not with bearing	0 %	-	31.12.2030
0.9022	ex 8511 90 00	30	Commutator for passenger car and commercial vehicle starter motors — with a length of 27,7 mm or more but not more than 44,6 mm, — with umbrella or drum design	0 %	-	31.12.2030
0.9043	ex 8516 80 80	10	Electric heating resistor with a triple loop design: — mainly made of AISI 316L stainless steel, — with a rated voltage of 230V, — with a rated power of 2000W, — with a total heating element length of 217 mm or more, but not more than 223 mm, — with a heating element working length of 169,5 mm or more, but not more than 174,5 mm, — with a mounting flange diameter of 28 mm or more, but not more than 32 mm, — with a heating element bending radius of 10,75 mm, — equipped with thermal fuses, — without a built-in NTC sensor, — with nickel plated terminal pin and connector	0 %	-	31.12.2030
0.9014	ex 8544 30 00	23	High-voltage single-core battery supply cable fitted with: — a high-voltage connector, — a metal flat lug with an eyelet in a plastic housing, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2030
0.9000	ex 8544 30 00	33	Wiring harness for transmitting safety parameters from battery modules fitted with: — input and output connectors, — three or more plastic mounting clips for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2030
0.9002	ex 8544 30 00	43	High voltage battery cable assembly, comprising: — a single core high voltage cable terminated with a flat lug, — a safety fuse for an electric current of 10 A or more but not more than 400 A, — a flat copper conductor with surface insulation terminated with a flat lug, — three or more plastic clips for attachment for use in the manufacture of rechargeable batteries for hybrid and electric vehicles (1)	0 %	-	31.12.2030
0.9027	ex 8547 90 00	10	Li-ion battery module component made of mica for fire protection, with a specially designed shape for the top and sides with: — a length of 480.0 or more but not more than 630.0 mm, — a width of 78.0 or more but not more than 233.0 mm and — a thickness of 0.75 or more but not more than 2.50 mm	1.85 %	-	31.12.2026

Serial Number	CN code	TARIC	Description	Rate of autonomous duty	Supplementary Unit	Deadline foreseen for mandatory review
0.9038	ex 8548 00 90	45	Electromagnetic Interference filter designed to eliminate conducted electromagnetic interference from a power line, — with a rated voltage of 250 V AC, — with a rated current of not more than 15 A, — with an operating frequency of 50/60 Hz, — with a dielectric strength of 1500V AC for 1 minute, — containing a bleeder resistor with a resistance of 470 kΩ, — containing three varistors: one with rated voltage of 680 V, one of 910 V and one of 1800 V, each ±10 %, — mounted with an M8 screw with an average breaking force of 93 kgf/cm	0 %	-	31.12.2030
0.9033	ex 8708 94 99	80	Blank assembly worm gear, consisting of a hub of carbon steel (GB/T 699 grade 25 or DIN EN 10277 grade 11SMn30) and a ring of cast polyamide 6/12 with: — an outer diameter of 97,35 mm or more, but not more than 102,65 mm, — an inner diameter of 27,91 mm or more, but not more than 27,93 mm, — a height of the hub of 11,75 mm or more, but not more than 12,00 mm, — an overall height of 16,00 mm or more, but not more than 18,00 mm	0 %	-	31.12.2030
0.9029	ex 8708 99 97	27	Inner pole electromagnet core used in Magneto-Rheological engine mounts to reduce shocks and for isolation and damping in passenger cars: — of a powder metal assembly, — with a diameter of not more than 90,95 mm, — with an overall height of 24,5 mm, — impregnated with sealant, — zinc plated	0 %	-	31.12.2030
0.9030	ex 9401 99 20	30	Latch seat system modules enabling seat sliding, latching and unlatching in random, independent positions along the rails: — with an integrated safety locking mechanism, — with a cassette architecture for integration with seat through screw connections, — with a housing made of a magnesium die-cast alloy, — with an anti-noise system, — interfacing with car rail systems, — without electronic control unit, — without semiconductors, — with a weight of 1475 g or more, but not more than 1619 g	0 %	-	31.12.2030

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.⁷.